

CheckFire
GROUP



Contents

2	Introduction
4	Commander Fire Extinguishers
14	CommanderEDGE Fire Extinguishers
26	Contempo Fire Extinguishers
34	Trolleys and Covers
36	Stands
38	Cabinets
39	Signs
42	Alarms
43	Fire Protection Products

From our family to yours

CheckFire was established in 1975, when it operated as a small family business from a garage in the family home. Today, we are almost unrecognisably a bigger company, yet we remain committed to family values more so than ever. Care, trust and passion are at the core of everything we do.

And we are still 100% trade-only suppliers. That means you can trust us to not only provide the products you require but also offer a comprehensive service alongside them. You can be confident that, in turn, you're offering the best possible service to your customers. As the market leader, CheckFire is proud to offer an unprecedented level of support to the fire trade. The fog of regulations in the industry can often prove confusing. We can guide and assist you with our unrivalled industry knowledge and technical expertise.

CheckFire only stocks the most trusted and reliable fire safety equipment. We're a long-standing supplier of the dependable Commander and CommanderEDGE fire extinguishers - many of which offer the trusted BSI kitemark to demonstrate the highest quality. Look to the exquisite Contempo range for beautifully hand-finished extinguishers to complement the finest interior design. Plus, we're the go-to provider of high-performance ancillary products too. Our broad range includes an industry-leading selection of extinguisher cabinets, as well as trolleys and fire point stands, to provide peace of mind your fire safety equipment is protected from the elements and accidental damage.



CheckFire
GROUP

CheckFire
GROUP

CheckFire
TRADE COUNTER
CUSTOMER
COLLECTION
POINT



... safety pin



Free hose
Aim nozzle
at base of fire



Squeeze handles



Tested to BS EN3-7. Safe for inadvertent use on live electrical fires up to 1000V
CAUTION:
Depressurise and recharge after any use.
Check weight at least once a year.
Protect from frost.

COMMANDER®

CheckFire Ltd, Caerphilly, CF83 3HU



BS EN3
KM 50330



RECHARGE AFTER USE
THIS EXTINGUISHER SHOULD
SERVICED AT LEAST ONCE
A QUALIFIED COMPETENT
ACCORDANCE WITH BS
RECHARGING SHOULD BE
OUT TO BS 6643 PART 1
COMPONENTS RECOMMENDED
THE MANUFACTURER

MODEL WSWX6 (WBR)
EXTINGUISHER MEDIUM
OPERATING TEMPERATURE RANGE
TEST PRESSURE 27 BAR (NITROGEN)
PRESSURISING GAS NITROGEN



With one of the widest ranges available on the market today, Commander is firmly regarded as a true market leader.

Time has proved these portable fire extinguishers as a dependable choice for almost any situation and reliable performance is guaranteed. What's more, the 6ltr/kg and 9ltr/kg units now carry the BSI Kitemark certification.

Commander Water Fire Extinguishers

A water-based fire extinguisher is a popular choice for Class A fires (combustible materials). Water fire extinguishers work by cooling the fuel and ensuring it burns at a much slower pace until the fire is extinguished.

Most premises are required to have a water or foam extinguisher - they're often found in busy places like offices, schools and hospitals. With a low-cost price and ease of maintenance, it's easy to see why water fire extinguishers are a preferred choice for many businesses. The Commander range of water fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products



3ltr Water Compact PLUS

CODE	WSEX3A
CAPACITY	3 LITRE
FIRE RATING	13A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN

6ltr Water PLUS Spray

CODE	WSWX6
CAPACITY	6 LITRE
FIRE RATING	21A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



9ltr Water PLUS Spray

CODE	WSWX9
CAPACITY	9 LITRE
FIRE RATING	27A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN





Commander Foam Fire Extinguishers

Most commonly used on Class B fires (flammable liquids), a foam fire extinguisher is also a recommended choice for Class A risk areas (those featuring combustible materials). These extinguishers perform a cooling function and quickly smother burning materials, while the foam agent helps prevent the fire reigniting.

Foam fire extinguishers shouldn't be used on kitchen fires or those with an electrical source. However, they're ideal for office environments, hospitals, schools and other spaces where organic materials play a large role in the landscape. The Commander range of foam fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products



**1ltr
AFF Foam**

CODE FSEX1
CAPACITY 1 LITRE
FIRE RATING 5A 21B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**3ltr
AFF Foam**

CODE FSEX3
CAPACITY 3 LITRE
FIRE RATING 13A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 12 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6ltr
AFF Foam**

CODE FSWX6
CAPACITY 6 LITRE
FIRE RATING 21A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr
AFF Foam**

CODE FSWX9
CAPACITY 9 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





AFF Foam

Safe for use on:
Class A
Class B

Safe for use on:
Flammable liquid fires
Flammable solid fires

DO NOT use on:
Electrical fires
Flammable water fires

Water

Safe for use on:
Class A

DO NOT use on:
Electrical fires
Flammable liquid fires
Flammable solid fires

Foam

FIRE EXTINGUISHER
6 Litre FOAM SPRAY
21A 144B

For use on burning liquid fires (Class B) and wood, paper, textile and plastic (Class A) fires.

Use upright
Pull out safety pin
Free hose
Aim nozzle at base of fire
Squeeze handles

COMMANDER

Water
PLUS

FIRE EXTINGUISHER
6 Litre WATER SPRAY PLUS
21A

For use on wood, paper, textile and plastic (Class A) fires.

Use upright
Pull out safety pin
Free hose
Aim nozzle at base of fire
Squeeze handles

COMMANDER



Commander Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile. It's suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers. This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen.

A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. The Commander range of powder fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products



**3kg ABC
Dry Powder**

CODE DPEX3
CAPACITY 3KG
FIRE RATING 13A 89B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6kg ABC
Dry Powder**

CODE DPWX6
CAPACITY 6KG
FIRE RATING 43A 223B C
EXTINGUISHER MEDIUM ABC 30
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9kg ABC
Dry Powder**

CODE DPWX9
CAPACITY 9KG
FIRE RATING 55A 233B C
EXTINGUISHER MEDIUM ABC 30
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





Commander Wet Chemical Fire Extinguishers

A wet chemical fire extinguisher is specifically designed for use on Class F fires (cooking oils and fats), making it the ideal solution for the demands of commercial kitchen and canteen environments.

This type of extinguisher works by creating a layer of foam on the burning oil or fat, stopping the supply of oxygen so the fire isn't fuelled any further. Available in a choice of sizes, find the ideal wet chemical fire extinguisher for your requirements. The Commander range of wet chemical fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Corrosion-resistant cylinders
- Polyethylene internal lining
- Full range of spare parts available
- Easy-clean design



3ltr Wet Chemical

CODE
WCEX3

CAPACITY
3 LITRE

FIRE RATING
8A 75F

EXTINGUISHER MEDIUM
WET CHEMICAL

WORKING PRESSURE
7 BAR

TEMPERATURE RANGE
+5-+60°C

CYLINDER MATERIAL
STAINLESS STEEL

PRESSURING GAS
NITROGEN

6ltr Wet Chemical

CODE
WCEX6

CAPACITY
6 LITRE

FIRE RATING
13A 75F

EXTINGUISHER MEDIUM
WET CHEMICAL

WORKING PRESSURE
7 BAR


TEMPERATURE RANGE
+5-+60°C

CYLINDER MATERIAL
STAINLESS STEEL

PRESSURING GAS
NITROGEN



All food must be covered and dated





**Free hose
Aim nozzle
at base of fire**



Squeeze handles



WARNING:
Do not use on liquid fires or live electrical equipment
Depressurise and recharge after any use
Check weight at least once a year
Protect from frost

For use on wood, paper, textile and similar
Class A fires.

COMMANDER EDGE

CHECKFIRE, Pontygwindy Industrial Estate, Caerphilly, UK, CF83 3HU



RECHARGE AFTER USE
THIS EXTINGUISHER SHOULD
SERVICED AT LEAST ONCE
A QUALIFIED COMPETENT PERSON
ACCORDANCE WITH BS EN 37
RECHARGING SHOULD BE DONE
OUT TO BS 6843 PART 1
COMPONENTS RECOMMENDED BY
THE MANUFACTURER

MODEL WS 9E (10)
EXTINGUISHER MEDIUM RATED
OPERATING TEMPERATURE RANGE
TEST PRESSURE 30 BAR (NOMINAL)
PRESSURISING GAS: NITROGEN



With one of the widest ranges available on the market today, CommanderEDGE is firmly established as the market leader.

The range is fully Kitemarked by BSI and is the choice of the professional with its reassuring mixture of performance, quality and value.

CommanderEDGE Water Fire Extinguishers

Ideal for Class A fire risk areas (those featuring combustible materials), water-based extinguishers remain a popular choice for many businesses. Pointed at the base of the fire, this extinguisher releases water to cool the fuel, ensuring it burns at a slow pace until it's completely extinguished.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in six-litre and nine-litre units, CommanderEDGE water fire extinguishers come with a five-year warranty. What's more, the 6ltr Water Compact 34, with additive, boasts a remarkable 34A fire rating, making it an exceptional powerhouse for its light weight. The CommanderEDGE range of water fire extinguishers benefits from great design, a strong plastic base skirt and the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**6ltr
Water**

CODE WS6E
CAPACITY 6 LITRE
FIRE RATING 13A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr Water
Compact 34**

CODE WS6EA
CAPACITY 6 LITRE
FIRE RATING 34A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr
Water**

CODE WS9E
CAPACITY 9 LITRE
FIRE RATING 13A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





			DO NOT use on
			DO NOT use on
			DO NOT use on
			DO NOT use on

CommanderEDGE Foam Fire Extinguishers

This type of extinguisher is an ideal choice for Class A and B risk areas (those featuring combustible materials and flammable liquids). A foam extinguisher performs a cooling function, while a layer of foam floats on top of the burning liquid to prevent reignition.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in two-litre, six-litre and nine-litre units, CommanderEDGE foam extinguishers are a robust and reliable solution for tackling Class A and B fires. Plus, for the environmentally conscious, EnviroFoam's low fluorine content ensures it's less harmful to the environment than regular foams. The CommanderEDGE range of foam fire extinguishers benefits from great design and the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**2ltr
AFF Foam**

CODE FS2E
CAPACITY 2 LITRE
FIRE RATING 8A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
🔒

**6ltr
AFF Foam**

CODE FS6E
CAPACITY 6 LITRE
FIRE RATING 13A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
🔒 Ⓢ

**6ltr
EnviroFoam**

CODE FS6ECO
CAPACITY 6 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
🔒

**9ltr
AFF Foam**

CODE FS9E
CAPACITY 9 LITRE
FIRE RATING 21A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
🔒 Ⓢ

EniroFoam

Foam

FIRE EXTINGUISHER

6 Litre FOAM SPRAY
27A 183B

For use on burning liquid fires (Class B) and wood, paper, textile and similar Class A fires



Use upright
Pull out safety pin



Free hose
Aim nozzle
At base of fire



Squeeze handles



CAUTION:

Tested to BS EN3-7 safe for inadvertent use on electrical fires.
Depressurise and recharge after any use.
Check weight at least once a year. Protect from frost

COMMANDER EDGE

CheckFire, Caerphilly, CF83 3HU

CommanderEDGE Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile, suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers.

This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen. A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. This range benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**1kg ABC
Dry Powder**

CODE DP1E
CAPACITY 1KG
FIRE RATING 8A 34B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**2kg ABC
Dry Powder**

CODE DP2E
CAPACITY 2KG
FIRE RATING 13A 70B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**4kg ABC
Dry Powder**

CODE DP4E
CAPACITY 4KG
FIRE RATING 21A 89B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6kg ABC
Dry Powder**

CODE DP6E
CAPACITY 6KG
FIRE RATING 34A 233B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9kg ABC
Dry Powder**

CODE DP9E
CAPACITY 9KG
FIRE RATING 55A 233B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





CommanderEDGE MultiCHEM Fire Extinguishers

For an innovative fire-fighting solution, choose the latest in high-performance multi-class extinguishers.

MultiCHEM is an ABF-rated extinguisher ideal for flammable liquid fires involving large quantities of fuel and a big surface area. But it's also suitable for deep fat fryer fires too.

The extinguisher's 34A rating – the industry's highest for a six-litre extinguisher – means that it's capable of tackling a sizeable fire. This ground-breaking extinguisher is also available in two and three litre sizes, as well as unique, aesthetically pleasing finishes, to perfectly tailor to your needs. This range benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



2ltr MultiCHEM

CODE
FS2EMC

CAPACITY
2 LITRE

FIRE RATING
8A 70B 25F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



3ltr MultiCHEM

CODE
FS3EMC

CAPACITY
3 LITRE

FIRE RATING
13A 89B 40F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



6ltr MultiCHEM

CODE
FS6EMC

CAPACITY
6 LITRE

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN





Multi Class
Foam

Multi Class
Foam
FIRE EXTINGUISHER
6 LITRE FOAM
34A 233B 75F

Use upright
Pull and pin

Free hose
Also reaches all types of fire
no closer than 1 metre

Squeeze handle and
sweep across contents
to total area of fire

Multi
CHEM

COMMANDER EDGE

CommanderEDGE CO2 Fire Extinguishers

A carbon dioxide (CO2) extinguisher is the perfect choice for Class B fires (those involving flammable liquids). However, it's also suitable for use on electrical fires because it won't damage electrical equipment or machinery. Carbon dioxide suffocates a fire and displaces oxygen in the air.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. These CO2 extinguishers are among the finest on the market. Aluminium or alloy squat bodies (in the 2kg models) allow for ease of handling, while in the 5kg models, you can rely on a best-in-class 89B fire rating. The CommanderEDGE range of CO2 fire extinguishers benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Distinctive black horn
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products

			
2kg CO2	5kg CO2	2kg CO2 Aluminium	5kg CO2 Aluminium
CODE CO2E	CODE CO2E	CODE CO2EA	CODE CO2EA
CAPACITY 2KG	CAPACITY 5KG	CAPACITY 2KG	CAPACITY 5KG
FIRE RATING 34B	FIRE RATING 70B	FIRE RATING 34B	FIRE RATING 89B
EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2
WORKING PRESSURE 56 BAR @ 20°C			
TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C
CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALUMINIUM	CYLINDER MATERIAL ALUMINIUM
 	 	 	 



     
CO₂

CO₂
FIRE EXTINGUISHER
2kg CARBON DIOXIDE
348

-  Use upright
-  Pull out safety pin
-  Lift horn and aim at base of fire
-  Squeeze handles

CAUTION: This unit contains 2.5 kg CO₂ gas under pressure. Do not use on electrical equipment. Do not use on clothing. Do not use on the face. Check supplier's literature for full details.
COMMANDER EDGE
DAKEN, Portugal's Industrial Estate, Casimiro 10, 2010



Use upright.
Pull out safety pin.



Free hose.
Aim nozzle at base of fire.



Squeeze handles.



CAUTION:

Do not use on live electrical equipment.
Despressurise and recharge after every use.
Check weight at least once a year.
Protect from frost.





A fire extinguisher is a vital piece of equipment and, for any space that particularly prides itself on its aesthetic, the Contempo range – an industry first – has arrived.

The very finest interior finishes are beautifully researched and designed. Contempo provides stunning hand-finished extinguishers to complement the most exquisite interior – and nine-litre models can be available on request.

Contempo Polished Gold

Synonymous with luxury, these hand-finished polished gold extinguishers serve as a stunning addition to elegant interiors.

Whether you are fitting out a stately home, palace or a castle, these extinguishers are a perfect solution. These are electro plated to give a stunning mirror finish. And with the matching polished gold tubular stands and ID signs, this range truly is elegance in fire defence. The Contempo range of Polished Gold fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- 9ltr models available. More information on request.



**2kg CO2
Polished Gold**

CODE
COEX2PG

CAPACITY
2KG

FIRE RATING
34B

EXTINGUISHER MEDIUM
CO2

WORKING PRESSURE
56 BAR @ 20°C

TEMPERATURE RANGE
-20+60°C

CYLINDER MATERIAL
ALLOY STEEL

**6ltr AFF Foam
Polished Gold**

CODE
FSEX6PG

CAPACITY
6 LITRES

FIRE RATING
13A 144B

EXTINGUISHER MEDIUM
AFF FOAM

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN

**6ltr MultiCHEM
Polished Gold**

CODE
FSEX6MCPG

CAPACITY
6 LITRES

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN

**6ltr Water
Polished Gold**

CODE
WSEX6PG

CAPACITY
6 LITRES

FIRE RATING
13A

EXTINGUISHER MEDIUM
WATER

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN

**6kg Powder
Polished Gold**

CODE
DPEX6PG

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



Contempo Antique Copper

Truly an industry-first, these exquisite extinguishers have been hand-finished. Each one is unique in its beauty.

Perfect for modern bars and restaurants, luxury hotels and contemporary commercial interiors, this is fire safety equipment that deserves to be on show. And with the matching brushed Antique Copper tubular stands and ID signs, this range exudes elegance as well as providing all the practical features and meeting industry standards. This unique range benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)



**2kg CO2 Brushed
Antique Copper**

CODE COEX2AC
CAPACITY 2KG
FIRE RATING 34B
EXTINGUISHER MEDIUM CO2
WORKING PRESSURE 56 BAR @ 20 C
TEMPERATURE RANGE -20+60°C
CYLINDER MATERIAL ALLOY STEEL

**6ltr AFF Foam
Antique Copper**

CODE FSEX6AC
CAPACITY 6 LITRES
FIRE RATING 13A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6ltr MultiCHEM
Antique Copper**

CODE FSEX6CAC
CAPACITY 6 LITRES
FIRE RATING 34A 233B 75F
EXTINGUISHER MEDIUM FOAM
WORKING PRESSURE 12 BAR
TEMPERATURE RANGE -5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6ltr Water
Antique Copper**

CODE WSEX6AC
CAPACITY 6 LITRES
FIRE RATING 13A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6kg Powder
Antique Copper**

CODE DPEX6AC
CAPACITY 6KG
FIRE RATING 34A 233B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



		Safe for use on wood, paper, fabric and other Class A fires		DO NOT use on electrical fires			Safe for use on wood, paper, fabric and other Class A fires
		DO NOT use on flammable liquid fires		DO NOT use on flammable metal fires			Safe for use on electrical fires
		DO NOT use on flammable metal fires		DO NOT use on flammable metal fires			DO NOT use on flammable liquid fires
		DO NOT use on flammable metal fires		DO NOT use on flammable metal fires			DO NOT use on flammable metal fires

WATER

FIRE EXTINGUISHER

6 Litre WATER 13A

For use on wood, paper, fabric and other Class A fires.

- Use on wood, paper, fabric and other Class A fires.
- Do not use on electrical fires.
- Do not use on flammable liquid fires.
- Do not use on flammable metal fires.

CONTEMPO

CAUTION:
Do not use on live electrical equipment. Always disconnect power before use. Do not use on flammable metal fires. Do not use on flammable liquid fires. Do not use on flammable metal fires.

CO2

FIRE EXTINGUISHER

5kg CARBON DIOXIDE 340

For use on electrical fires, flammable liquid fires, and flammable metal fires.

- Use on electrical fires.
- Use on flammable liquid fires.
- Use on flammable metal fires.

CONTEMPO

CAUTION:
Do not use on live electrical equipment. Always disconnect power before use. Do not use on flammable metal fires. Do not use on flammable liquid fires. Do not use on flammable metal fires.



Contempo Stainless Steel

With a superb highly polished finish, luxury stainless steel extinguishers are perfect for areas where appearance is important.

Stainless steel is one of the most corrosion-resistant metals known, as well as being extremely strong. That means these units are among the toughest available and are proven to last – even in the harshest of environments. The Contempo range of Stainless Steel fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- We also have 9ltrs available in the range



**2kg CO2
Stainless Steel**

CODE
COEX2P

CAPACITY
2KG

FIRE RATING
34B

EXTINGUISHER MEDIUM
CO2

WORKING PRESSURE
56 BAR @ 20°C

TEMPERATURE RANGE
-20+60°C

CYLINDER MATERIAL
ALLOY STEEL



**6ltr AFF Foam
Stainless Steel**

CODE
FSEX6SS

CAPACITY
6 LITRES

FIRE RATING
13A 144B

EXTINGUISHER MEDIUM
AFF FOAM

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr MultiCHEM
Stainless Steel**

CODE
FSEX6MCSS

CAPACITY
6 LITRES

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
ALLOY STEEL

PRESSURE GAS
NITROGEN



**6ltr Water
Stainless Steel**

CODE
WSEX6SS

CAPACITY
6 LITRES

FIRE RATING
13A

EXTINGUISHER MEDIUM
WATER

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6kg Powder
Stainless Steel**

CODE
DPEX6SS

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



GOOD
VIBES
ONLY

Trolleys and Covers

Fire extinguisher trolleys and covers help to protect vital fire fighting equipment from corrosion, accidental damage and misuse.



Double Trolley

CODE
CS23

WEIGHT
16KG

DIMENSIONS (WHD)
1200 X 720 X 400MM

FIRE EXTINGUISHERS
2

ROBUST POWDER COATED
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /
SITE ALARM

CAN BE ADAPTED
TO HOLD CO2 FIRE
EXTINGUISHERS



Compact Double Trolley

CODE
CS23A

WEIGHT
14KG

DIMENSIONS (WHD)
1200 X 470 X 400MM

FIRE EXTINGUISHERS
2

ROBUST POWDER COATED
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /
SITE ALARM

COMPACT, SPACE SAVING
DESIGN



Backboard Double Trolley

CODE
CS23-DF

WEIGHT
16KG

DIMENSIONS (WHD)
1200 X 720 X 400MM

FIRE EXTINGUISHERS
2

ROBUST POWDER COATED
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /
SITE ALARM

A LARGE STEEL
BACKBOARD FOR
MOUNTING ALARM
EQUIPMENT AND SIGNAGE



Mobile Fire Point Stand

CODE
CS26A

WEIGHT
20KG

DIMENSIONS (WHD)
1800 X 890 X 480MM

FIRE EXTINGUISHERS
4

ROBUST POWDER COATED
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /
SITE ALARM

A LARGE STEEL
BACKBOARD FOR
MOUNTING ALARM
EQUIPMENT AND SIGNAGE

ALSO AVAILABLE IN
YELLOW AND GREEN



PVC Extinguisher Cover (Medium)

CODE
CS22

FITS UP TO 6KG / 6LTR
FIRE EXTINGUISHERS

QUALITY PVC MATERIAL

CLEAR VIEWING WINDOW

VELCRO STRAPS TO
ALLOW FOR EASE OF
FITTING AND SECURING



PVC Extinguisher Cover (Large)

CODE
CS21

FITS UP TO 9KG / 9LTR
FIRE EXTINGUISHERS

QUALITY PVC MATERIAL

CLEAR VIEWING WINDOW

VELCRO STRAPS TO
ALLOW FOR EASE OF
FITTING AND SECURING



Fire
assembly p

FIRE ALARM



COMMANDER

Water

FIRE EXTINGUISHER
8 LITRES WATER
12 A

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles

For use on wood, paper, textiles and some
Class B fires.
Based on BS 5037. Safe to use on all materials
mentioned in BS 5037.

COMMANDER EDGE

Powder

FIRE EXTINGUISHER
10kg ABC POWDER
BSA 2338 C

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles



For use on all fire classes A, B & C
including petrol fires and electrical fires
including on equipment and
structures not covered by BS 5037
Do not use on live wires.

COMMANDER EDGE

Stands

Fire extinguisher stands are a versatile solution for display where wall-mounting might not be appropriate.



Single Tubular Stand

CODE CS30
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Double Tubular Stand

CODE CS31
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Single Tubular Stand

CODE CS32
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Double Tubular Stand

CODE CS33
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Commander Single Extinguisher Stand

CODE CS50
WEIGHT 1.2KG
DIMENSIONS 280 X 750 X 275MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



Commander Double Extinguisher Stand

CODE CS51
WEIGHT 2.3KG
DIMENSIONS 548 X 750 X 288.5MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



Wave Wall Extinguisher Stand

CODE WAVE/RED
WEIGHT 1.90KG
DIMENSIONS 386 X 234 X 400MM
SUITABLE FOR MAX DIAMETER 135-200MM
SOLID STRUCTURE FIVE FIXING POINTS
AVAILABLE IN RED AND WHITE



Cabinets

Safely store fire extinguishers in a cabinet that protects against accidental damage, misuse and all-weather conditions.



Single Commander Cabinet

CODE
CS01DA9

CAPACITY
9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)
335 X 715 X 240MM

INTERNAL DIMS (WHD)
264 X 652 X 204MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

Single Cabinet Extended

CODE
CS02DA

CAPACITY
9KG/9LTR/5KG CO2

EXTERNAL DIMS (WHD)
335 X 865 X 240MM

INTERNAL DIMS (WHD)
264 X 816 X 204MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

Double Cabinet

CODE
CS03 DA

CAPACITY
2 X 9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)
616 X 735 X 270MM

INTERNAL DIMS (WHD)
530 X 700 X 229MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

LOCKABLE

ALSO AVAILABLE IN YELLOW AND GREEN

Commander Double Lockable Cabinet

CODE
CS03A DA

CAPACITY
2 X 9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)
616 X 735 X 270MM

INTERNAL DIMS (WHD)
530 X 700 X 229MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

LOCKABLE

Vehicle Extinguisher Cabinet 6kg / 9kg

CODE
CS04 DA / CS05 DA

WEIGHT
2.1KG

EXTERNAL DIMS (WHD)
265X284X595MM

INTERNAL DIMS (WHD)
224X224X561MM

EXTINGUISHER DIAMETER
140/160MM

NYLON TENSION SPRING (Ø 140/160 MM)

EXTRA TENSION SPRINGS* < Ø 140 MM(Ø 140/160 MM)

NYLON HANDLE SEALABLE OR LOCKABLE

REINFORCED AND NON DEFORMABLE STRUCTURE

INTERNAL TPE SEAL AGAINST WATER AND DUST

BRACKETS CAN BE MOUNTED ON ANY SIDE

*OPTIONAL

Commander Safety Box

CODE
CS60

CAPACITY
4 X 6LTR/6KG

EXTERNAL DIMS (WHD)
655 X 520 X 570MM

INTERNAL DIMS (WHD)
536 X 420 X 537MM

INTERNAL TPE SEAL AGAINST DUST AND WATER INGRESS

HIGH RESISTANCE TO: WATER AND DUST INGRESS, UV RAYS, HIGH AND LOW TEMPERATURES

SMOOTH, FLAT ROOF FOR SIGN APPLICATION

ERGONOMIC SIDE HANDLES FOR EASY CARRYING

ALSO AVAILABLE WITH COMMANDER CONTACT ALARM – SEE PAGE 42

Fire Extinguisher Signs

Fire extinguisher ID signs clearly identify the location of fire extinguishers within a building and inform users of their contents. Signs are available on white rigid plastic and can be photoluminescent to ensure visibility in all conditions.



Water ID Sign

CODE
101P / 111P

SIZES
75 X 200MM
150 X 100MM

Foam ID Sign

CODE
102P / 112P

SIZES
75 X 200MM
150 X 100MM

CO2 ID Sign

CODE
103P / 113P

SIZES
75 X 200MM
150 X 100MM

Powder ID Sign

CODE
104P / 114P

SIZES
75 X 200MM
150 X 100MM

Wet Chemical ID Sign

CODE
105P / 115P

SIZES
75 X 200MM
150 X 100MM

Fire Blanket ID Sign

CODE
106P / 116P

SIZES
75 X 200MM
150 X 100MM

MultiCHEM ID Sign

CODE
107P / 117P

SIZES
76 X 200MM
150 X 100MM

Emergency Escape Signs

Clearly demonstrate where the nearest emergency exit is situated to direct people safely off the premises.



**Fire Exit
(Right) Sign**

CODE
201P / 211S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Up) Sign**

CODE
202P / 212R

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Down) Sign**

CODE
203P / 213S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Left) Sign**

CODE
204P / 214S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Up Left) Sign**

CODE
207P / 217P

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Down Right) Sign**

CODE
205P / 215S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Up Right) Sign**

CODE
206P / 216S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Down Left) Sign**

CODE
208P / 218P

SIZES
300 X 100MM
450 X 150MM



**Final Fire
Exit Sign**

CODE
301P

SIZE
300 X 150MM



**Final Fire Exit
(Man Left) Sign**

CODE
302R

SIZE
300 X 150MM



**Final
Exit Sign**

CODE
303R

SIZE
300 X 150MM



**Final Exit
(Man Left) Sign**

CODE

SIZE
300 X 150MM



**Push Bar To
Open Sign**

CODE
306P / 307R / 315S

SIZES
300 X 100MM
450 X 150MM
300 X 150MM
600 X 75MM



**Push Pad To
Open Sign**

CODE
308R

SIZE
300 X 100MM



**Fire Assembly
Point Sign**

CODE
702R 712R

SIZE
400 X 300MM
600 X 400MM



**Fire Exit
Keep Clear Sign**

CODE
309R / 310P

SIZES
450 X 150MM
200 X 200MM

Fire Action, Equipment and Door Signs

Ensure all users of the building are aware of the location of vital fire-fighting equipment and fire doors and understand exactly what action to take.



Fire Action Standard Sign

CODE
401P
SIZE
150 X 200MM



Fire Action Picto Sign

CODE
402P
SIZE
150 X 200MM



Fire Alarm Call Point Sign

CODE
501P
SIZE
150 X 200MM



Fire Extinguisher Sign

CODE
502P
SIZE
150 X 200MM



Fire Hose Reel Sign

CODE
503P
SIZE
150 X 200MM



Fire Point Sign

CODE
504P
SIZE
150 X 200MM



Call Point Picto Sign

CODE
505P
SIZE
100 X 100MM



Fire Extinguisher Picto Sign

CODE
506P
SIZE
100 X 100MM



Fire Alarm Call Point Sign

CODE
511R
SIZE
200 X 300MM



Fire Extinguisher Sign

CODE
512R
SIZE
200 X 300MM



Fire Hose Reel Sign

CODE
503P
SIZE
200 X 300MM



Fire Point Sign

CODE
514S
SIZE
200 X 300MM



Automatic Fire Door Sign

CODE
901R
SIZE
100 X 100MM



Fire Door Keep Shut Sign

CODE
902R
SIZE
100 X 100MM



Fire Door Keep Locked Shut Sign

CODE
903R
SIZE
100 X 100MM



Fire Door Keep Closed Sign

CODE
904R
SIZE
100 X 100MM

Alarms

Manually raise the alarm in times of emergency to ensure all users of the building are made aware they should vacate.



Commander Alert Site Alarm

CODE
AE25

WEIGHT
670G

DIMENSIONS (WHD)
170 X 250 X 80MM*

ALARM SOUND LEVEL
115DB

12 LED SUPER BRIGHT STROBE

ABS CASE RESISTS SHOCKS AND DROPS

SIMPLE FITTING AND OPERATION

RADIO LINK MODULE AVAILABLE

IP65 RATED

*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



Commander Alert Site Alarm Wireless

CODE
AE25/W

WEIGHT
670G

DIMENSIONS (WHD)
170 X 250 X 80MM*

ALARM SOUND LEVEL
115DB

12 LED SUPER BRIGHT STROBE

ABS CASE RESISTS SHOCKS AND DROPS

SIMPLE FITTING AND OPERATION

RADIO LINK MODULE AVAILABLE

IP65 RATED

*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



Smoke Alarm

CODE
AE20

WEIGHT
130G

DIMENSIONS (DH)
110 X 370MM

ALARM SOUND LEVEL
85DB

TECHNOLOGY
IONISATION SMOKE SENSOR

BATTERY TYPE
9V ALKALINE

WARRANTY
5 YEARS

CEILING INSTALLATION



Commander Contact Alarm

CODE
AE15

WEIGHT
100G

DIMENSIONS (ØD)
87 X 87 X 43MM

ALARM SOUND LEVEL
85DB-110DB

BATTERY OPERATION
6F22 9V BATTERY

SIMPLE FITTING AND OPERATION

SUITABLE FOR USE ON THE CS60 AND ALL CABINETS OF ALARM FUNCTION



Carbon Monoxide Alarm

CODE
AE23

WEIGHT
115G

DIMENSIONS (ØD)
140 X 35.5MM

ALARM SOUND LEVEL
85DB

BSI KITEMARKED
EN50291

BATTERY OPERATION
3 X AA ALKALINE BATTERIES SUPPLIED AS STANDARD

WARRANTY
5 YEARS

TEST/RESET BUTTON TO ALLOW REGULAR TESTING OF ALARM FUNCTION



Rotary Alarm Bell

CODE
AE01

WEIGHT
1.57KG

DIMENSIONS (ØD)
274MM X 89.4MM

ALARWM SOUND LEVEL
85DB

SUITABLE FOR USE INDOORS AND OUTDOORS

HAND-OPERATED FIRE ALARM BELL

ALUMINIUM ALLOY



Air Horn Alarm

CODE
AE02

ACOUSTIC RANGE
APPROX. 1500M

IDEAL FOR PROVIDING TEMPORARY COVER

IDEAL FOR CONSTRUCTION SITE APPLICATIONS

Intumescent Products

Intumescent sealants, strips and other items help slow down the spreading of fire to provide more time for evacuation of the building.



Intumescent Strip

Intumescent strip is a vital ancillary product for any door. Available as either brush pile or rubber fins, the strip works to seal around vulnerable edges of a fire door. We stock intumescent strip in a range of sizes.



Door Closers

Fire doors must be kept shut at all times to remain a crucial barrier to prevent the spread of smoke and fire. Door closers ensure a fire door is automatically closed after it's been opened. They also help to remove some the weight of this heavy door, meaning they offer a practical solution for certain settings.



Drop Seals

Fire doors require automatic drop-down seals, which provide an effective barrier against climate, noise, light, fire, smoke and insects. Once the door is closed, a plunger-like system ensures the gap between the door and flooring is closed. Choose from a range of seals suitable for glass and timber doors.



Mastic and Foam

These sealants help prevent the spread of smoke and fire. In the event of a fire, fire-resistant expanding foam fills gaps around fire doors, joints and holes in fire-rated structures, while intumescent sealant swells to create a seal.



Grilles

For easy installation in walls and fire doors, intumescent grilles allow ventilation where required and form a barrier to prevent the spread of smoke and fire. Grilles are used to provide fire dampers in ductwork.



Collars and Wraps

Pipes that penetrate fire compartment walls must be fitted with a fire prevention solution – either intumescent pipe collars or wraps. These items are fixed where the pipes intersect the wall or floor and when exposed to heat, expand to plug any gaps.

Ancillary Products

Provide support to vital fire safety equipment with our extensive selection of ancillary products, which are fully compliant with British Standards.



Engineer's Tool Kit (Standard)

CODE
ST49

- 1KG SPRING BALANCE
- 20KG SPRING BALANCE
- TG HEADCAP SPANNER
- BRITANNIA 'C' SPANNER
- ALLEN KEYS
- ADJUSTABLE SPANNER
- GLORIA HEADCAP 'T' BAR
- FIREPOWER HEADCAP 'T' BAR
- GAUGE TESTER MIJA
- STANDARD ENGINEER'S TORCH
- RUBBER MALLET
- NYLON VALVE BRUSH
- BRASS VALVE BRUSH
- 200ML WD40
- 'O' RING REMOVAL TOOL
- PETROLEUM JELLY 200G
- POWDER BLOW OUT BAG



Engineer's Tool Kit (Advanced)

CODE
ST50

- INCLUDES STANDARD ENGINEER'S TOOL KIT PLUS:
- DIGITAL SCALE
- MAGLITE® TORCH
- LED INSPECTION LAMP
- GAUGE TESTER EBUR WIKA
- LEAK DETECTOR SPRAY
- 'V' CLAMP
- PLASTIC FUNNEL



Year Gauge Indicator Dots

CODE
ST03

- SHOWS THE GAUGE HAS BEEN TESTED
- AVAILABLE IN VARIOUS COLOURS AND CLEAR
- IN ACCORDANCE WITH BS5306



Pull Tite Seals

CODE
PS09

- SELF LOCKING SEAL NO TOOLS REQUIRED
- PROTECTS AGAINST TAMPERING AND ACCIDENTAL DISCHARGE
- 10 SEALS PER MAT



Chubb Type Pin and Discs

CODE
PS04

- PIN DIAMETER 7MM
- COLOURS AVAILABLE GREEN, BLUE, YELLOW, RED, WHITE, ORANGE, BLACK



Commander Fire Blankets

CODE
FB01 / FB02 / FB03

- SIZES 1 X 1M, 1.2 X 1.2M, 1.8 X 1.2M
- BLANKET MATERIAL SILICONE COATED FIBERGLASS FABRIC
- OUTER CASE MATERIAL PP CASE



Fire Safety Log Book

CODE
A4LOG / A5LOG

- SIZES A4, A5
- COMPLETED FOLLOWING INSPECTIONS, TESTING AND ANY MAINTENANCE OF FIRE SAFETY EQUIPMENT

Ancillary Products



Service Labels

CODE
ST04

DIMENSIONS
70 X 100MM

RECORD INSPECTION
DETAILS

FULL COLOUR PRINT

SELF-ADHESIVE

BRANDING AVAILABLE



O-rings

CODE
PP144

PIN DIAMETER
7MM

COLOURS AVAILABLE
GREEN
BLUE
YELLOW
RED
WHITE
ORANGE
BLACK



Digital Hand-Held Scales

CODE
ST08

WEIGHT
25KG X 20G

COLOURS AVAILABLE
COMPLETE WITH TARE AND
READING HOLD FACILITY

COLOURS AVAILABLE
BATTERY OPERATED



20ltr Foam Drum Refill

CODE
RP21

A FULL RANGE OF FOAM
FOR ALL APPLICATIONS



20ltr Wet Chem Refill

CODE
CH01

SUITABLE FOR 2KG CO2
FIRE EXTINGUISHERS



CO2 Horns 2KG / 5KG

CODE
CH05

SUITABLE FOR 2KG / 5KG
CO2 FIRE EXTINGUISHERS

WITH A DIRECT SWIVEL
ACTION AND IS EASY
TO FIT ON TO FIRE
EXTINGUISHERS



Plastic Fire Bucket & Lid

CODE
FBK01

CAPACITY
10LTR



CHECKFIRE GROUP

PONTYGWINDY INDUSTRIAL ESTATE, CAERPHILLY, CF83 3HU

T 029 2086 8333

E INFO@CHECKFIRE.CO.UK

CHECKFIRE GROUP IS A COMPANY REGISTERED IN ENGLAND AND WALES WITH COMPANY NUMBER 7990436. VAT NUMBER 144 0143 57