

## Available sizes & Specifications

Model	Length	Weight Kg/m	ID	Wmm	Tape Width
SGX16	20m	0.062	12	2.25	13
SGX20	20m	0.082	15	2.5	15.5
SGX25	20m	0.117	19	2.75	19
SGX32	20m	0.176	23	3.5	23
SGX40	20m	0.293	30.5	4.25	29
SGX50	20m	0.36	38	4.25	36
SGX63	20m	0.583	47	5.5	39.5
SGX75	15m	0.821	61	6	44
SGX90	10m	1.116	70.5	7	51
SGX110	10m	1.428	84	7.5	56

- **Industry**
  - **Agriculture**
  - **Mining, Quarrying**
  - **Oil and Gas**
  - **Power Generation**
  - **Forestry**
  - **Welding**
  - **Robotics**
  - **transport**
- **Application**
  - **Spray units, Power Plants, Articulated Machinery, Harvesters**
  - **Excavators, Transport, Long wall operations, Loaders, Roof Bolters, Drilling Rigs, Blast Hole Rings, Jumbo drill Rigs**
  - **Fuel Distribution Hose, Offshore Oil Rigs**
  - **Engine Bays, Gables & Wire harnesses, Stationary Plant**
  - **Harvesters, Forwarders, Transport Rigs**
  - **Welding Cables & Gas hoses**
  - **Cables, Looms, Remote Arms & Booms**
  - **Articulation, Battery Cables, Brake & Wire harnesses, Fuel Distribution, Chassis rails**

### Key Features

- Rounded edges
- Domed Profile
- Flexible
- UV Stabilized
- Self Lubricating
- High abrasion construction
- FRAS - Flame retardant and anti-static

### Key Benefits

- Improves Workplace and operator safety
- Aids containment of burst hoses
- Easy to fit on site - new or existing
- No need to dismantle assembly
- minimizes industrial injury
- Minimizes machinery downtime
- Extends life of hoses and cables