



05/17/2023

EXHIBIT 110

CTETS_000300



Zero Ozone Depletion Potential
IT IS THE BUYER'S RESPONSIBILITY
CAUTION: This product is combustible.
ESR-3089 CRJ TER 1-06-03 And
if listed accepted to weather cover
for more information, performance

Water Shield
Virt Release

Water Shield
Virt Release



Nominal Board Thickness	1/2"	3/8"	3/4"
R-VALUE	3.5	4.1	5.0

An additional R-2 (7.2 R) may be added to the system R-value when used in conjunction with a 2" rigid insulation and horizontal lead line are present in application. See ASHRAE Fundamentals Handbook and F.T.C. 16CFR Part 460.

CONFORMANCE WITH ALL APPLICABLE CODES AND REGULATIONS.

For thermal barrier installation, see the manufacturer's literature. For questions, call 1-800-250-3263. In an emergency call 1-800-441-3821.

DUPONT



ion

05/17/2023



05/17/2023

EXHIBIT 110

CTETS_000302



05/17/2023

EXHIBIT 110

CTETS_000303



◀ DUPONT ▶
TUFF-R™
Insulation

◀ DUPONT ▶
TUFF-R™
Insulation

DO NOT STEP ON!

DUPONT
TUFF-R™
Insulation

05/17/2023

EXHIBIT 110

PHOTO_000304



05/17/2023



05/17/2023

EXHIBIT 110

CTETS 000306



DUPONT
TUFF-R
Insulation

DUPONT
TUFF-R
Insulation

Insulation

TUFF-R
Insulation

05/17/2023



05/17/2023

EXHIBIT 110

CTETS_000308

UNABLE TO
WRITE ADDRESS
PROPERTY NUMBER 2110

1763
6794



05/17/2023

EXHIBIT 110
Insulation

OTETS 000309

TUFF-R