

Liscotts low quality construction of the front entry. This structure wasn't even secured to the house. Also note the defective installation of siding, flashing and trim throughout these images.









**OWENS CORNING**  
**FOAMULAR NGX**  
HIGH PERFORMANCE XPS INSULATION

**250**  
R-VALUE PER INCH

FOAMULAR NGX is a 100% polystyrene extruded polystyrene (XPS) insulation that meets all federal and state energy efficiency and emission regulations in the USA and Canada.

**R-5**  
PER 1 INCH



**FOR USE IN:**

- EXTERIOR FOUNDATION WALLS
- INTERIOR FOUNDATION WALLS
- EXTERIOR SHEATHING
- CAVITY WALLS
- COMMERCIAL APPLICATIONS

OWENS CORNING FIBERGLASS INSULATION COMPANY  
1000 EAST 10TH AVENUE  
ANN ARBOR, MI 48106  
TEL: 734.769.4000  
WWW.OWENS-CORNING.COM  
© 2010 Owens Corning Fiberglas Insulation Company. All rights reserved. This document is a technical specification and is not intended for general distribution. For more information, please contact your local Owens Corning representative.

**OWENS CORNING**  
**FOAMULAR NGX**  
HIGH PERFORMANCE XPS INSULATION

**250**  
R-VALUE PER INCH

FOAMULAR NGX is a 100% polystyrene extruded polystyrene (XPS) insulation that meets all federal and state energy efficiency and emission regulations in the USA and Canada.



**TUFF-R**  
DOW PONT

**DOW PONT**  
**F-R**  
Membrane









◀ DUPONT ▶  
TUFF-R™  
Insulation

◀ DUPONT ▶  
TUFF-R™  
Insulation

◀ DUPONT ▶  
TUFF-R™  
Insulation





2017-00000

2017-00000

Owens Corning





