

## SAFETY DATA SHEET

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	GPX SERIES
Product Use	Sheet-fed offset printing ink
Manufactured/Distributed by	TOKYO PRINTING INK CORP. USA
Address	2695 Temple Ave., Signal Hill, CA 90755
Telephone	(562) 424-2226
Fax	(562) 424-2216

### 2. HAZARDS IDENTIFICATION

#### UN Hazard Classification


HAZARD CLASS	Not Applicable
UN/NA NUMBER	Not Applicable

#### GHS Classification\*

Physical	Flammable Liquid	Not classified
Health	Acute Toxicity (oral) -	Not classified
	Acute Toxicity (inhalation) -	Category 4
	Eye Corrosion (serious damage/irritation) -	Category 2B
	Skin Corrosion -	Category 2
	Skin Sensitization -	Category 1
	Respiratory sensitizer -	Not classified
	Mutagenicity -	Not classified
	Aspiration Hazard -	Not classified
	Carcinogenicity -	Not classified
	Reproductive Toxicity -	Not classified
Environmental	Target Organ Toxicity (single exposure) -	Category 2
	Target Organ Toxicity (repeated exposure) -	Category 2
	Aquatic Toxicity (acute) -	Not classified
	Aquatic Toxicity (chronic) -	Not classified

\*Classified the product based on Japanese chemical substance registration.

#### GHS Label Elements

Symbols	
Pictogram code	GHS07
	
Signal word	Warning
Hazard Communication	
Hazard Code	
H332	Harmful if inhaled (mist).
H320	Causes eye irritation.
H317	May cause allergic skin reaction.
H335	May cause respiratory irritation.

H371 May cause damage to lungs.

## Prevention

## Summary

Avoid breathing mist **w**ear suitable protective clothing and gloves. After handle this product, wash hands immediately and gargle sufficiently **r**ead well Safety Data Sheets (SDS) before handling **e**lf you feel unwell or allergy, seek medical advice immediately.

## Prevention Code

- P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray  
 P264 Wash thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection  
 P281 Use personal protective equipment as required.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.  
 P314 Get medical advice/attention if you feel unwell.  
 P321 Specific treatment (see Prevention on this label).  
 P363 Wash contaminated clothing before reuse.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local, state and federal regulation.

## Other Precautionary Statements

- Keep away from heat/sparks/open flame. - No smoking.  
 Use only in a well-ventilated area.  
 Store container tightly closed in cool/well-ventilated place.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No 1272/2008 and Directive 67/548/EEC.

COMPOSITION	CONTENT		EU CLP & DSD (Risk) Classification(*)	
	CAS#	wt.%		
Rosin modified phenolic resin	70955-45-2	20- 30	-	-
Vegetable oils mixture ( Ingredient )	Various	20- 30	-	-
Tung oil	8001-20-5		-	-
Soybean oil	8001-22-7		-	-
Petroleum hydrocarbon	64742-46-7	20-30	-	-
Pigment (Black: Carbon black)	1333-86-4	10 - 20	-	-
Pigments (Yellow. Magenta, Cyan)	Various	10 - 20	-	-
Additives	Various	1 - 5	-	-

(\*) For full text of Products EU CLP & DSD see section 15

## 4. FIRST AID MEASURES

**EYE CONTACT** : In case of eye irritation, flush immediately with clean & large amounts of water for at least 15minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get immediate medical attention.

**SKIN CONTACT** : Itching or burning of the skin. Immediately flush the skin with plenty of water while removing contaminated clothing and shoes. Wash skin thoroughly with mild soap / water. Get immediate medical attention. Wash contaminated clothing before reuse.

**INHALATION**: Remove person to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, give artificial respiration.

**INGESTION** : Get immediate medical attention. Do not induce vomiting unless directed by medical personnel.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguish:** Use dry chemical, carbon dioxide, or foam to extinguish fire. Water may be ineffective but should be used spray/fog for cooling and suffocating. Use water to dilute spills and flush them away from sources of ignition.

**Special Fire Fighting Procedures:** Exposed firefighters must wear proper protective equipment and positive pressure self-contained breathing apparatus with full face mask. Do not inhale combustion gases.

**HAZARDOUS DECOMPOSITION PRODUCTS** Products of combustion are hazardous carbon monoxide and Carbon dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

**GENERAL** : Consult an expert on the disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

**LAND SPILL** : Vapor protective clothing should be worn for and leaks. Shut off ignition sources; no flares, smoking or flames in hazard area. Keep public away. Take up with sand or other noncombustible absorbent material and place into containers for later disposal. Prevent additional discharge of productive possible to do so without hazard.

**WATER SPILL** : Remove from surface by skimming or with suitable absorbents. Do not flush to sewer or waterways. Prevent release to the environment if possible.

## 7. HANDLING AND STORAGE

### Handling

Avoid contact with eyes. Avoid prolonged repeated skin contact and breathing mists/vapors. Use only with adequate ventilation. Use good hygiene practices. Wash hands before eating, drinking, smoking. Remove contaminated clothing and clean before re-use. Keep away from heat and flame. Keep operating temperatures below ignition temperatures at all times. Use non-sparking tools.

### Storage

**STORAGE TEMPERATURE** (min. / max. ) : 59°F (15°C) / 86°F (30°C)

**AVERAGE SHELF LIFE** : 2 years at 59°F (15°C)

**SPECIAL SENSITIVITY** : Heat. Air (Oxygen) .

Risk of rapid polymerization / possibly rupturing container by fire, high heat sources, raising temperature.

Store in tightly closed containers in cool, dry, well-ventilated area away from heat, sources of ignition and incompatibles. Ground lines and equipment used during transfer to reduce the possibility of static spark-initiated fire or explosion. Store at ambient or lower temperature. Store out of direct sunlight. Protect against physical damage.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Limits**

Substance	CAS#	OSHA		ACGIH	
		TWA	STEL	TWA	STEL
Petroleum hydrocarbon	64742-46-7	n/e	n/e	5mQ/m <sup>3</sup>	n/e
Carbon black	1333-86-4	3.5mQ/m <sup>3</sup>	n/e	3.5mQ/m <sup>3</sup>	n/e

n/e-none established

OSHA Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200) Carbon black is considered hazardous ingredient (List on "Table Z-1").

ACGIH : Petroleum hydrocarbon (as oil mist) TLV; 5mg/m<sup>3</sup> as TWA [ACGIH2004]. Carbon black TLV ; 3.5mg/m<sup>3</sup> as TWA & A4 (not classifiable as a human carcinogen)(ACGIH2004).

**Engineering Controls**

VENTILATION: Local exhaust ventilation may be necessary to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the sources Provide mechanical ventilation for confined spaces. Use explosion-proof ventilation equipment.

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**

Wear chemical safety splash-proof goggles for eye protection and face shield. Avoid skin contact. Wear impervious gloves for skin protection. Use NIOSH approved respirators when necessary.

**9. PHYSICAL and CHEMICAL PROPERTIES**

APPEARANCE : Viscous Paste

Color : Various Colors

ODOR : Mild

FLASH POINT : &gt; 132°C / 270°F

BOILING POINT : 270-320°C (Mineral oil)

MELTING POINT : Not Applicable

VAPOR PRESSURE : No Data Available

VAPOR DENSITY (AIR=1) : No Data Available

MOLECULAR FORMULA : Mixture

MOLECULAR WEIGHT : Mixture

SPECIFIC GRAVITY : 0.9-1.2 at 25°C / 77°F

SOLUBILITY IN WATER : Insoluble

pH : No Data Available

**10. STABILITY AND REACTIVITY**

Condition to avoid: Avoid open flames, welding arcs, or other high temperature sources which include thermal decomposition.

Incompatibles: Oxidizing agents

Hazardous Reactions/Decomposition Products: Reacts with strong oxidizing agents. Thermal decomposition products may include oxides of carbon and nitrogen.

**11. TOXICOLOGICAL INFORMATION****Corrosive and Irritant Properties**

Petroleum hydrocarbon  
 Oral LD50 (rat) > 5,000mg/kg  
 Dermal LD (rabbit) > 5,000mg/kg  
 Inhalation LD50 (rat) = 2.18mg/L

Cobalt compound  
 Oral LD50 (rat) = 3900mg/kg

Petroleum Hydrocarbon

Acute Toxicity (inhalation) - Category 4

Skin Corrosion/irritation- Category 3  
Eye Corrosion/irritation- Category 2B  
Aspiration hazard – Category 1  
Target Organ Toxicity (following single exposure) – Category 2  
Target Organ Toxicity (following repeated exposure) – Category 1

#### Carbon Black -GHS Information

Carcinogenicity – Category 2\*\*

\*\* Classified on the basis of evaluation as Group 2B (Possibly carcinogenic to humans) according to IARC. Printing inks are not classifiable as to their carcinogenicity to humans (Group 3).

Target Organ Toxicity (following repeated exposure) - Category 1  
Causes damage to lungs.

#### Cobalt compound

Skin Sensitization – Category 1

Carcinogenicity – Category 2\*

\* IARC: Cobalt and compounds are possibly carcinogenic to humans (Group 2B). But the material concerned was not classified so that there was the description of "There is *inadequate evidence* for the carcinogenicity of cobalt--- and cobalt [III] acetate in experimental animals." (4.5 Evaluation of IARC Monographs/mono52-16.11 /10/09)

Other evaluations of Carcinogenicity are not applicable by EPA, Euan NTP.

## 12. ECOLOGICAL INFORMATION

No information available  
GHS Information - Not classified

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State and local regulations.  
Empty containers must be handled with care due to product residue.

## 14. TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)  
Proper SHIPPING NAME: Not applicable  
HAZARD CLASS: Not applicable  
UN/NA NO: Not applicable  
Packing Group: Not applicable  
Labels Required: Not applicable

The following description is transport in accordance with ADR for road. RID for rail. IMDG for sea and ICAO for air transport.

ADR/RID/IMDG/ICAO/IATA Class: Not applicable  
UN Number: Not applicable  
Label: Not applicable  
Packing group: Not applicable  
Proper SHIPPING NAME: Not applicable

## 15. REGULATORY INFORMATION

(1). U.S. Federal Regulations  
Toxic Substances Control Act (TSCA) information

All components of these products are included on the 8 (b) TSCA Inventory lists.

#### Superfund Amendments and Reauthorization Act (SARA) Title III Information

These products contain none of the substances subject to reporting requirements of SARA section 313 (40 CFR 372)

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

	Health: 1
	Flammability: 1
	Reactivity: 0

#### (2). EU Regulations

European inventory of Existing Chemicals (EINECS): All of the components of this product are included on EINEC

The following information is based on current EU (directives 67/548/EEC – 28th update [2001/59/EC]. 1999/45/EC. 2001/58/EC and CLP Hazard classification [Regulation (EC) No 1272/2008]).

#### EU CLP & DSD Classification:

Designation according to EC guidelines in label:

CLP	CLP Hazardous substance: none
	CLP Classification: No classification standards applicable
DSD	Contains [Cobalt driers]. May produce allergic skin reactions:
	S: 7-24/25-26-28-36/37-61

Code letter and hazard designation of product: No symbol

Risk (R) Phrases: none

By the component of under cobalt dryer 1%, not classified Risk phrase R42/43.

Safety (S) Phrases:

S7 Keep container tightly closed

824/25 Avoid contact with eyes and skin

S26 In case of contact with eyes. Rinse immediately with plenty of water and seek medical advice.

828 After contact with skin, wash immediately with plenty of water and seek medical advice.

S36/37 Wear suitable protective clothing and gloves.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheet

## Components Hazard Information:

Petroleum hydrocarbon

Cas No.64742-46-7 is classified into R45 (May cause cancer) for DSD, or into Carc.1B, GHS08, Ogr and H350 for CLP, but this product is refined highly, and this material removes a cancer-causing material. IARC classified Group 3.

Cobalt compound (Co CAS No. 7440-48-4 )\*

CLP Resp. Sens. 1 GHS08 H334

Skin Sens. 1 Dgr H317

Aquatic H413

Chronic 4

DSD Xn Harmful

R42/43 May cause sensitization by inhalation and skin contact.

R68 Possible risk irreversible effects.

\*Cobalt in the material concerned is not classified. In the CLP and DSD Regulations for the content of under 0.1%.

Follow all regulations in your country.

16. OTHER INFORMATION
-----------------------

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.