

207.628.2054
Fax: 207-628-2057
Email: sales@mainetimbermats.com

## Log Specifications Log Scale- International 1/4"

## Species-

Mixed Hardwood – Any Native Hardwood (No Poplar at this time). Please call for current pricing.

Hemlock – Please call for current pricing.

## Hardwood Log Requirements-

Length: 16'6"

• Trim Allowance: 5" Minimum

• Diameter: 10" Minimum, 36" Maximum on big end

- Two-inch sweep and crooks are acceptable; however, each log must yield a full length
   8" timber.
- All knots and butt swells must be trimmed flush with the stem.
- Logs must be the product of fresh cut timber.
- Scaling Defects that will warrant a cull log include crooks, forks, rot, seams, shake, splits, sweep, voids, worm holes, and timber breaks.

## **Hemlock Log Requirements-**

Length: 16'6" & 20'6"

• Trim Allowance: 5" Minimum

- Diameter: 10" Minimum on 16'6" and 14" Minimum on 20'6"
   36" Maximum on big end
- Two-inch sweep and crooks are acceptable; however, each log must yield a full length 8" timber on 16'6" logs and 12" timber on 20'6" logs.
- All knots and butt swells must be trimmed flush with the stem.
- Logs must be the product of fresh cut timber.
- Scaling Defects that will warrant a cull log include crooks, forks, rot, seams, shake, splits, sweep, voids, worm holes, and timber breaks.

All cull logs are to be picked up within 2 weeks of being delivered or they will become the property of Maine Timber Mats.

All log scale decisions are final.