

304 Stainless Steel Membrane Housings



Advantech Aqua™ 304 Stainless Steel Membrane Housings are manufactured using state of the art equipment and the highest quality materials. Advantech Aqua™ 304 Stainless Steel Housings are engineered to withstand pressures up to 300psi, while ensuring consistent quality and performance for a broad range of water chemistries.

- ✓ World Class Manufacturing Facility
- ✓ Precision Manufacturing Tolerances
- ✓ 35+ Combined Years Experience

Features

- 304 Stainless Steel
- Seamless Body Design
- Injection Molded Glass Filled Nylon (GFN) End Plugs
- CNC Machined O-Ring Grooves
- Mounting Straps and Hardware Included
- Works with all Standard Membranes

Ph: 866-851-4566

Fax: 951-200-4391

E-Mail: info@advantechaqua.com

Web: www.advantechaqua.com

ADVANTECH AQUA™

Advancing Water Treatment Through Technology™



MODEL	2514	2521	2540	4014	4021	4040	4080
Part Number	40060	40061	40062	40063	40064	40065	40066
Specifications							
Body Material	304 SS	304 SS	304 SS	304 SS	304 SS	304 SS	304 SS
End Cap Material	GFN	GFN	GFN	GFN	GFN	GFN	GFN
Closure Type	Dual Clamp	Dual Clamp	Dual Clamp	Dual Clamp	Dual Clamp	Dual Clamp	Dual Clamp
Membrane Capacity	1	1	1	1	1	1	2
Operating Limits							
Max Pressure psi	300	300	300	300	300	300	300
Max Pressure bar	20.68	20.68	20.68	20.68	20.68	20.68	20.68
Max Temperature F°	120	120	120	120	120	120	120
Max Temperature °C	49	49	49	49	49	49	49
Max Chlorides ppm	300	300	300	300	300	300	300
Ports							
Permeate (inch)	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"
Feed (inch)	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"
Dimensions							
B* (inch)	2.5"	2.5"	2.5"	4"	4"	4"	4"
A* (inch)	14"	21"	40"	14"	21"	40"	80"

- Dimensions listed are approximate, contact an Advantech Aqua™ Representative if exact dimensions are required.
- Always ensure clamps are securely fastened when in operation.
- 1/2" X 3/4" end caps available

