



MARKETED BY
 **ENERGY**
 BATTERY GROUP INC.
 1800 Roswell Road, Suite 2200
 Marietta, GA 30062
 888-823-0954

EV SERIES

VALVE REGULATED LEAD ACID BATTERY



Deep Cycle
AGM Battery



EP-EVGC-220A-AM

Energy Power EV Series Batteries provide superior performance, capacities and reliability. Using state of art dry cell technology the EV series is designed for environmentally sensitive areas that require enhanced cycle life capabilities in commercial, industrial, residential, and private applications.

The maintenance free (VRLA) construction and advanced design features makes the EV Series the definitive choice for a wide variety of markets; solar and renewable energy storage; electric vehicle and golf cart; industrial equipment, floor machines, forklifts, aerial lifts, and robotics; marine, RV, and no-idle solutions; mobility and medical equipment; telecom, broadband and cable TV; UPS systems.

FEATURES AND BENEFITS

- The Energy Power, EV Battery Series along with our factories are certified to multiple standards:
- ISO, OHSAS18001, UL, CE
- QC/T 742-2006, GB/T18332.1-2009
- High density lead paste and specialized paste formula for deep cycle application.
- High strength ABS or PP case & cover and valve-regulated construction.
- Maintenance-free. High capacities.
- Environmentally friendly, classified as "Non-Spillable Battery" for transportation. Complies with DOT CFR 49.173.
- High tin alloy grids offer: Less gassing, High corrosion-resistant, Low self discharge, Alloy sheeting material for deep cycle applications.
- Exceptional adaptability to operate at high and low temperature environments.
- Durable copper and stainless steel terminals for high electric conductivity.
- Excellent cycle life: 80% DOD 800 cycles.
- Exclusive electrolyte formula and separator, for protecting the electrolyte density from stratification.
- Superior design allows for fast charge acceptance and resistance to over-discharge.



MECHANICAL CHARACTERISTICS

Industry Type	GC6
Length(mm/inch)	260/10.2
Width mm inch	180/7.1
Height(mm/inch)	254/10.0
Total Height(mm/inch)	274/10.8
Approx Weight (kg/lbs)	30/66.1
Terminal	AM
Container material	PP
Cells	3 cell
Nominal Voltage	6 V

ELECTRICAL CHARACTERISTICS


Nominal Capacity	220Ah@20 hour rate F V 1 75V Cell	
Internal Resistance Approx	Fully Charged battery 25 1 9mOhms	
Self Discharge	3% of capacity per month@68°F/20	
Cranking Amps	1430A@32°F/0	1100A@0°F/-18
Max Discharge	1650A(5s)	
Reserve Capacity (80°F/27)	@25A F.V.(1.75V/Cell)	460Min
	@75A F.V.(1.75V/Cell)	120Min
Charging(25)	Cycle use	Initial Charging Current: 66A,2.40-2.45VPC
(Constant Voltage)	Float use	2.20-2.30VPC

ELECTRICAL CHARACTERISTICS


Final voltage 1 75V &ell	Amp Hours \$H #77 ° 5 &						Minutes of 'ischarge#80) ° 7 &	
	20HR	10HR	5HR	3HR	2HR	1HR	#25A	#75A
	220	210	190	175	155	130	460	120

CHARGE / DISCHARGE TABLES & GRAPHS


CHARGE CHARACTERISTIC CURVE




CYCLE SERVICE LIFE IN RELATION TO DEPTH OF DISCHARGE




RELATIONSHIP OF OCV AND STATE OF CHARGE (25°)




SELF-DISCHARGE CHARACTERISTIC



RELATIONSHIP BETWEEN CHARGING VOLTAGE AND TEMPERATURE



TEMPERATURE EFFECTS ON CAPACITY



To ensure safe and efficient operations always refer to the latest edition of our Technical Manual, as published on our Web site. All specifications subject to change without notice.

