

Parasol commercial grade shadecloth







Parasol[™] is designed for Australian conditions and made to stringent quality and manufacturing specifications.

Parasol™ is a commercial grade knitted shadecloth suitable for tension structures and other heavy duty applications. It is manufactured using a combination of high density monofilament and tape which offers a higher degree of protection from UV radiation, known to cause sunburn and skin cancers.

For ease of fabrication and improved performance, **Parasol**™ shadecloth has been 'heat set' before rolling, to improve lay flat characteristics and dimensional stability.

W UV stabilised

Up to 95% UVR block

Heat set

High strength

Abrasion resistant 2 10 year warranty

APPROVED BY
MELANOMA
INTERNATIONAL
FOUNDATION

Technical Specifications		WARP	WEFT
Breaking Force	N/50mm	700	1800
Breaking Extension	%	81	77
Tear Resistance (Wing Tear)	N	184	319
Bursting Pressure	Mean kPa	3500	
Bursting Force (Steel Ball)	Mean N	19	920
	70.7	100 House 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	

Meets the requirements of AS 4174-1994	'Synthetic Shadecloth'

Colours	Cover Factor %*	UVR Block %	Mean UPF	Shade Factor %
Beach Sand	91.5	91.0	11.8	80.2
Ivory	93.0	91.5	14.1	70.4
Red	91.8	92.1	15.7	81.6
Terracotta	91.6	92.2	14.1	86.5
Harvest	93.1	92.7	14.5	84.5
Forest Green	93.5	93.2	15.5	92.5
Yellow	92.4	92.3	13.3	74.1
Sky Blue	93.9	93.6	17.1	91.0
Ocean Blue	94.5	93.2	16.2	87.4
Navy	95.2	93.8	18.8	90.9
Turquoise	88.9	87.1	8.6	78.4
Steel Grey	93.3	92.7	14.9	85.1
Gunmetal	95.3	95.1	21.6	93.5
Charcoal	94.9	94.8	19.4	94.7
Carbon Black	94.8	94.7	18.9	95.4

^{*}Percentage of UVR block



Fire retardant details

AS 1530 Part III Test results (Building code of Australia General Requirements) Smoke Developed: 5 (8 max). Spread of flame: 8 (9 max) **Parasol™** is available in 15 designer colours.



Nominal weight: 325gsm

Available in: 3 x 50m centre folded rolls*
*3 x 50m straight rolls are available upon request and would be subject to minimum ordering quantities.

Product Disclaimers:

- Polyfab shadecloth is engineered to comply with the Building Code of Australia's general requirements for flammability (FR). Test data available upon request.
- The above information represents the results sourced from third party testing authorities, and tolerances may vary by as much as 10%.
- The Manufacturer reserves the right to alter or modify product specifications and colours without notice, and assumes no obligation or liability for the suitability and use of its products other than those applications intended by the manufacturer.
- Colours shown may not be an exact representation of the actual product.
- Outdoor fabrics are subject to harsh conditions and degradation over time is to be expected. Parasol™ is supported with a 10 year UV warranty. During this period the fabric will remain serviceable and fit for purpose. Color fading is normal over time. Colours containing red and yellow pigments have a tendency to fade more than others. This is not a loss of strength caused by UV breakdown and is not covered by the product warranty. For more details refer to the supporting Polyfab product warranty.
- Polyfab Australia assumes no liability in the event of negligent installation /fabrication or application or choice of cloth.
- During installation, Polyfab shadecloth should not be subject to "pre-stressed" loading in excess of 20%.



Polyfab Australia Pty Ltd ABN 54 069 432 846 63 Frankston Gardens Drive Carrum Downs VIC 3201 Australia Telephone (03) 9770 8480 Facsimile (03) 9770 8483

www.polyfab.com.au

To find your closest distributer visit www.polyfab.com.au