


DESCRIPTION:

EC-5980 Kick starter is specially designed for Easicoat 2K topcoat and Clearcoat. It can speed up the dust free time and air drying time of paint film. It is suitable for spot repair or application at low temperature.

COMPONENTS:

EC-5980 Kick Starter

MIX RATIO:



- ◆ 50°F to 59°F: 5-6 gram EC-5980 per RTS 1 quart
- ◆ 32°F to 50°F: 6-10 gram EC-5980 per RTS 1 quart
- ◆ Below 32°F: 10-15 gram EC-5980 per RTS 1 quart

Note:

- ◆ Pot life of paint mixed with EC-5980 kick starter would be shortened considerably, use up as soon as possible.
- ◆ Not recommended addition of EC-5980 kick starter is over 15 gram per RTS 1 quart, otherwise, it would cause paint film embrittlement and loss of gloss
- ◆ EC-5980 kick starter cannot be used as activator.

PHYSICAL DATA:

VOC: 7.3 lbs/gal

FOR PROFESSIONAL USE ONLY

Read MSDS Before Use

NOTE: The information in this data sheet is based on our knowledge and the current laws. It is always the responsibility of the user to fulfill the requirements of local rules and legislations. The uncertain factors may affect the application of products, such as the condition of substrate. We do not accept any liability on loss, damage and performance of products unless we issue a special agreement. Always read the latest Material Data Sheet and the Technical Data sheet before applying the products.