

**DESCRIPTION:**


Additive for 2K solid colors or clear coats, able to remove fisheye or cratering on the paint film.

### COMPONENTS:

MAX-6930

## Anti-Silicon

**MIX RATIO:**



Packaged ready to use

Can add 0.5%-1% anti-silicon of the paint quantity.

**APPLICATION:**

Spray one or two coats over the paint film with fisheyes or caterings by paint mixed with MAX-6930.

Notes:

- ◆ Use according to the recommended ratio. Excess addition may cause defect of small bubbles or pin holes.
- ◆ In serious defects, fisheyes affected paint film must be sanded out and filled when it is hard dry. Refinish with paint mixed with MAX-6930 .
- ◆ Shelf Life: 2 years in original sealed can at cool and dry place at 41-95°F.

**PHYSICAL DATA:**

VOC: 7.2 lbs/gal

**FOR PROFESSIONAL USE ONLY**

**Read MSDS Before Use**

**NOTE:** The information in this data sheet is based on our knowledge and the current laws. It is always the responsibility of the user to fulfill the requirements of local rules and legislations. The uncertain factors may affect the application of products, such as the condition of substrate. We do not accept any liability on loss, damage and performance of products unless we issue a special agreement. Always read the latest Material Data Sheet and the Technical Data sheet before applying the products.