

DESCRIPTION:

Perfeccoat PC-3460 is a single-component putty with good filling power, fast drying, easy to apply and sand, suitable to cover small scratches, sand holes and pinholes.

COMPONENTS:

PC-3460 Filler

SUBSTRATES:


Dried and sanded existing finishes, putty, 1K & 2K primer

SURFACE PREPARATION:



Remove wax, silicon or other contaminations with 3910 Degreaser.

MIX RATIO:



Packaged ready to use, apply with spreader.
Apply a thin coat at a time with 10-15 minutes.

APPLICATION TOOL:

Putty knife, soft rubber or plastic spreader.

DRYTIME:



@ 73°F

30 minutes

Allow longer drying time for thick coating.

SANDING:

Dry sanding: P400-P600

Wet sanding: P600-P800

Note:

- Not recommended to apply over large area.
- Seal the can tightly after use to avoid skinning.
- Shelf Life: 2 years in original sealed can at cool and dry place at 41-95°F

PHYSICAL DATA:

VOC: 4.3 lbs/gal

FOR PROFESSIONAL USE ONLY

Read MSDS Before Use

NOTE: The information in this data sheet is based on our knowledge and the current laws. It is always the responsibility of the user to fulfill the requirements of local rules and legislations. The uncertain factors may affect the application of products, such as the condition of substrate. We do not accept any liability on loss, damage and performance of products unless we issue a special agreement. Always read the latest Material Data Sheet and the Technical Data sheet before applying the products.