



PC Reducer Series

A high-quality reducer specifically designed for PC basecoats and topcoats. Available in a variety of formulations including fast-drying, standard, slow-drying, and extra slow-drying to accommodate different products, application areas, and temperature conditions.

Usage:

Reduces the spraying viscosity of the paint, improves film smoothness, and enhances dissolving power.

Characteristics:

P-5 Premium Fast Reducer	Fastest evaporation, dedicated 1K basecoat reducer, suitable for spot repairs or application at temperatures below 59°F. VOC: 7.4lb/gal
P-1 Premium Standard Reducer	Medium evaporation, universal reducer for 1K basecoats and 2K products, suitable for spot repairs or application at temperatures between 59°F-77°F. VOC: 7.4lb/gal
P-2 Premium Slow Reducer	Slow evaporation, slow-drying reducer for 1K basecoats and 2K products, suitable for spot repairs, full vehicle spraying, or application at temperatures between 77°F-86°F. VOC: 7.2lb/gal
P-3 Premium Extra Slow Reducer	Slowest evaporation, dedicated reducer for 2K products, suitable for full vehicle spraying, large-area application, or use at temperatures above 86°F. VOC: 7.2lb/gal

Notes:

1. In conditions of high temperature or humid weather, 10-30% Retarder Solvent may be added as needed.
2. Shelf Life/ Packaging: Store in a cool, dry place at 68°F. The product can be stored for two years in its original sealed container.