


### DESCRIPTION:

MAX-6980 quick drier is specially designed for Maxytone 2K topcoat and Clearcoat. It can speed up the dust free time and air-drying time of paint film. It is suitable for spot repair or application at low temperature.

### COMPONENTS:

MAX-6980 Quick Drier

### MIX RATIO:



- ◆ 50°F to 59°F: 5-6 gram MAX-6980 per RTS 1 quart
- ◆ 32°F to 50°F: 6-10 gram MAX-6980 per RTS 1 quart
- ◆ Below 32°F: 10-15 gram MAX-6980 per RTS 1 quart

### Note:

- ◆ Pot life of paint mixed with MAX-6980 Quick drier would be shortened considerably, use up as soon as possible.
- ◆ Not recommended addition of MAX-6980 quick drier is over 15 gram per RTS 1 quart, otherwise, it would cause paint film embrittlement and loss of gloss.
- ◆ MAX-6980 quick drier cannot be used as activator, but can be used with activator.
- ◆ Shelf Life: 2 years in original sealed can at cool and dry place at 41-95°F.

### PHYSICAL DATA:

VOC: 7.3 lbs/gal

### FOR PROFESSIONAL USE ONLY

Read MSDS Before Use

**NOTE:** The information in this data sheet is based on our knowledge and the current laws. It is always the responsibility of the user to fulfill the requirements of local rules and legislations. The uncertain factors may affect the application of products, such as the condition of substrate. We do not accept any liability on loss, damage and performance of products unless we issue a special agreement. Always read the latest Material Data Sheet and the Technical Data sheet before applying the products.