

MONSOON



Irrigators Australia Pty Ltd

TRAILCO

Traveller T400-2

Soft Hose Irrigator

Standard Equipment Fitted

- **Trailco Proven Piston Drive** – Patented, efficient piston drive with virtually no pressure loss, reducing pumping costs and maintenance. No chains, sprockets, belts or gearboxes.
- **Powerful Drive Unit** – Double-acting piston with mechanically actuated valve for reliable, trouble-free operation and a wide range of travel speeds.
- **Low Labour Operation** – Designed to be easily operated by one person.
- **Compact & Stable Design** – Short turning circle with four-wheel stability for easy handling.
- **Flotation Tyres** – Matching front and rear track to minimise bogging and soil compaction.
- **Reversing Attachment** – Locks the drawbar to allow front wheels to lift via tractor linkage, making reversing simple.
- **Wide Wheel Track & High Clearance** – Ideally suited for row crops, reducing crop damage.
- **Long Life Construction** – All major components galvanised or plated for maximum protection.
- **Angus Premium Hi Flow Hose** – High quality irrigation hose with a 10-year warranty.
- **Automatic Shut Off** – Forward travel stops automatically at the end of the spray run.
- **Constant Travel Speed** – Ensures excellent water uniformity with simple speed adjustment.
- **Accurate Steering** – Automotive style steering for stable tracking.
- **Cable Drum Brake** – Prevents cable over-run and damage during towing.
- **Manual Cable Rewind** – Easy cable recovery on aborted runs and slack take-up before start up.
- **Automatic Brakes** – Allows neat hose lay without long anchor loops; brakes release automatically during operation.
- **Automatic Start Up** – Self-engaging system automatically starts forward travel after set up.
- **Self Cleaning Filter** – Protects the drive unit from debris.
- **Easy Servicing** – All service points conveniently located.
- **Pressure Gauge** – High quality liquid-filled gauge fitted to the sprinkler.



Optional Extras

- **200mm Ram & 1" Valve Assembly** – Provides increased pulling power for heavy hose conditions and longer hose lengths.
- **Sprinkler Tilt Coupling** – Assists in combating wind by adjusting the sprinkler trajectory angle.
- **15" Flotation Tyres** – Minimise bogging and reduce soil compaction.
- **Riser Pipe Extension** – Allows irrigation of crops up to 6.5m (21') tall.
- **6.95 x 14" Tyres (Set of 4)** – Supplied in place of 11 x 15" flotation tyres.

Ideally suited for :

Row crops, with a wide wheel track and high ground clearance to reduce crop damage.

