

C&I Energy Storage System

>> UP-C&I-(430-466)-L



Flexible

- ▶ Flexible expansion of system capacity
- ▶ Applicable to different industrial and commercial scenarios
- ▶ Compatible with DC coupling and AC coupling

Safe and Reliable

- ▶ Excellent safety of cobalt free LiFePO₄ battery
- ▶ Built-in liquid cooling system and fire protection system
- ▶ BMS real-time monitoring and protection

Intelligent

- ▶ Integrated EMS
- ▶ Cloud operation and maintenance
- ▶ APP online monitoring

Simple

- ▶ Easy installation with modular design
- ▶ Convenient maintenance
- ▶ HMI

Model:

UP-C&I-430-L UP-C&I-460-L UP-C&I-466-L

UP-C&I-(430-466)-L Datasheet

Model Name	UP-C&I-430-L	UP-C&I-460-L	UP-C&I-466-L
------------	--------------	--------------	--------------

DC

Cell type	LFP3.2V/280Ah		LFP3.2V/300Ah
Battery pack	1P48S/43kWh	1P52S/46.59kWh	1P48S/46kWh
Battery pack connection	Max. 5S*2P		
Battery voltage range	672V~864V	728V~936V	672V~864V
Battery system capacity	430kWh	466kWh	460kWh
Charge and discharge ratio	≤0.5C		
DC-DC	125~200kW (Integrated MPPT function)		
	BAT : 250~1000V ; Busbar : 250V~1000V		

AC

Rated power	100kW/125kW/150kW/175kW
Max.output power	110kW/137.5kW/165kW/192.5kW
Rated voltage	380V, -15%~+10%
Rated frequency	50Hz/60Hz, ± 5Hz
Power factor	- 1 (lead)~1 (lag)
AC current harmonic	THDi<3% (Rated output power)
Access mode	3P/3P+N
Overload capacity	1.1 times long-term@45°C ; 1.2 times 1min

Efficiency

Max.system efficiency	91%
-----------------------	-----

Protection

DC input	Load switch+Fuse
Overvoltage	DC Type II/AC Type II
Fire protection system	Aerosol/Water fire protection optional

Physical

Weight	4250kg (Subject to actual weight)
Dimension (W*H*D)	2230mm*1300mm*2280mm
IP Protection	IP65

Environmental requirements

Allowable ambient temperature	-20°C~+55°C (50°C derating)
Allowable ambient humidity	0~95% RH
Max. operating altitude	2000m
Cooling mode	Intelligent liquid cooling