

Company: _____
Address: _____
Attn.: _____
Phone: _____
Email: _____
Ship To: _____
Address: _____
Req. Ship Date: _____

Purchase Order #: _____
Date: _____
Job Name: _____
Job Location: _____
Installation By: _____
Number of Cars: _____
Contact: _____
Phone: _____
Lift Gate Truck: ☐ Yes ☐ No
☐ 24 hrs* ☐ 48 hrs* **(Freight fees applicable)*
Delivery Notification: ☐ Notification by VC

Certification: ☐ UL/CUL

Office Prints: ☐ 11"x17" ☐ Submittals

Service: ☐ Passenger ☐ Freight ☐ Service **Jack Type:** ☐ Telescopic ☐ Hole-less ☐ In-Ground ☐ Roped

Machine Room: ☐ Conventional ☐ MRL ☐ Adjacent ☐ Remote Distance Remote: _____

Controller: ☐ Vision 2.0 w/Car Top Inspection Station (serial I/O) ☐ MH3000 (Discrete-wired)
☐ A-B Compact Logix PLC ☐ A-B ControlLogix PLC

Building Power: _____ V - _____ ϕ - _____ Hz **Car Capacity:** _____ lbs **Car Speed:** _____ fpm

No. of Landings: _____ **Total Travel:** _____ ft. ☐ **Short Floors**

Travel Between Ldgs: 1-2: _____ ft. 2-3: _____ ft. 3-4: _____ ft. 4-5: _____ ft.

5-6: _____ ft. 6-7: _____ ft. 7-8: _____ ft. 8-9: _____ ft. 9-10: _____ ft.

Travel cable: By Virginia Controls: ☐ Customer Supplied: ☐
(Vision 2.0 controllers only) Contact Sales for Specification

Length: _____ ft. *(NOTE: default is travel + 70 ft.)*

Type: ☐ Jute Core w/grips *(suspended < 200 ft.)*

Operation:

- ☐ Selective Collective ☐ Single Automatic Pushbutton
☐ Single Button Collective ☐ Constant Pressure Pushbutton
☐ Call & Send ☐ Real Time Dispatching
☐ Simplex ☐ Duplex
☐ Group: _____

Doors:

- ☐ GAL MOVFR ☐ GAL Other: _____ ☐ VC MODSS Door Controller
☐ Wittur: _____ ☐ MAC Solid State ☐ ECI: _____
☐ Other: _____ ☐ Swing Door
☐ Manual: ☐ Fixed Cam ☐ Retiring Cam: ☐ AC: _____ V - _____ ϕ - _____ Hz @ _____ Amps ☐ DC _____ V, _____ Ω , _____ Amps
 Power Freight: ☐ EMS ☐ Peelle ☐ Courion Model _____ ☐ Auto-open ☐ Auto-close

Fire & Safety Code:

- ☐ A17 '22 ☐ A17 '19 ☐ A17 '16 ☐ A17 '13 ☐ A17 '10 ☐ A17 Other: _____ (year)
☐ CAN B44- _____ (year) ☐ Local Code: _____ ☐ Other: _____
☐ Fire Service Phase 1 Only ☐ NO FIRE SERVICE *(Safety code year required, even if "no fire service" selected)*

	Floor Labels / Ldg Numbers	Main / Alt	Front / Rear
10			
9			
8			
7			
6			
5			
4			
3			
2			
1			
	Front	Rear	Fire Access

☐ **Pre-Wire Fixtures:** Ship boards to: _____ Ship by Date: _____

Fixture Voltages: (MH-3000 = 120VAC, Vision 2.0 = 24VDC) Car/COP: _____ V Hall/Hoistway: _____ V

Hall I/O Boards: ☐ Screw Terminal Connections (CANbus cable by Virginia Controls) ☐ Plug-In (RJ45) Connection (Ethernet cables not provided)

- | | | | |
|--|----------------------------------|--|--|
| ☐ Car Position Indicator | ☐ Digital | multi-light | |
| ☐ Hall Position Indicator | ☐ Digital | multi-light | @ Non-Main landings |
| ☐ C.E. Electronics Micro-Comm PI Driver Board (Floor Labels Required) | | ☐ Voice Annunciator | ☐ Direction Arrows |
| ☐ Passing Gong | _____ V | ☐ AC | ☐ DC |
| ☐ Car Travel Lantern | _____ V | ☐ AC | ☐ DC ☐ Serial (from driver board) ☐ ½ Stroke Gong Programming by VC |
| ☐ Hall Lanterns | _____ V | ☐ AC | ☐ DC ☐ Serial (from driver board) ☐ ½ Stroke Gong Programming by VC |
| ☐ Door Open Bell | _____ V | ☐ AC | ☐ DC |
| ☐ In-Use Lights | _____ V | ☐ AC | ☐ DC |
| ☐ Barrier Free Gong | _____ V | ☐ AC | ☐ DC BFG @ Ldg# _____ |

Features: (interfaces only, unless otherwise specified)

- | | |
|--|---|
| ☐ Hoistway Inspection Access: ☐ Top ☐ Bottom ☐ Other | ☐ Load Weighing Bypass |
| ☐ In-Car Inspection | ☐ Low Oil Switch |
| ☐ Independent Service | ☐ Flood Switch |
| ☐ Emergency Power: ☐ Auto ☐ Manual ☐ Lower Only | ☐ Car-to-Lobby Switch |
| ☐ Battery Lowering "BORIS" (battery lowering unit included) | ☐ Key or Card Lockout in C.O.P. @Ldg.#'s: |
| ☐ Door Nudging with Timed Electric Eye Cutout | ☐ Card Reader Contactor Location: ☐ C.O.P. ☐ Machine Room |
| ☐ Infrared Curtain Unit (Nudge on Fire Service) | ☐ Homing: Specify Landing#: _____ |
| ☐ Safety Edge: ☐ with Elect. Eye | ☐ Jack Resynchronization (telescoping piston) |
| ☐ Oil Viscosity Control | ☐ Door Hold Open: ☐ Switch ☐ Button |
| ☐ Low Pressure Switch | ☐ Fan & Light Auto K/O |
| ☐ Hospital Service - "Code Blue" | ☐ Governor Reset Circuit: ☐ 24VDC ☐ 120VAC |
| ☐ Massachusetts EMT Hospital Service | ☐ WiFi - Mobile Interface: ☐ Router & Tablet ☐ Router Only |
| ☐ Anti-Nuisance | ☐ Other: _____ |
| ☐ Machine Room Monitoring: ☐ Local ☐ Remote | ☐ Other: _____ |

Controller Enclosure: (Lift off door standard with Vision 2.0 and MH-3000 models)

- | | |
|---|--|
| ☐ Wall Mounted ☐ Free Standing ☐ Hinged | ☐ Other: _____ |
| ☐ NEMA 1 ☐ NEMA 12 ☐ NEMA 4 ☐ NEMA 4X | |
| ☐ Special Dimensions: _____" H x _____" W x _____" D | Cooling: ☐ Fan Kit ☐ AC Unit |

Car Top Inspection Enclosure: (Vision 2.0 ONLY) ☐ NEMA 1 ☐ NEMA 12 ☐ NEMA 4 ☐ NEMA 4X

Positioning/Leveling System:

- ☐ ELGO Absolute Positioning System (Default for all controller models) ☐ NEMA 1 ☐ NEMA 12 ☐ NEMA 4 ☐ NEMA 4X
- ☐ Other: _____

Valve: (Standard is (4) Coils @ 115VAC)

- | | | | |
|---------------------------------------|--|--------------------------------|--|
| ☐ Maxton | ☐ EECO | ☐ Blain | ☐ Dover/TKE (I2-I3) |
| ☐ Other: _____ | ☐ Non-Standard Coil Voltage: _____V ☐ AC ☐ DC | | |

Motor: _____HP _____Volts _____F.L. Amps _____ Starts/HR

- ☐ Solid State Starter Preferred Starter: Siemens Sprecher & Schuh
- ☐ Dual with Sequential Starting ☐ Wye-Delta ☐ Across-the-Line
- ☐ 6/12 Motor Leads ☐ 3/9 Motor Leads

EMAIL FORM