



UNITY CHARGING CART


NT-Unity-CC88

Stores, Charges, and Transports 32 Devices

NADIV TECHNOLOGIES Unity Charging Cart

- Full Equipped with three extendable shelves, accommodating up to 32 devices.
- Features optimized ventilation through dividers and frame for efficient cooling.
- → Delivered fully assembled—ready to use with plug-and-play functionality.
- ♦ Offers customizable colors at no extra charge.
- Constructed with a durable, high-quality steel frame for long-lasting performance.
- 4 Tailored for both commercial and educational applications.
- 4 Includes a lifetime frame warranty, a 2-year warranty for USB-C charging hubs, and a 1-year warranty for power banks.
- ← Certified to meet CE and RoHS standards.







Key Features



Efficient Cable Management:

The cable management system positions connections at the front of the cart, reducing strain on cables to enhance durability and minimize maintenance needs.



Smart Timer Power Management:
Features a power management system
with three customizable charging modes for flexible and
efficient operation.



UV Sterilization:

Integrated UV sterilization eliminates germs and viruses quickly, promoting a healthier environment for users.



Advanced Cooling System:
Ensures optimal device performance
by preventing overheating during storage.



Silent Swivel Casters:
Designed for smooth,
noise-free mobility, ideal for sensitive
environments.



Enhanced Build Quality:
Superior craftsmanship extends to every detail, including durable buttons and switches, ensuring reliable long-term performance.

Specifications

Model	NT-Unity-CC88
Device Capacity	Accommodates up to 32 devices with a maximum size of 15.6" notebooks.
Material	Durable steel structure for long-lasting use.
Wheels	Four high-quality, 5-inch ball-bearing wheels for smooth mobility, with braking options (two or four brakes available).
Charging	USB-C 65W Smart Charging
External Option	Features an external on/off button with an indicator light for convenient operation.
Electric Parameter	Input Voltage:110V-240V Rated current 10A 50/60Hz

Power Management System	Smart Power Management System with built-in power protection.
Device Trays	ABS plastic dividers with integrated cable management
Cooling	Divider and frame integrated ventilation
Door Locking System	Doors open to a full 180 degrees and include a 3-point locking system for enhanced security.
Color	Black, White, or Custom