





# IPW-BL5111-SH

## 5MP IR Bullet Network Camera

### Key Features:

- 30 fps@2880\*1620
- H.265 Compression Technology
- 0.01Lux
- Built-in IR Illuminators, Effective up to 30 Meters
- PoE Class 0/3(IEEE802.3af)
- IP67-rated dust and water protection
- Two-way Audio



### Key Specifications:

Camera	
Image sensor	1/2.8" 5 megapixel CMOS sensor
Resolution	5 megapixel
Max. Resolution	2880x1620
Lens Type	Fixed-focal
Focal Length	f=3.03mm
Aperture	F=1.6
Minimum Illumination	0.01 Lux
Removable IR-cut Filter	Yes
IR range	30m
On-board Storage	Micro SD Card

Video	
Video Compression	H.265/H.264/MJPEG
Maximum Frame Rate	2880x1620@30fps
Maximum Streams	3 simultaneous streams
S/N Ratio	3DNR
Dynamic Range	120dB WDR
Resolution	2880*1620 / 1920*1080/1280*720 / 1024*576 / 960*544 / 720*480 / 640*360
Image settings	General settings: video title and time stamp overlay, video orientation (flip, mirror), day /night settings; Illuminators: illuminators, anti-overexposure; Image settings: white balance, image adjustment (brightness, contrast, saturation, sharpness), 3DNR; Exposure: BLC, exposure control (exposure level, exposure time, gain control), WDR; Privacy mask; Scheduled profile settings
Audio	
Audio Capability	Two-way Audio(full duplex)
Audio Interface	Audio/in X 1、 Audio/out X 1
Smart function	
VCA	SD card life expectancy、 Alarm Input、 Human Detection、 Motion Detection、 Network Failure、 Video Tampering、 Audio Detection Electric Fence (option)
ROI	Yes
Network	
Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DDNS,RTP,RTSP,RTMP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45)
Power Input	PoE Class 0/3(IEEE802.3af)
ONVIF	Profile S,T supported
System Requirements	
Web Browser	Chrome 70+,Firefox 30.0-51,Safari 8.0-11,edge
General	
DI/DO	2 IN 2 OUT (option)
Weather-proof	IP67
Operating Temperature	-30° C to 60° C
Connectors	RJ-45 cable connector f or 10/100Mbps
Power	MAX 8W
Dimensions	ø 72.5*178.5mm