


Series: Zahara Specifications



3" x 12" Glossy Wall Tiles


Zahara's handcrafted wall tiles feature a beautifully undulated surface that showcases rich color variations and natural imperfections, giving each piece a unique character. The glossy finish enhances these details, creating a dynamic blend effect where colors appear vibrant and full of life. Available in an array of 10 stunning shades, Zahara tiles have the power to transform any space into a statement of elegance and artistry.



ZL01RCT312UNDGL
Color: Turchese



ZL02RCT312UNDGL
Color: Salvia



ZL03RCT312UNDGL
Color: Bosco



ZL04RCT312UNDGL
Color: Cielo



ZL05RCT312UNDGL
Color: Petrolio



ZL06RCT312UNDGL
Color: China



ZL07RCT312UNDGL
Color: Lana



ZL08RCT312UNDGL
Color: Argilla



ZL11RCT312UNDGL
Color: Gesso



ZL12RCT312UNDGL
Color: Carbone

Specifications* All field tile is sold in full cartons.

Zahara Glazed Ceramic Wall Tile
10 Glossy Colors
Shade V-2 Colors: Gesso & Carbone
Shade V-3 Colors: All others shown
Shade V-4 Colors: Lana & Argilla
3" x 12" S/F Carton - 12.14
3" x 12" Tiles per carton - 48

Alternate special order sizes are available for this series. For details contact your sales representative.

*Note - Check with your sales representative for proper use and application of this product.

+Estimated delivery time of 2-3 weeks.

Series: Zahara Specifications

GLAZED CERAMIC WALL

FINISHES: GLOSSY

USAGE



MATERIAL





SPECIAL FEATURES




MADE IN THE U.S.A.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.


SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 4 Wall Tile	3-3/4" x 3-3/4" (9.85 cm x 9.85 cm)	5/16" (9.50 mm)	5.67	54
	3 x 12 Wall Tile	3" x 12" (7.65 cm x 30.71 cm)	5/16" (7.75 mm)	12.14	48

TRIM

Description	Number	Size	Shape
Jolly	S1/212J	1/2 x 12	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain (Residential or Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	




A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

PilotPLUS+

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Medium Variation (ZL11 & ZL12)  High Variation (ZL01, ZL02, ZL03, ZL04, ZL05 & ZL06) (ZL07 & ZL08)  Random Variation (ZL07 & ZL08)**


* 3 x 12 tile only.
** 4 x 4 tile only.

PERFORMANCE CHARACTERISTICS

	ASTM #	Wall Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

FEATURES



All or select items within this series meet the requirements for these qualifications.