CDLB Pre-trip Outside.	Leaf Springs, Spring Mounts(FB), U-Bolts,
Underneath the truck no puddles or leaks from my coolant and	Shock Absorber ☐ All Securely Mounted, Not broken, Not cracked
power steering reservoirs, and hoses., no hanging wires.	☐ All have no missing hardware and are tight
All my lenses	☐ Leaf springs not shifted or missing
Securely Mounted, Not broken, Not cracked	Shock absorber is not leaking
□ Not missing, proper color	SHOCK absorber is not leaking
☐ Clean and clear.	Brake Lines or Hoses
	Both Securely Mounted, No cuts, tares, or leaks
Vehicle is sitting level, Front/Back/Side to Side	☐ Clamps are present and tight.
	☐ Supplies air to brake system.
Coolant and Power steering reservoirs	
☐ Securely Mounted, Not broken, Not cracked	Brake Drums and Linning
no missing clamps, caps are tight	☐ Both Securely Mounted, Not broken, Not cracked
☐ Proper level and have no leaks.	□ No contaminates, fluids, oil, or grease in between.
Dip Stick	
☐ Securely Mounted, Not broken, Not cracked	
Pull out the dip stick, wipe it clean, replace it, pull back	Side of Vehicle All my Lenses and reflectors.
out, Proper level.	☐ All Securely Mounted, Not broken, Not cracked
0.00, 2.10p 02.10.10.1	☐ All not missing, proper color
Steering System /Gear box and Linkage	☐ Clean and clean.
☐ Both Securely Mounted, Not broken, Not cracked	
□ No missing castle nuts and cotter keys.	Traffic Devices (Mirrors)
☐ Arms and rods, joints are not lose or worn.	☐ Securely Mounted, Not broken, Not cracked
•	□ No missing hardware.
Fluid and Air leaks (Coolant & Power steering hoses	☐ Clean and clear.
☐ Securely Mounted, No cuts, tares, or leaks	
□ clamps are present and tight.	Battery Box Door Opens and Closes
	☐ Cables and Connections, tight with no corrosion.
Air Hoses	☐ All Securely Mounted, Not broken, Not cracked
Securely Mounted, No cuts, tares, or leaks	☐ Batteries have no leaks.
☐ clamps are present and tight.	DEPT. I. IE IT I
Tino	DEF Tank and Fuel Tank
Tire ☐ Securely Mounted to rim, Not cuts, tares, or leaks	All Securely Mounted, Not broken, Not cracked
☐ Tread depth is 4/32 seconds or more.	 Caps are tight and sealed No leaks from tanks or the hoses.
☐ Check with a tread depth gauge.	INO leaks from taliks of the floses.
□ No exposed wire.	Frames (CAB AND CARGO BOX)
L	All Securely Mounted, Not broken, Not cracked
Valve Stem (Accessible)	□ No missing hardware, no broken welds.
☐ Securely Mounted, Not broken, Not cracked	□ No holes in trailer floor
☐ Cap is present and tight with no leaks.	
□ Properly inflated, checked with a pressure guage.	Reflective tape (On the side and rear of truck)
	☐ All Securely Mounted, Not broken, Not cracked
Rim Inside and Outside	☐ Present and affixed securely to the trailer.
☐ Securely Mounted, Not broken, Not cracked	☐ Proper color red and silver.
□ No distorted Bolt holes.	
□ No illegal welds.	Lenses and reflectors (Rear of truck)
Luca Nuta and Stude	All Securely Mounted, Not broken, Not cracked
Lug Nuts and Studs	☐ All not missing, proper color
 All Securely Mounted, Not broken, Not cracked All hardware are present and tight. 	☐ Clean and clear
☐ They have no shiny thread or rust trails.	

CDL B Pre-trip In-cab Climb in the truck using **Three points of contact** sit down and put on your **Seat belt**. Safe Start/ Make sure both brakes are applied. Make sure the truck is in neutral. Press in the clutch to be able to start the truck. Turn the key to the on position, and let it cycle. Look for your ABS/lights to come on and off on the dash and on the trailer. (5 sec) Look for all your **DEF** indicators to come on/off. (5 sec) Take you foot off the clutch. While the Truck is Building air pressure you can use this time to do some of the In-cab check items. **Light Indicators** Low beams and high beams working properly Left and right turn signals working properly. 4-way flashers working properly. **Emergency Equipment** Six spare fuses There are 3 reflective triangles. Fire extinguisher charged and secure. Windshield and Mirrors Both Securely Mounted, Not broken, Not cracked Both are clean and clear with no obstructions Both have no flawed glass. Mirrors are adjusted to the driver, **Wipers and Washers** Securely Mounted, Not broken, Not cracked Arms and Blades firmly against the glass Not dry rotted, washers work and squirt **Check Heater and defrost** Turn heater and defrost on Wave hand above for defrost and below for heater. Say both are working properly.

City Horn and Air Horn

Pull air Horn, push city horn. Both working properly

Governor Cut-off

Building air to (120psi to 140psi) or governor cut-off. If its proper range it is working properly.

- 1. SHUT OFF ENGINE, TURN THE KEY BACK TO ON POSITION.
- 2. PRESS DOWN AND HOLD (S E R V I C E) BRAKE PEDAL
- 3. RELEASE ALL PARKING AND TRAILER VALVES. (PUSH IN BOTH BUTTONS)

WAIT FOR GUAGE TO SETTLE (APPX 4 SECONDS)

AIR LEAK-NO MORE THAN 3 PSI IN 1 MINUTE

- ☐ Air Stabilized, time starts now.
- ☐ After 1 minute stop timer.
- ☐ Check that vehicle did not lose more than 4psi in 1 min.
- ☐ Working properly

AIR WARNING DEVICE (ALARM)

- ☐ Without restarting the engine.
- I will fan my brakes until the Alarm comes on 55 psi or above.
- Proper range working properly.

Emergency Brake Test-

- ☐ I will continue to fan my brakes.
- ☐ Between 20 to 45 psi both my valves should pop out.
- Proper range working properly.

Only tell the examiner about the air pressure if it is outside of the range.

Truck Brake Check-Safe start the vehicle and build up air pressure to at least (90psi).

1. Tugging on Truck Brake

Apply truck brakes "pull out the yellow button."
Put the tuck in 1st gear or drive.
Lift your foot off the clutch slowly until it engages.
The truck did not move the tractor brakes are working
properly.

2. Service brakes Check

_	Traine sure that years were in publica in
	Put the truck in gear and you must drive forward and
	reach 5mph and apply service brakes coming to a
	smooth stop.

Make sure that yellow Valve is pushed in

- ☐ The wheel did not pull left or right, and the truck stopped.
- ☐ My brakes are working properly.

