



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

SAFETY DATA SHEET (SDS)

Q20 – INSTANT LUBRICANT

SAFETY DATA SHEET (SDS) according to ISO / SANS 11014:2009/2010, UN Transportation of Dangerous Goods, UN Globally Harmonized System of Classification and Labelling and EC Directives 1272/2008

SECTION 1: Identification – Chemical Product and Company

Trade Name	Q20 – INSTANT LUBRICANT
Product Code	030022
Chemical Technical Name	Aerosol
Proper Shipping Name	Aerosols
UN Number	1950
CAS Number	Mixture
GHS Product Identifier	Moisture Repellent (Aerosol)
Chemical Family	Moisture Repellent
Recommended use of the Chemical	Moisture repellent for protecting and removing moisture from wet ignition systems on cars, trucks, motorbikes, marine engines and electric motors. Q20 overcomes and prevents stubborn starting and stalling in damp climates and heavy downpours. Q20's unique penetrating power makes it ideal as a release agent and light duty lubricant for use in the home, garage and workshop. Q20 is silicone free.
Restrictions of the Chemical	Not to be used by untrained persons.
Supplier Details	CRC Industries RSA (Pty) Ltd
Address	Gauteng Business Park, Triton-Leo House, 15/16 Bronssingel, Clayville Ext 20, Olifantsfontein.
Telephone Number	+27(0)87 135 5888
E-Mail	Info.sa@crcind.com / simon.smith@crcind.com
24 Hour Emergency Phone Number	+27 (0)82 874 5969

SECTION 2: Hazards Identification

GHS Classification of substances: Flammable Aerosol

Hazard Class: 2.3

Hazard Type	Hazard Category	GHS Hazard Statement
Flammable Aerosols	Category 2	H223 Flammable Aerosols
Acute Toxicity Oral	Category 5	H302 Harmful if swallowed
Acute Toxicity Dermal	Category 2	H315 Causes Skin Irritation
Acute Toxicity Inhalation	Category 4	H332 Harmful if inhaled
Respiratory Sensitizer	Category 1B	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Eye Damage/Irritation	Category 2A	H318 Causes serious eye irritation
Aquatic Acute	Acute 2	H402 Harmful to Aquatic Life
Aquatic Chronic	Category 2	H402 Harmful to Aquatic Life
Carcinogenicity	Category 2A	H351 Suspected of causing cancer if swallowed

Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

The most important adverse effects to know in emergency are:-

SANS 10234:2007 GHS Label elements, including precautionary statements:



Signal word: Warning

Hazard Statement:-

H223 Flammable Aerosols

H302 Harmful if swallowed

H318 Causes serious eye damage

H315 Causes skin irritation

H332 Harmful if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer if swallowed

H402 Harmful to aquatic life

Precautionary statements:-

P210 Keep away from Heat, Sparks, Open Flames and Hot surfaces – No Smoking

P211 Do not spray on open flames or other ignition source

P251 Pressurized container – Do not pierce or burn even after use.

P280 Wear protective Gloves

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using / handling this product

P302 + P352 If on skin wash off with plenty of water

P332 + P313 If skin irritation continues, get medical attention

P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes, remove contact lenses if safe and easy to do, continue rinsing and get medical attention.

P261 + P271 avoid breathing mist, wear eye & face protection and use in well ventilated areas

P301 If swallowed and feels unwell, get medical attention.

Response:

Refer Sections 5, 6 and 8

Storage:

Refer Section 7

Special Labelling requirements

Refer to Section 14 for transport labels.

SECTION3: Composition / Information on Ingredients

Chemical Identity	Mixture
Other means of identity	None
Common Name, synonyms, etc.	None

Ingredient Name	UN Number	CAS Number	%	Classification EC1272/2008
Tetrachloroethylene	1897	127-18-4	40-60	204-825-9
Distillates (Petroleum), hydrotreated heavy naphthenic	Mixture	64742-52-2	10-20	265-155-0
Nonane	1920	111-84-2	5-15	203-913-4
Octane, N-Octane	1262	111-65-9	<5	203-892-1



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

SECTION 4: First Aid Measures

Description of necessary first aid measures:

Eye Contact – Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation – Remove victim to fresh air and keep at the rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, systems may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin Contact – Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion – Wash mouth out with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that the vomit does not enter the lungs. Get medical attention. If necessary, call poison centre or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye Contact – Causes serious eye irritation

Inhalation – Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Over-exposure signs/symptoms

Eye Contact – Adverse symptoms may include the following: Pain/Irritation, Watering, redness

Inhalation – No specific Data

Skin Contact – Adverse symptoms may include the following: Irritation, redness

Ingestion – No specific Data

Indication of immediate medical attention and treatment needed, if necessary

Notes to physician – In case of inhalation of the decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific Treatments – No specific Treatments

Protection of first-aiders – No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

SECTION 5: Fire-Fighting Measures

Product is flammable

Suitable extinguishing media: Dry Chemical, CO², Foam

Unsuitable extinguishing material: Water

Special hazards arising from the substance or mixture, in case of fire, the following can develop:

- Oxides of carbon
- Danger of bursting (Explosion) when heated
- Danger of explosion by prolonged heating



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

- Explosive vapour/any mixture

Small fires – immediate action should be to quickly put out the fire.

Large Fires – evacuate area, move containers out and away from fire if can be done safely without increasing risk. Isolate and contain fire as much as possible, and dike or use inert material form berm to contain any spilled materials and run-off water for later disposal. NB need to prevent run-off containing product from contaminating any water source as toxic to aquatic life.

Special Hazards – Use water to keep containers cool to prevent pressure build up and possible explosion which could be caused through pressure build up.

Protective Clothing – Wear full protective clothing and self-contained, positive breathing apparatus. For large fires, get professional emergency response where very large.

Refer to the ERG – Emergency Response Guide 2016 and SANS 10232 – 3 - ERG 154

NB: Prompt actions can prevent spread of small fires but large fires involving chemicals require professional Emergency Response.

SECTION 6: Accidental Release Measures

For non-emergency personnel – No action shall be taken involving any personnel risk or without training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders – If specialised clothing is required to deal with the spillage, take note of any information in section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel"

Environmental precautions – Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material, may be harmful to the environment if released in large quantities. Collect spillage.

Clean-up methods

Small Spills: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large Spills: Stop leak without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water sources, basements or confined areas. Wash spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

GHS Disposal Precautionary Statement – P501 dispose of spilt product, waste and containers in accordance with SA National and/or regional Regulations, refer National Environmental Management Waste Act –NEM: WA, it's Waste Information Centre sawic.environment.gov.za

SECTION 7: Handling and Storage

Precautions for safe handling – wear appropriate personal protective equipment see section 8.

Eating, drinking and smoking shall be prohibited in areas where chemicals are handled, stored or processed. Workers must wash hands before eating, drinking or smoking to remove any chemicals that could be ingested or inhaled and should remove contaminated clothing and protective equipment before entering eating areas. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure – obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Conditions for Safe Storage – Store in accordance with local regulations. Store away from; direct sunlight, in a dry, cool, well-ventilated area, incompatible materials (See section 10), food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Use appropriate containment to avoid environmental contamination.

Product Shelf Life – 5 Years from date of manufacture.

SECTION 8: Exposure controls / personal protection

Control parameters e.g. occupational exposure limit values or biological limit values

Ingredient Name	%	Exposure Limits – OHS Act South Africa 1993
Tetrachloroethylene	1-5	ACGIH (United States, 1994) TWA: 25PPM STEL: 100PPM TWA: 170 mg/m ³ STEL: 685 mg/m ³ ACGIH TLV (United States, 2/2010) TWA: 25PPM 8 Hours STEL: 100PPM 15 Minutes TWA: 170 mg/m ³ 8 Hours STEL: 685 mg/m ³ 15 Minutes Occupational Health and Safety Act, 1993 (SA) TWA: OEL:RL 50PPM STEL: OEL:RL 150PPM TWA: OEL:RL 335 mg/m ³ STEL: OEL:RL 1000 mg/m ³
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	1-5	ACGIH TLV (United States, 2/2010) TWA: 5MG/m ³ 8 Hours Form: Inhalable fraction
Nonane	1-5	ACGIH (United States, 1994) TWA: 200PPM TWA: 200 mg/m ³ CEIL: 250mg/m ³ ACGIH TLV (United States, 2/2010) TWA: 200PPM 8 Hours TWA: 1050 mg/m ³ 8 Hours
Octane; n-octane	1-5	ACGIH (United States, 1994) TWA: 300PPM STEL: 375PPM TWA: 1400 mg/m ³ STEL: 1750 mg/m ³ ACGIH TLV (United States, 2/2010) TWA: 300PPM 8 Hours

Recommended monitoring procedures:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls:

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also

Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of the environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection procedures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes/Face protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection:

Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection:





Personal protective equipment for the body should be selected based on the task being performed and risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Use properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Gloves	Eye Protection	Running Water	Dust Masks
Rubber/PVC	Goggles/Shield	Access	Dust Mask
			

SECTION 9: Physical and Chemical Properties

Appearance	Liquid (Aerosol) Light Brown
Odour	Hydrocarbon (Slight)
Odour Threshold	Not Known
Ph (of diluted product)	-
Density	0,817g/ml
Concentration	Liquid Concentrate

Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

Initial boiling point / range	176°C (Liquid concentrate)
Melting / Freezing point / range	<-66°C (ASTMD97, Liquid Concentrate)
Flash point	Close cup: >70°C (7158°F) Pensky-Martens
Explosive Properties	Not Applicable
Flammability	Yes
Viscosity	Kinematic (40°C (104°F)): 0.02cm ² /5 (2cSt)
% Volatile by volume	Not Assessed but not readily volatile at ambient temperatures
Solubility – water	Insoluble in cold water and hot water
Auto-ignition temperature	Not Determined
Decomposition temperature	Not Determined
Vapour Density	Not Determined
Vapour Pressure	7.2 Bar (20°C) ; 9.4 Bar (50°C)
Lower Explosive Limit	Not Determined
Upper Explosive Limit	Not Determined
Partition coefficient (n-octanol/water)	Not Determined

SECTION 10: Stability and Reactivity

Chemical Stability	Product is stable under normal operating and temperature Conditions.
Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Conditions to Avoid	Heating, Open Flame, Ignition sources (See section 7)
Possibility of Hazardous Reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Incompatible Materials	Avoid contact with strong oxidizing agents (See section 7)
Hazardous Decomposition Products	No decomposition when used as directed.

SECTION 11: Toxicological Information

Acute toxicity	Results	Species	Product/Ingredient name	Dose/Exposure	Caution
Oral	Cat 5	Rat	Tetrachloroethylene	LD ₅₀ 2629mg/kg	Harmful if swallowed
Oral	Cat 5	Rat	Distillates (Petroleum), Hydrotreated heavy naphthenic	LD ₅₀ >5000mg/kg	Harmful if swallowed
Inhalation	Cat 4	Rat	Nonane Gas	LD ₅₀ 3200ppm 4 Hours	Harmful if Inhaled
Inhalation	Cat 4	Rat	Nonane Vapor	LD ₅₀ 17000mg/m ³ 4 Hours	Harmful if Inhaled
Inhalation	Cat 4	Rat	Octane Gas	LD ₅₀ 25260ppm 4 Hours	Harmful if Inhaled
Inhalation	Cat 4	Rat	n-Octane Vapor	LD ₅₀ 118g/m ³ 4 Hours	Harmful if Inhaled
Dermal	Cat 2	Rabbit	Distillates (Petroleum), Hydrotreated heavy naphthenic	LD ₅₀ 500mg	Mild Irritation
Dermal	Cat 2	Rabbit	Tetrachloroethylene	LD ₅₀ 810mg	Severe Irritation



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

Dermal	Cat 2	Rabbit	Tetrachloroethylene	LD ₅₀ 500mg	Severe Irritation
Eye	Cat 2	Rabbit	Tetrachloroethylene	500mg 24 Hours	Mild Irritation
Eye	Cat 2	Rabbit	Tetrachloroethylene	162mg 24 Hours	Mild Irritation
Dermal	Cat 2	Pig	Nonane	LD ₅₀ 250 micro Litres	Mild Irritation
Dermal	Cat 2	Rat	Nonane	LD ₅₀ 300 micro Litres	Moderate Irritation

Carbon Dioxide Toxicity/Effect symptoms	Unconsciousness, Blisters by skin-contact, vomiting, frostbite, amnoxcance, palpitations, itching, headaches, ear noises, dizziness.
Sensitization	No significant risk level
Tetratogenicity	No significant risk level
Germ Cell Mutagenicity	Negative Analogous Conclusion
Carcinogenicity	Probably carcinogenic to humans
Reproductive Toxicity	Negative Analogous Conclusion
STOT Specific Target Organ Toxicity Single Exposure	Category 3, Octane; n-Octane – May cause drowsiness or dizziness
Aspiration Hazard	Category 1, Octane; n-Octane – May cause allergy or asthma symptoms or breathing difficulties if inhaled

SECTION 12: Ecological Information

	Result	Species	Exposure
Toxicity	Acute EC50 3.64mg/L Fresh Water	Algae – Chlamydomonas reinhardtii – Exponential Growth phase – 7 Days	72 Hours
	Acute EC50 509000ug/L Marine Water	Algae – Skeletonema costatum	96 Hours
	Acute EC50 7500ug/L Fresh Water	Daphnia – Daphnia magna – Instar - <24 hours.	48 Hours
	Acute LC50 3.5mg/L Marine Water	Crustaceans – Elminius modestus	48 Hours
	Acute LC50 4000ug/L Fresh Water	Fish – Jordanella floridae – Juvenile (Fledgling, Hatchling, Weanling) – 2 to 4 months.	96 Hours
	Chronic NOEC >0.4mg/L Fresh Water	Daphnia – Daphnia Magna	21 Days
Chronic NOEC 500ug/L Fresh Water	Fish – Pimephales promelas – Larvae – 30 to 35 days	32 Days	

Persistence & Degradability	Test	Result	Dose	Inoculum
	-	15.38% - Not Readily – 5 Days	-	-

Product/Ingredient Name	Aquatic Half-Life	Photolysis	Biodegradability
Tetrachloroethylene	2.9	77	Low
Nonane	0.00417	3.92	Low
Octane; n-octane	4 to 5.18	3.71	Low

Mobility in soil

Soil/Water Partition coefficient (K_{oc}): Not Available

Other Adverse Effects: No known significant effects or critical hazards

SECTION 13: Disposal considerations

Disposal methods

Hazardous chemical waste. Empty containers or liners may retain some product residues. Do not puncture or incinerate container. Waste must be disposed to a landfill permitted in terms of the Department of Water Affairs and Forestry's minimum requirements for waste disposal to landfill, and the minimum requirements for the handling, classification and disposal of hazardous waste.

Johannesburg +27 11 452 7048




Triton-Leo House, 16 Bronsingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

SECTION 14: Transport information

	SANS 10228:2012	IMDG	IATA
UN Number	UN1950	UN1950	UN1950
UN Proper shipping name	Aerosols	Aerosols. Marine pollutant (tetrachloroethylene, octane)	Aerosols, Flammable, containing substances in Division 6.1, Packing Group III
Transport Class	2 (6.1) 	2.1 	2.1 (6.1) 
Packing Group	-	-	-
Environmental Hazards	Yes	Yes	Yes
Special Precautions for users	None	None	None
Additional Information		Emergency schedules (EmS) F-D, S-U	Passenger and Cargo Aircraft Quantity limitation: 75kg Packaging instructions: 203 Cargo Aircraft Only Quantity limitation: 150kg Packaging instructions: 203 Limited Quantities Passenger Aircraft quantity limitation: 30kg Packaging instructions: Y203

SECTION 15: Regulatory information

Safety, Health and Environmental Regulations Specific for the Product

No known specific and/or regional regulations applicable to this product (Including its ingredients).

SECTION 16: Other Information

ECHA – European Chemical Agency website, Chemical information, C&L Inventory, Chemicals of Very High Concern (SVHCs) and Chemicals for Community Rolling Action Plan (CoRAP)

ERG 2016 Transport Canada and US Dept Transportation PHMSA – Pipeline and Hazardous Materials Safety Administration.

Other relevant information including information on preparation and revision of the SDS – ISO 11014:2009 Safety Data Sheets for Chemical Products – content and order of sections adopted as SANS 11014:2010

UN Recommendations for Transport of Dangerous Goods Model Regulations commonly known as the TDG “Orange Books” 18th revision 2013 currently in effect, 19th revision published June 2015.



Johannesburg +27 11 452 7048

Triton-Leo House, 16 Bronssingel (off Koppel St.), Gauteng Business Park, Clayville Ext 20, Olifantsfontein, 1666

P.O. Box 1161, Olifantsfontein, 1665 • E-mail: info@q20.co.za • CRC E-mail: louis.munnick@crcind.com

www.q20.co.za / www.crcindustries.co.za

Registration Number: 2011/148738/07

UN Globally Harmonized System of Classification and Labelling of Chemicals – GHS commonly known as the **GHS “purple book”** 5th revision 2013 in effect, 6th revision published July 2015.

IMDG – International Maritime Dangerous Goods Code, 2014 edition, amendment 37-14

IATA Technical Regulations 56th edition, January 2015.

EXCLUSION OF LIABILITY

The information provided in the Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication; however no guarantee is made to its accuracy. The information given is prepared only as guidance for safe handling, use, processing, storage, transportation, disposal and release and should not be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials or in any process, unless specified in this Safety Data Sheet.