



Technical Bulletin

		NUMBER: HLX21902R4	TEST DATE: 02/15/2019
HYUNDAI 	<input checked="" type="checkbox"/>	KIA 	<input type="checkbox"/>
		MODEL YEAR: 2020	MODEL CODE: LX2
SUBJECT: MY2020 Hyundai Palisade SUV			

COMMENTS:

TRUCK HAULAWAY

- Upper Deck:** Palisade may not be loaded in the #1 head rack position. Installed luggage rack adds 4.5" (11.43cm) to vehicle height and will exceed U.S. and State maximum load height limitations. All other upper deck positions are approved, provided vehicle height does not exceed U.S. Federal 13'.6" or State load height limitations. **Please load Palisades facing the forward direction whenever possible. Please ensure ppf covering fuel cover door is secure, or ask the VPC to repair same. Vehicles at railheads, please load Palisade facing forward direction should the ppf adhesion be failing.**
- Lower deck:** Approved for all lower trailer positions, except directly behind the driver's cab on trailers built with short ramps seen on many 65' trailers, and trailers with limited overhead clearances. Carriers must maintain a minimum of 4" (10.16cm) overhead space separation between upper and lower vehicles.
- Soft-tie wheel straps are required on all four (4) tires.** Chains or any other method of securement are strictly prohibited. Wheel straps may contact tire tread surfaces only. Side pulls and strap contact with undercarriage components are strictly prohibited.



RAIL LOADING

- Tri-level railcars:** Not Approved.
- Bi-level railcars:** Approved for bi-level railcar shipments only. Utilize the highest chock setting that will maintain a minimum of 2" (5.08cm) clearance between the chock and any vehicle body panel or its components. Follow AAR loading and spacing guidelines.

GENERAL

- The Hyundai Palisade has approximately 7.9 inches (20cm) of ground clearance.
- Seat Belt(s) must be worn at all times.** Key placement: cup holder.
- Vehicle must be shipped with its front tires in the straight forward position, the transmission in "Park" position and its parking brake fully engaged.



Specifications

3.8L Lambda II, GDI D-CVVT 24V 6 cylinder

Curb weight range: 4,127 - 4,387 lbs. (1,871.98kg - 1,989.91kg)

Wheelbase: 114.2 in. (290cm)

Length: 196.1 in. (498cm)

Width: 77.8 in. (198cm)

Height: 68.9 in. (175cm)

Wheels: 18 in. or 20 in. Alloy

(46cm or 51cm)

Transmission: Automatic

*All weights and dimensions are subject to change without notice

QUALITY

Page 1 of 1
Revision R4