



Technical Bulletin

HYUNDAI 		KIA 	NUMBER: KON1811R1	TEST DATE: 11/26/2018
<input type="checkbox"/>	<input checked="" type="checkbox"/>	X	MODEL YEAR: 2020	MODEL CODE: ON
SUBJECT: MY2020 KIA Telluride				

COMMENTS:

TRUCK HAUL-AWAY

- Upper Deck:** Approved for all upper deck positions.
- Lower deck:** Approved for all lower trailer positions with exception of position #6 behind the cab on short ramps seen on many 65' trailers, or trailers with limited overhead clearances. Always check load heights for state 13'6" or 14' height limitations.
- Soft-tie wheel straps are required on all four (4) tires.** Chains or any other method of securement are strictly prohibited. Wheel straps may contact tire tread surfaces only. Side pulls and strap contact with undercarriage components are strictly prohibited.

RAIL LOADING

- Tri-level railcars:** **Not Approved.**
- Bi-level railcars:** Approved for bi-level railcar shipments only. Utilize the highest chock setting that will maintain a minimum of 2" clearance between the chock and any vehicle body panel or its components.

GENERAL

- The KIA Telluride has approximately **7.9 in. (201 mm) of ground clearance.**
- Rear seat alarm.** If a rear door (s) is opened for inspection, deactivate sensor or alarm will sound. Deactivation button is found on right side of steering column next to cruise control switch.
- Seat belt(s) must be worn at all times.**
- Vehicle must be shipped with its front tires in the straight forward position, the transmission in "Park" position and its parking brake fully engaged.



Specifications

Models: S / SX / LX / EX

3.8L V6 GDI
Curb weight: 4,112 - 4,482 lbs. (1,865 - 2,033 kg.)
Wheelbase: 114.2 in. (2,900mm)
Length: 196.9 in. (5,000 mm)
Width: 78.3 in. (1,900 mm)
Height w/rails: 69.3 in. (1,759 mm)
Wheels: 18 or 20 in. Alloy (457 - 508 mm)
Transmission: Automatic

**All weights and dimensions are subject to change without notice*

QUALITY

Page 1 of 1
Revision R1