

Technical Bulletin

NUMBER: HJX12002R0 MODEL YEAR:

2021

TEST DATE: 02/13/2020

MODEL CODE:

JX1

HYUNDAI



KIA



SUBJECT:

MY2021 GENESIS GV80 SUV

COMMENTS: TRUCK HAULAWAY

- **Upper Deck:** The Genesis GV80 may not be loaded in the #1 or #2 upper trailer headrack positions. Installed luggage rack adds 4.5" (11.43cm) to vehicle height and will exceed U.S. and State maximum load height limitations. All other upper deck positions are approved, provided vehicle height does not exceed U.S. Federal 13'.6" or your State load height limitations. Please load all GV80's facing the forward direction whenever possible.
- **Lower deck:** Approved for all lower trailer positions, except directly behind the driver's cab for trailers built with short ramps seen on some 65' trailers, and trailers with limited overhead clearances issues. All carriers must maintain a minimum of 4" (10.16cm) overhead space separation between upper and lower vehicles.
- Soft-tie wheel straps are required on all four (4) tires. Chains or any other method of C. securement are strictly prohibited. Wheel straps may contact tire tread surfaces only. Side pulls and strap contact with undercarriage components are strictly prohibited.

RAIL LOADING

- **Tri-level railcars**: Not approved conveyance.
- b. **Bi-level railcars**: Genesis GV80 SUV are approved for bi-level railcar shipments only. Utilize the highest chock setting that will maintain a minimum of 2" (5.08cm) clearance between the chock and any vehicle body panel or its components. Install all grate lock type chock systems tightly against tires whenever possible. Rail loaders are to follow AAR loading and spacing guidelines.

GENERAL

- The Genesis GV80 has approximately 8.5 inches (21.59cm) of ground clearance.
- Seat Belt(s) must be worn when operating vehicle at all times. Key placement: cup holder. h.
- Vehicle must be shipped with its front tires in the straight forward position, the C. transmission in "Park" position and its parking brake fully engaged.

Specifications 2021 Genesis GV80 SUV

2.5L T I4 300hp, 2.5L T 300hp AWD, 3.5L T V6 375hp AWD

116.34" Wheelbase: 295.51cm Length: 194.69" 494.51cm Width: 76 97" 195.50cm Height: 73" w/rack 185.42cm 8.5" Min. Ground Clearance: 21.59cm

Wheels: 19", 20", 22" 48.26cm, 50.80cm, 55.88cm Est. Curb Weight 4.707 - 5.104 lbs. 2,135.06 - 2315.14 kg

* Subject to change without notice



17305 Von Karman, Suite 200 Irvine, CA 92614 714-435-2960

QUALITY

Page 1 of 1 Revision