



**ACCELERATED SERVICES**  
AUTO TRANSPORTERS

## Accelerated Services GM Quality Load Audit

- Ensure that the driver has mutilation protection in place (bib or coveralls) at all times when handling GM vehicles (safety vest when required)
- Are rings, watches, belt buckles, cell phones, etc. removed or covered before handling GM vehicles?
- Driver must be sure to follow the yard traffic flow rules and posted speed limit
- Ensure that VIN in driver's device matches the VIN on the dash or driver's door plate
- Be sure to perform a quality inspection. Start at the driver's door moving counter clock wise around the vehicle looking for impact damage. Be sure that all loose shipped items are accounted for
- Take extra care when inspecting driver's door, front and rear bumpers, quarter panels and roofs (top 5 damage areas)
- Ensure that loading skids are fully extended and decks are bridged before loading so no contact made
- Beep the horn before backing vehicle out of bay-don't drive through bays
- Do not exceed 5 MPH when loading or unloading GM vehicles.
- Ensure that all windows are rolled up
- Be sure to maintain 2" clearance for undercarriages, 3" between bumpers and a minimum of 5" between horizontal panels and decks above (roof, hood and deck lid)
- All vehicles must be secured with 4 soft tie straps, 1 over each tire, centered in tread, straight down into decking-NO ANGLES
- Are all decks pinned and secured?
- Load height must be measured before leaving yard and at the dealer on multiple drop loads to ensure 13'6"

Driver Signature \_\_\_\_\_ Date \_\_\_\_\_

Supervision Signature \_\_\_\_\_ Date \_\_\_\_\_