



# Technical Bulletin

HYUNDAI		KIA		NUMBER: HRG32002R0	TEST DATE: 02/13/2020
	<input checked="" type="checkbox"/>		<input type="checkbox"/>	MODEL YEAR: 2021	MODEL CODE: RG3
SUBJECT: <b>MY2021 Genesis G80</b>					

## COMMENTS:

### TRUCK HAULAWAY

- Upper Deck:** The Genesis G80 is approved for all upper deck positions. Avoid using wheel pocket extensions in the headrack position if driven forward due to possible insufficient undercarriage clearance.
- Lower deck restriction:** *All G80 (RG3's) must be driven onto the lower haulaway trailer facing the forward position only. If position #6 behind driver's cab requires a vehicle to be backed on, please use a higher profile vehicle.*
- Soft-tie wheel straps are required on all four (4) tires.** Chains and strap side pulls are prohibited. Strap contact with any vehicle component except tire tread is strictly prohibited.
- Use extreme caution:** Reduce loading speeds when approaching or exiting skids, tandem wheel area break-over points and when backing onto skids, as the front fascia can drop to less than 2" (5.08 cm) of ground clearance.

### RAIL LOADING

- Bi-level rail cars:** The Genesis G80 is approved for all loading positions. Always place chock setting in its highest setting that will maintain a minimum of 2" (5.08 cm) clearance between the chock any vehicle component.
- Tri-level rail cars:** Tri-levels may be utilized provided that bi-level railcars are unavailable. *Standard tri-levels are approved for 'C' deck loading only. Rail loaders must utilize next generation low-profile chocks only.* AutoMax, AutoFlex, and MultiMax are approved conveyances provided that only low-profile or grate lock chock systems are used to secure the G80. Limit '2' G80's on the flat surfaces of AutoMax 'A' decks. *The use of SCT and similar off-brands of the 5 7/8" copolymer chock systems are strictly prohibited on all multilevel railcars.*

### GENERAL

- The Genesis G80 has **limited ground clearance of approximately 5.5" (13.97 cm).**
- G80 must be shipped with its front tires in the straight forward position, the transmission in "Park" position and parking brake fully engaged.
- Always wear a seatbelt when operating vehicle.
- Key Placement: Cup Holder.



### Specifications

#### 2.5L Turbo I4 or 3.5L Twin Turbo V6

Wheelbase:	118.5"	300.99 cm
Length:	196.45"	498.99 cm
Width:	75"	190.50 cm
Height:	57.67"	146.49 cm
Min. Ground Clearance:	5.5"	13.97 cm
Wheels:	18", 19", 20"	45.72 cm, 48.26 cm, 50.80 cm
Est. Curb weights:	4,156 - 4,497 lbs.	1,885.13 - 2,039.81 kg

\* Subject to change without notice