

## MATERIAL SAFETY DATA SHEET

### SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Spindle Oil

Company: Genesis Industrial Pty Ltd

Address : 6 Ginger Street, Paget 4740

Phone: 0424 785349

Emergency Telephone Number: 131126 Poisons Information Centre

Recommended Use: Lubricant for precision apparatus, plastic modifier and stainless steel polish

### SECTION 2 HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

NOT A DANGEROUS GOODS ACCORDING TO THE CRITERIA OF THE ADG CODE

Symbols: None

Risk Phrases: None

Safety Phrases: S2 - Keep out of the reach of children

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### INGREDIENTS

Chemical Entity	CAS Number	Proportion	(%)
Mineral Oil	8012-95-1		100

### SECTION 4 FIRST AID MEASURES

#### FIRST AID TREATMENT

Swallowed: If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Eye: If in eyes, hold eyes open, flood with water for at least 15 minutes. If redness, burning, blurred vision, or swelling persist transport to nearest medical facility for additional treatment.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.

Inhaled: Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.

First Aid facilities: Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers.

Advice to Doctor: Treat symptomatically.

Additional Information: None available.

### SECTION 5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, water spray or fog, dry chemical powder. Do not use water in a jet.

Hazards from combustion products: Combustible, may emit fumes of oxides of carbon on combustion.

Precautions for Fire Fighters and Special Protective Equipment: Wear full protective clothing and self-contained breathing apparatus.

Additional Information: Combustible.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

Observe all local and national regulations.

Spills and Disposal: Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks.

Remove all sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination.

Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Methods and Materials for Containment and Clean Up Procedures: For small spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (> 1 205 litre drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

## SECTION 7 HANDLING AND STORAGE

Precautions for Safe Handling and Storage: Avoid breathing of or contact with material. Use in well ventilated areas.

Wash thoroughly after handling. Avoid contact with skin and eyes and clothing. Handle open containers in well ventilated area. Ensure that the workplace is ventilated such that the occupational exposure limit is not exceeded. Do not empty into drains. Do not eat, drink or smoke in contaminated areas. Before eating, drinking or smoking, remove contaminated clothing and wash hands. Do not store near strong oxidants.

Flammability: Combustible.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards: ASCC has set an exposure standard of 5mg/m<sup>3</sup> TWA (8hr) for oil mists.

Biological Limit Values: No biological limit allocated.

Personal Protective Equipment:

Respiratory Protection: If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter and select a filter for organic gases and vapours (boiling point > 65 Deg C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

Hand Protection: Use solvent resistant gloves (nitrile for longer term protection or PVC and neoprene for incidental splashes).

Eye Protection: Wear safety goggles.

Protective Clothing: Use chemical resistant glove/gauntlets, boots and apron. Skin protection not ordinarily required beyond standard issue work clothes.

Engineering Controls: Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists. Keep containers closed when not in use.

## SECTION 9 IDENTIFICATION

### PHYSICAL DESCRIPTION / CHEMICAL PROPERTIES

Appearance	Colourless liquid
Odour	Paraffinic hydrocarbon odour
pH:	N/A
Vapour Pressure	(kPa @ 20C): N/A
Vapour Density (air = 1)	N/A
Boiling Point (°C):	No Data available
Freezing/Melting Point (C):	No data available
Solubility in Water	<0.1 Wt%
Specific Gravity (g/ml @ 15C):	0.85
Flashpoint (C):	210 (degC)
Flammability Limits (%):	N/A

Auto Ignition Temperature (C): N/A

#### SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of use.

Conditions to Avoid: Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials: Strong oxidising agents.

#### SECTION 11 TOXICOLOGICAL INFORMATION

##### HEALTH EFFECTS

Acute:

Swallowed: Expected to be of low toxicity: Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis. Ingestion may result in diarrhoea.

Eye: Irritant.

Skin: Prolonged contact may cause defatting of skin which can lead to dermatitis.

Inhaled: Inhalation of vapours or mists may cause irritation to the respiratory system. Vapour concentrations above recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anaesthetic and may have other central nervous system effects

Chronic: Prolonged contact may cause defatting of skin which can lead to dermatitis.

#### SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic organisms: No acute toxicity to aquatic organisms is expected at the maximum water solubility of this material.

Mobility: Floats on water.

Persistence/degradability: No data.

#### SECTION 13 DISPOSAL CONSIDERATIONS

Disposal Methods: Ensure waste disposal conforms to local waste disposal regulations.

#### SECTION 14 TRANSPORT INFORMATION

UN Number: N/A Proper Shipping Name: N/A

Class: N/A Subsidiary Risk: N/A

Packing Group: N/A Hazchem Code: N/A

Special Precautions for User: None

#### SECTION 15 REGULATORY INFORMATION

Poisons Schedule : None

AICS : Listed

Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76:2010) : N/A

#### SECTION 16 OTHER INFORMATION

Further Information may be obtained by contacting Genesis Industrial on 0424 785349

The information sourced for the preparation of this document was correct and complete at the time or writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product.