


PUR Miniature CONTROL CABLE - 200 VOLT



Robotics (dull jacket) braid shield



Medical Micro Miniature Flex cable

PUR cables have excellent chemical and abrasion qualities. The durability of PUR is proven in high abuse applications. Temperatures rating is **-30° to +80°c** indoor and outdoor environments. Conforms to a wide rang of American and European approvals.

CABLEscience® custom manufactures these cables to OEM specifications in most any conductor count, shielding and cable configuration.

Construction: Bare or Tinned stranded copper, PP insulation and **PUR** jacket.

Part No. 20 ft. EXT.	Cond. No.	AWG. SIZE	Cond Ins.OD”	Amp rating	JACKET	Cable O.D. “
FLX302	2	30	0.024	350MA	Single	.098
FLX303	3	30	0.024	350MA	Single	.105
FLX304	4	30	0.024	350MA	Single	.110
FLX305	5	30	0.024	350MA	Single	.115
FLX307	7	30	0.024	350MA	Single	.125
FLX3412	12	34	0.016	200MA	Double	.160
FLX3436	36	34	0.016	200MA	Double	.215
PUR3612	12	36	0.014	100MA	Double	.110
PUR36363	36	36	0.014	100MA	Double	.150
PUR223-20	3	22	0.050	1	Double	.170
PUR205-20	5	20	0.056	1	Double	.210