




Technical Specification

- 1.Connection type Clevis
- 2.Leakage Distance, 11 inches (279mm)
- 3.M&E strength, 40000 lbs (178kN)
- 4.Tension proof. 20000 lbs (89kN)
- 5.Impact strength, 90 inch-lbs (10N-m)
- 6.Low-frequency dry flashover voltage 80kV
- 7.Low-frequency wet flashover voltage 50kV
- 8.Critical impulse flashover voltage,positive 125kV
- 9.Critical impulse flashover voltage,negative 130kV
- 10.Low-frequency puncture voltage 110kV
- 11.Radio-influence Voltage:
 - Low-frequency test voltage 10kV
 - Maximum RIV at 1,000 kHz 50 μ V
- 12.Colour Grey
- 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise.

7	Split pin	1	Stainless Steel																		
6	Cylinder Pin	1	Steel,Hot dip galvanized																		
5	Cushion	1	Asphalt																		
4	Cement		Portland																		
3	Pin	1	Forged Steel,Hot dip galvanized																		
2	Cap	1	Hot dip galvanized cast iron																		
1	Sheel	1	High Strength Pocolain																		
Item	Title/Name	Quantity	Note																		
<table border="1" style="width: 100%;"> <thead> <tr> <th colspan="2">Revision details</th> <th>Signature</th> <th>Approved</th> </tr> </thead> <tbody> <tr> <td rowspan="3" style="text-align: center; vertical-align: middle;">  </td> <td>Reference</td> <td colspan="2">52-10-H</td> </tr> <tr> <td>VE No.</td> <td colspan="2">5210HCG1</td> </tr> <tr> <td>Rev</td> <td colspan="2">0</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">Vanguard Electric,LLC</td> </tr> </tbody> </table>				Revision details		Signature	Approved		Reference	52-10-H		VE No.	5210HCG1		Rev	0				Vanguard Electric,LLC	
Revision details		Signature	Approved																		
	Reference	52-10-H																			
	VE No.	5210HCG1																			
	Rev	0																			
		Vanguard Electric,LLC																			
Weight		27.09 lbs	Page 1 of 1																		