


Technical Specification

- | | |
|--|---------------------|
| 1.Connection type | B&S Type K |
| 2.Leakage Distance, | 15 inches (381mm) |
| 3.M&E strength, | 50000 lbs (222kN) |
| 4.Tension proof.kN | 25000 lbs (111kN) |
| 5.Impact strength, | 90 inch-lbs (10N-m) |
| 6.Low-frequency dry flashover voltage | 80kV |
| 7.Low-frequency wet flashover voltage | 50kV |
| 8.Critical impulse flashover voltage,positive | 140kV |
| 9.Critical impulse flashover voltage,negative | 140kV |
| 10.Low-frequency puncture voltage | 125kV |
| 11.Radio-influence Voltage: | |
| Low-frequency test voltage | 10kV |
| Maximum RIV at 1,000 kHz | 50 μ V |
| 12.Colour | Grey |
| 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise. | |

Item	Title/Name	Quantity	Note
6	Split pin	1	Stainless steel
5	Cushion	1	Asphalt
4	Cement		Portland
3	Pin	1	Forged Steel,Hot dip galvanized
2	Cap	1	Hot dip galvanized cast iron,
1	Shell	1	High strength pocolain
		Revision details	
		Signature	Approved
		Reference	52-11
		VE No.	52110BG1
Disc Insulator		Rev	0
		Vanguard Electric,LLC	
Weight	21.59 lbs	Page 1 of 1	