


Technical Specification

- | | |
|--|-----------------------|
| 1.Connection type | B&S Type B |
| 2.Leakage Distance, | 11-1/2 inches (292mm) |
| 3.M&E strength, | 15000 lbs (67kN) |
| 4.Tension proof. | 7500 lbs(33.4kN) |
| 5.Impact strength, | 55 inch-lbs (6N-m) |
| 6.Low-frequency dry flashover voltage | 80kV |
| 7.Low-frequency wet flashover voltage | 50kV |
| 8.Critical impulse flashover voltage,positive | 125kV |
| 9.Critical impulse flashover voltage,negative | 130kV |
| 10.Low-frequency puncture voltage | 110kV |
| 11.Radio-influence Voltage: | |
| Low-frequency test voltage | 10kV |
| Maximum RIV at 1,000 kHz | 50 μ V |
| 12.Colour | Grey |
| 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise. | |

6	Split pin	1	Stainless Steel		
5	Cushion	1	Asphalt		
4	Cement		Portland		
3	Pin	1	Forged Steel,Hot dip galvanized		
2	Cap	1	Hot dip galvanized cast iron		
1	Porcelain	1	High Strength Pocolain		
Item	Title/Name	Quantity	Note		
		Revision details		Signature	Approved
		Disc Insulator	Reference	52-3-L	
			VE No.	5203LBG1	
			Rev	0	
Weight	11.01 lbs	Page 1 of 1		Vanguard Electric,LLC	