


Technical Specification

- | | |
|--|--------------------|
| 1.Connection type | Clevis |
| 2.Leakage Distance,mm | 11 inches (279mm) |
| 3.M&E strength, | 25000 lbs (111kN) |
| 4.Tension proof. | 12500 lbs (55.5kN) |
| 5.Impact strength, | 60 inch-lbs (7N-m) |
| 6.Low-frequency dry flashover voltage | 80kV |
| 7.Low-frequency wet flashover voltage | 50kV |
| 8.Critical impulse flashover voltage,positive | 125kV |
| 9.Critical impulse flashover voltage,negative | 130kV |
| 10.Low-frequency puncture voltage | 110kV |
| 11.Radio-influence Voltage: | |
| Low-frequency test voltage | 10kV |
| Maximum RIV at 1,000 kHz | 50 μ V |
| 12.Colour | Grey |
| 13.All Tolerances are According to ANSI C29.2B Unless Specified Otherwise. | |

Item	Title/Name	Quantity	Note				
7	Split pin	1	Stainless Steel				
6	Cylinder Pin	1	Steel,Hot dip galvanized				
5	Cushion	1	Asphalt				
4	Cement		Portland				
3	Pin	1	Forged Steel,Hot dip galvanized				
2	Cap	1	Hot dip galvanized cast iron				
1	Porcelain	1	High Strength Pocerlain				
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%;"></td> <td style="width:30%;"></td> <td style="width:10%; text-align: center;">Signature</td> <td style="width:10%; text-align: center;">Approved</td> </tr> </table>						Signature	Approved
		Signature	Approved				
		Revision details					
		Reference	52-6-L				
		VE No.	5206LCG1				
		Rev	0				
Weight	16.52 lbs	Vanguard Electric,LLC					
		Page 1 of 1					