

### SPECIAL PURPOSE TWO INLET, TWO OUTLET FIXED REGULATORS

**Model Number:** 1000AL-DxxxF  
Compact Fixed Flow Aluminum Regulators

Preece Precision's lightweight fixed outlet performance regulators are used in a variety of configurations. Each regulator has two high pressure and two low pressure ports. There are many specialty applications this unique pressure regulator can be utilized including air shifter, parachute, suspension, transmission and other pneumatic operated devices used in automotive and powersports racing applications.



#### Specifications:

- Two high pressure ports, two low pressure ports
- (2) 1/4" Female NPT Inlet (Inlet Pressure Source)
- (2) 1/8" Female NPT Outlets (Regulated Pressure)
- Designed for Carbon Dioxide (Co2), Nitrogen or Air
- High flow capacity
- 35CFM (cubic feet per minute)
- Light weight aluminum body, brass piston

#### AVAILABLE STOCK PRESSURES:

100PSI, 125PSI, 150PSI, 200PSI, 475PSI

*Can be tuned by end users to any pressure from 50 to 500PSI*

#### DIMENSIONS

2.00 x 1 1/4  
0.2 LBS

### VARIOUS CGA320 TANK CONNECTIONS



One -4AN Flare Fitting Outlet

Low Pressure Delivery Gauge

#### Regulator Only Ordering:

1000AL-D100F	100PSI
1000AL-D125F	125PSI
1000AL-D150F	150PSI
1000AL-D200F	200PSI
1000AL-D475F	475PSI

### BOTTOM MOUNT AND BACK MOUNT GAUGES



One -4AN Flare Fitting Outlet

Two -4AN Flare Fitting Outlets

