

# High pressure cleaner

Cold water, mobile - series 4x4

KD1140



Type		KD1140-Standard	KD1140-Premium
Voltage	3/400-415V/ 50Hz	<ul style="list-style-type: none"> <li>▶ 10m HP-Hose DN08 - 315bar</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Spray-Lance 900mm c/w Vario-Nozzle</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ 25l Cleaning-Detergent tank</li> <li>▶ Detergent-Supply c/w Low-Pressure Injector and metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>▶ Hose-Reel</li> <li>▶ 15m HP-Hose DN08 - 315bar</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Spray-Lance 900mm c/w Nozzle-Protection</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>▶ 17l Water-Storage tank</li> <li>▶ Water-Supply separation acc. water reg.</li> <li>▶ Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-250bar/ 3-25MPa		
Max. pressure	270bar/ 27MPa		
Discharge capacity	300 - 1.000l/h		
Nozzle size	045		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	7,4kW / 13,1A		
Electrical protection	3x16A slow-blowing		
Weight net / with package		89 kg / 113kg	97 kg / 121 kg
Dimensions device / with package (LxWxH)		980 x 620 x 1000 mm / 1050 x 760 x 1180 mm	1020 x 620 x 1000 mm / 1050 x 760 x 1180 mm
<p>Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar</p>			
Art. No.		551001	551002