

PORT INFO INDONESIA
BATAM PORT - BATU AMPAR/ KABIL/ SEKUPANG/ TANJUNG UNCANG

GENERAL INFORMATION	
A.	NAME OF PORT : BATU AMPAR
A.1	PUBLIC WHARF
	ANCHORAGE POSITION / : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE : COMPULSORY 24 HRS
	TUGGAGE : COMPULSORY
	CHANNEL DRAFT : 9 MTR LWS
	DRAFT AT ALONGSIDE : 8 MTR LWS
	LENGTH OF WHARF : 1250 MTR
	250 MTR = MAX DRAFT 8 MTR (SOUTH JETTY)
	1000 MTR = MAX DRAFT 5 - 7 MTR
	MAX. LOA : 180 M
	MAX. DWT : DWT 35,000
	CARGO : CONTAINER, GENERAL CARGO, PROJECT VESSEL/OFF SHORE SUPPORT; SUPPLY, CREW CHANGE
	STEEL PLATE, H BEAM, CEMENTS, ETC.
	FRESH WATER SUPPLY : AVAILABLE
	BUNKER SUPPLY : AVAILABLE
A.2	MC. DERMOTT (PRIVATE PORT)
	ANCHORAGE POSITION / : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE : COMPULSORY / DAY LIGHT ONLY
	TUGGAGE : COMPULSORY
	CHANNEL DRAFT : 9 MTR LWS
	DRAFT AT ALONGSIDE : 10 MTR LWS
	LENGTH OF WHARF : 600 MTR
	PRIVATE PORT FOR OIL RIG / FACTORY MC DERMOTT
	FRESH WATER + BUNKER SUPPLY : NOT AVAILABLE
A.3	BATU MERAH / PT. BANGUN ADYA BAHAN (PRIVATE PORT)
	ANCHORAGE POSITION / : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE : COMPULSORY / DAY LIGHT ONLY
	TUGGAGE : COMPULSORY
	DRAFT AT ALONGSIDE : 5.5 MTR
	LENGTH OF WHARF : 110 MTR
	PRIVATE PORT FOR PT. BANGUN ADYA BAHAN
	LOADING/UNLOADING FOR FACTORY MATERIAL AND OFF SHORE SUPPORT; SUPPLY, CREW CHANGE
	FRESH WATER + BUNKER SUPPLY : AVAILABLE
A.4	BATU MERAH / PT. PROFAB (PRIVATE PORT)
	ANCHORAGE POSITION / : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOT BOARDING GROUND : 01 - 10 - 05 N / 103 - 59 - 00 E
	PILOTAGE : COMPULSORY / DAY LIGHT ONLY
	TUGGAGE : COMPULSORY
	DRAFT AT ALONGSIDE : 4.5 MTR
	LENGTH OF WHARF : 100 MTR
	PRIVATE PORT FOR LOADING/UNLOADING PRODUCT PT. PROFAB
	FRESH WATER + BUNKER SUPPLY : AVAILABLE
B.	NAME OF PORT : KABIL
B.1	KABIL - PTK
	ANCHORAGE POSITION / PILOT : 01 - 07 - 00 N / 104 - 10 - 30 E
	BOARDING POS
	PILOTAGE : COMPULSORY 24 HRS
	TUGGAGE : COMPULSORY
	LENGTH OF WHARF : 75 METERS



BBI AGENCY
YOUR LOGISTICS. OUR COMMITMENT.

PT BANDAR BERLAYAR INTERNASIONAL

Tel: +62 21 2528 613, 614, 615, 616 | Fax: +62 21 2528 613

AOH: +62 811 1609 711 | Email: ptbbi@ptbbi.net

Website: ptbbi.net

MAXIMUM DWT	:	5,000 DWT
MAXIMUM A/SIDE DRAFT	:	6 METERS
CARGO	:	GENERAL CARGO, FLOATING REPAIR WITH SPECIAL PERMISSION

		OFF SHORE SUPPORTING, CREW CHANGE, SUPPLY
FRESH WATER SUPPLY	:	AVAILABLE
BUNKER SUPPLY	:	AVAILABLE

B.2 KABIL - CPPI

PORT POSITION	:	01 - 06 - 30 N / 104 - 08 - 25 E
PILOT BOARDING GROUND	:	01 - 07 - 00 N / 104 - 10 - 30 E
ANCHORAGE POSITION	:	01 - 06 - 00 N / 104 - 10 - 00 E
		01 - 06 - 00 N / 104 - 11 - 18 E
		01 - 06 - 48 N / 104 - 11 - 18 E
		01 - 06 - 48 N / 104 - 10 - 00 E
PILOTAGE	:	COMPULSORY
IN/OUT BERTHING & UNBERTHING	-	24 HRS
TUG BOAT	:	COMPULSORY
STANDART TIME	:	GMT + 7 HRS
COMMUNICATION	:	VHF CH 16 / CH 8
		CITRA PORT CONTROL : TEL (0778) 7202111
RAIN SEASON	:	MAY TO SEPTEMBER, WORST IN OCTOBER TO FEBRUARY
TIDAL RISE	:	MHWS 320 CM / LWS/ZO 160 CM
WATER DENSITY	:	1.025
PORT RESTRICTON		
OUTER ROAD DEPTH	:	10 - 15 MTRS (MLWS)
INNER ROAD DEPTH	:	13 MTRS (MLWS)
CHANNEL DEPTH	:	13 MTRS (MLWS)

BERTH:

1. BERTH PARTICULARS (EXPORT/IMPORT)

COORDINATE	:	01 - 06 - 35.4 N / 104 - 08 - 57.8 E
TYPE	:	MARGINAL / PILLING CONCRETE FLOOR CONSTRUCTION
DIMENSION	:	176 X 29 M2
DEPTH	:	10 MTR LWS
MAX DWT	:	30,000 MT DWT

2. SPECIAL BERTH (SMALL CRAFT)

COORDINATE	:	01 - 06 - 43.3 N / 104 - 08 - 45.1 E
TYPE	:	JETTY / PILLING CONCRETE FLOOR CONSTRUCTION
BREASTING DOLPHIN	:	2 UNITS OF 5,4 X 3 M2 AND 2 UNITS OF 3,4 X 2,4 M2
MOORING DOLPHIN	:	2 UNITS OF 3,5 X 3,5 M2
DEPTH	:	5 MTR LWS
MAX DWT	:	2,000 MT DWT

3. LANDING CRAFT (RORO)

COORDINATE	:	01 - 06 - 46.3 N / 104 - 08 - 46.8 E
TYPE	:	JETTY / PILLING CONCRETE FLOOR CONSTRUCTION
BREASTING DOLPHIN	:	2 UNITS OF 5,6 X 4,7 M2
MOORING DOLPHIN	:	2 UNITS OF 4,2 X 4,2 M2
DEPTH	:	5 MTR LWS
FOR VESSEL	:	LCT / RORO

4. JETTY NO 5 & 6 / EXTENTION JETTY

COORDINATE	:	01 - 06 - 35.4 N / 104 - 08 - 57.8 E
TYPE	:	MARGINAL / PILLING CONCRETE FLOOR CONSTRUCTION
DIMENSION	:	290 X 36 M2
DEPTH	:	12.5 MTR LWS
MAX DWT	:	40,000 MT DWT

STEVEDORE WORKING HRS	:	3 SHIFT 24 HRS
CRANE & FORKLIFT	:	MOBILE CRANE 50 - 80 MT
		CRAWLER CRANES 100 - 250 MT
		FORKLIFT AVAILABLE 2 - 7 MT

FRESH WATER SUPPLY	:	80 MT / HOUR BY PIPE LINE
BUNKER SUPPLY	:	AVAILABLE
WATCHMAN	:	ISPS CODE COMPLIANCE
CARGO	:	GENERAL CARGO, PROJECT VESSEL FOR SUPPLY/CREW CHANGE, IRON ORE, STEEL PIPE,

		STEEL PLATE, RO/RO VESSEL



BBI AGENCY
YOUR LOGISTICS. OUR COMMITMENT.

PT BANDAR BERLAYAR INTERNASIONAL

Tel: +62 21 2528 613, 614, 615, 616 | Fax: +62 21 2528 613

AOH: +62 811 1609 711 | Email: ptbbi@ptbbi.net

Website: ptbbi.net

B.3 KABIL - CPO	
PORT POSITION	: 01 - 04 - 05 N / 104 - 09 - 00 E
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOATRDRING POS	
PILOTAGE	: COMPULSORY 24 HRS
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 410 METERS
MAX CHANNEL DRAFT	: 13 MTR ON HIGH TIDE
MAXIMUM A/SIDE DRAFT	: 13 METERS (Can berth in day and night time)
MAXIMUM DWT	: 40,000 DWT
MAXIMUM LOA	: 200 METERS
CARGO	: FOR LIQUID CARGO
SHIPPER	: SYNERGI OIL NUSANTARA, PATRA NIAGA. MUSIMAS, ECO GREEN.
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
B.4 KABIL - BOSOWA	
PORT POSITION	-
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOARDING POS	
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 110 METERS
	Available dophinS 2 unit with 150 mtr of range, vessel with LOA 180 also can alongside
MAX ALONGSIDE DRAFT	: 10.5 MTR ON HIGH TIDE
CARGO	: CEMENT / CLINKER IN BULK
SHIPPER	: SEMEN BATAM / BOSOWA
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
B.5 KABIL - SHIPYARD	
PORT POSITION	:
ANCHORAGE POSITION / PILOT	: 01 - 07 - 00 N / 104 - 10 - 30 E
BOARDING POS	
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
BUNKER SUPPLY	: AVAILABLE
FRESH WATER SUPPLY	: AVAILABLE
WHARF	:
	NINDA PRATAMA : LENGTH OF WHARF 400 MTR / DRAFT 5 - 7 MTR
	ANGGREK HITAM/JSE : MAX DRAFT 3 - 5 MTR ON HIGH TIDE
	NEXUS : MAX DRAFT 3 - 5 MTR ON HIGH TIDE / 110 MTR LENGTH OF WHARF
	ETC....
C. NAME OF PORT	: SEKUPANG
C.1 PASSANGER / PELNI TERMINAL	
PILOT BOARDING POSITION	: 01 - 10 - 00 N / 103 - 56 - 05 E (SAMBU PSTN)
PORT POSITION	: 01 - 07 - 30 N / 103 - 55 - 22 E
ANCHORAGE POSITION /	: 01 - 07 - 36 N / 103 - 53 - 42 E
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
LENGTH OF WHARF	: 180 METERS
MAXIMUM DWT	: 10,000 DWT
MAXIMUM LOA	: 170 METERS
MAXIMUM A/SIDE DRAFT	: 8 - 9 METERS
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
C.2 PRIVATE PORT FOR SHIPYARD	
ANCHORAGE POSITION	: 01 - 09 - 05 N / 103 - 55 - 01 E
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
LENGTH OF WHARF	: PRIVATE JETTY / VARIOUS SHIPYARD WITH DRAFT 2 - 7 MTR
	BRITOIL : 7 MTR

	NINDA PRATAMA : 7 MTR ETC....
D. NAME OF PORT	: TANJUNG UNCANG PORT (PRIVATE PORT FOR SHIPYARD)
PILOT BOARDING POSITION	: 01 - 10 - 00 N / 103 - 56 - 05 E (SAMBU PSTN)
ANCHORAGE POSITION	: 01 - 09 - 05 N / 103 - 55 - 01 E
MAXIMUM ANCHORAGE DRAFT	: 20 MTR
PILOTAGE	: COMPULSORY DAY LIGHT ONLY
TUGGAGE	: COMPULSORY
FRESH WATER SUPPLY	: AVAILABLE
BUNKER SUPPLY	: AVAILABLE
LENGTH OF WHARF	: PRIVATE JETTY / VARIOUS SHIPYARD WITH DRAFT 2 - 8 MTR
	ASL : 7.5 MTR
	BATAMEC : 7.0 MTR
	DDW GRAHA : 4.5 MTR
	DDW NANINDAH : 6 MTR
	DDW PERTAMA : 8 MTR
	ETC.....
DDW PERTAMA PORT POSITION	: 01 - 05 - 22 N / 103 - 53 - 13 E 01 - 05 - 63 N / 103 - 53 - 55 E

OTHER USEFUL INFORMATION

LOCAL TIME	: GMT + 7 HRS (SPORE-1 HR)
WHEATHER CONDITION	: SPEED WIND 15 Bft PEAK 3kph BEARING 30 ° , TEMPERATURE 31°C / 87°F WITH CLOUDS,MIST
WORKING HOURS	: 24 HRS (0600-0700 HRS, 1200-1300 HRS, 1800-1900 HRS AND 2400-0100 HRS IS MEAL TIME)
TYPE OF TERMINAL	: PUBLIC TERMINAL EXCEPT TANJUNG UNCANG PORT, SEKUPANG PORT, MC. DERMOTT AND BATU MERAH

SHORE CRANE HIRE AT BATAM

Crance Capacity (tons)	
45-50	: AVAILABLE
80 - 100	: AVAILABLE
125	: AVAILABLE
150	: AVAILABLE
250	: AVAILABLE

ALL INFORMATION ABOVE PROVIDED IN GOOD FAITH BY BBI AGENCY.

BBI AGENCY - AS AGENTS ONLY