

Safety Data Sheet



according to OSHA Hazard Communication
29 CFR Part 1910.1200

according to Regulation (EC)
No. 1907/2006 Article 31

Section 1. Identification

Product Code: SY0049

Product Name: SB LF YEL CAN LOW VOC

Product Type: SB Paint

Recommended Use: Traffic Markings

Supplied by: Ennis-Flint
4161 Piedmont Parkway, Suite 370
Greensboro, NC 27410
T: 800.331.8118 (For Technical Inquiries)

Emergency Telephone: Chemtec 1-800-424-9300

Section 2. Hazard(s) Identification

EMERGENCY OVERVIEW: Extremely Flammable/Sensitizer. This product contains a component suspected of causing cancer. However, it is in a non-respirable form and Inhalation is unlike to occur from exposure. This classification is relevant when exposed to dust or powder form only (e.g. sanding, grinding). May cause fire. In use, may form flammable/explosive vapour-air mixture.

Classification

Symbol(s) of Product



Signal Word
Danger

GHS Named Chemicals On Label
Toluene, Acetone

Possible Hazards

27% of the mixture consists of ingredient(s) of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
STOT, single exposure, category 3, NE	H336
Carcinogenicity, category 2	H351
Reproductive Toxicity, category 2	H361

STOT, repeated exposure, category 2 H373

Highly flammable liquid and vapour.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child. Classified Category 2
suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Section 3. Composition/Information on ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
Calcium Carbonate	1317-65-3	25-50		
Acetone	67-64-1	10-25	GHS02-GHS07	H225-319-336
Toluene	108-88-3	2.5-10	GHS02-GHS07-GHS08	H225-304-315-336-361-373
Titanium Dioxide	13463-67-7	1.0-2.5	GHS08	H351
Crystalline Silica, Quartz	14808-60-7	0.1-1.0	GHS08	
Methyl Ethyl Ketoxime	96-29-7	0.1-1.0	GHS05-GHS07-GHS08	H302-317-318-351
Dipropylene glycol monomethyl ether	34590-94-8	<0.1		

Chemical Name	CAS-No.	EINECS No.	REACH Reg No.	M-Factors
Calcium Carbonate	1317-65-3	215-279-6	not available	0
Acetone	67-64-1	200-662-2	not available	0
Toluene	108-88-3	203-625-9	not available	0
Titanium Dioxide	13463-67-7	236-675-5	not available	0
Crystalline Silica, Quartz	14808-60-7	238-878-4	not available	0
Methyl Ethyl Ketoxime	96-29-7	202-496-6	not available	0
Dipropylene glycol monomethyl ether	34590-94-8	252-104-2	not available	0

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures

FIRST AID - INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. Consult a physician if symptoms persist.

FIRST AID - SKIN CONTACT: Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and launder before reuse. Consult a physician if symptoms persist.

FIRST AID - EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician if symptoms persist.

FIRST AID - INGESTION: Do NOT induce vomiting. If conscious, rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material may polymerize explosively when involved in a fire. Runoff to sewer may create fire or explosion hazard. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors can spread along ground and collect in low or confined areas (sewers, basements, tanks). Water spray may reduce vapor, buy may not prevent ignition in closed spaces.

SPECIAL FIREFIGHTING PROCEDURES: Flammable. Cool fire-exposed containers using water spray. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Section 6. Accidental release measures

ENVIRONMENTAL PRECAUTIONS: Prevent entry into waterways, sewers, basements or confined areas. Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use personal protective equipment. Ensure adequate ventilation. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically. Keep in suitable and closed containers for disposal. Use clean non-sparking tools to collect absorbed material.

Section 7. Handling and storage



HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Ensure adequate ventilation. Avoid breathing vapor, mists or dust. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Observe good industrial hygiene practices. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use only in an area containing flame proof equipment.

STORAGE: Keep containers tightly closed in a cool, well-ventilated place. Store away from heat and sources of ignition. Keep in properly labeled containers.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Calcium Carbonate			15 mg/m ³	
Acetone	250 ppm	500 ppm	750 PPM	
Toluene	20 ppm		200 PPM	300 ppm
Titanium Dioxide	10 mg/m ³		15 mg/m ³	
Crystalline Silica, Quartz	0.025 mg/m ³		0.05 mg/m ³	
Methyl Ethyl Ketoxime				
Dipropylene glycol monomethyl ether	100 ppm	150 ppm	100 ppm	
Name	Percentage	VME mg/m³	VME ppm	OEL Note
Acetone	10-25	1210	500	1000 PPM
Toluene	2.5-10	191	50	50 PPM
Titanium Dioxide	1.0-2.5	10	0	15 mg/m ³

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



SKIN PROTECTION: Protective gloves/clothing.



EYE PROTECTION: Tightly fitting safety goggles.



OTHER PROTECTIVE EQUIPMENT: Eyewash stations, safety showers, ventilation systems. Ventilation system should be explosion proof.



HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

Section 9. Physical and chemical properties

Appearance:	No Information	Physical State:	Liquid
Odor:	Aromatic solvent/acetone	Odor Threshold:	Not Established
Density, g/cm3:	1.433	pH:	No Information
Freeze Point, °C:	NI	Viscosity:	NI
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/ water:	NI
Decomposition Temp., °C:	NI		
Boiling Point, °C:	N.I.	Explosive Limits, vol%:	N.I.
Combustibility:	Supports Combustion	Flash Point, °C:	-20
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temp., °C:	NI
Vapor Density:	Heavier than air	Vapor Pressure:	NI

(See "Other Information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Dust formation. Heat, flames and sparks.

INCOMPATIBILITY: Strong acids. Chlorinated compounds. Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides. Hydrocarbons. Carbon dioxide.

HAZARDOUS POLYMERIZATION: Hazardous polymerization does not occur.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: May cause allergic skin reaction. Irritating to skin. Repeated exposure may cause skin dryness or cracking.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Irritating to eyes.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause irritation to mucous membranes. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. Recurrent overexposure may result in liver and kidney injury.

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen. Repeated contact may cause allergic reactions.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Gas LC50</u>
1317-65-3	Calcium Carbonate	> 2000 mg/kg	> 2000 mg/kg	>20001 ppm
67-64-1	Acetone	5800 mg/kg Rat	>15700 mg/kg Rabbit	N.I.
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	N.I.
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	>20001 ppm
14808-60-7	Crystalline Silica, Quartz	>2000 mg/kg	> 2000 mg/kg	>20001 ppm
96-29-7	Methyl Ethyl Ketoxime	930 mg/kg Rat	> 2000 mg/kg	>20001 ppm
34590-94-8	Dipropylene glycol monomethyl ether	5350 mg/kg Rat	> 2000 mg/kg	>20001 ppm
N.I. - No Information				

Section 12. Ecological information

ECOLOGICAL INFORMATION: The environmental impact of this product has not been fully investigated.

Further Ecological Information

Contains the following Ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Bio. Conc. Factor (BCF)</u>	<u>Octanol-water par. Coeff (KOW)</u>
67-64-1	Acetone	3	-0.24
108-88-3	Toluene	13 - 90	2.65
13463-67-7	Titanium Dioxide	not available	not available
14808-60-7	Crystalline Silica, Quartz	not available	not available
96-29-7	Methyl Ethyl Ketoxime	0.5 - 5.8	not available

Section 13. Disposal considerations



Product

DISPOSAL METHOD: This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not re-use empty containers. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Code: 080111 waste paint/var.w.org.solv/DS

Uncleaned Packaging

European Waste Code: 150110 packaging dangerous residuals

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Road Transport

UN Number: UN1263
Packing Group: II
Shipping Name: Paint
Primary Shipping Hazard: No Information
Road Tunnel Transport Code: NI
ADRI/RID Class: 3

Sea Transport

UN Number:	UN1263
IMDG/GGVSee Class:	3
EmS-No:	F-E, S-E
Packing Group:	II
Shipping Name:	Paint
Primary Shipping Hazard:	No Information
Marine Pollutant:	Not A Marine Pollutant
Shipping Hazard(Marine Pollutant):	No Information

Air Transport

UN Number:	UN1263
ICAO/IATA Class:	3
Packing Group:	II
Shipping Name:	Paint
Primary Shipping Hazard:	No Information

Section 15. Regulatory information**U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Reproductive toxicity, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3
Ethylbenzene	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are hazardous or among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Proprietary	Proprietary
Nepheline Syenite	37244-96-5

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Proprietary	Proprietary
Nepheline Syenite	37244-96-5

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Titanium Dioxide	13463-67-7
Crystalline Silica, Quartz	14808-60-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: B2 D2

Denmark

B-Value: 0.000000

France

Storage Conditions: No Information

Professional Illness Table:

<u>CAS Number</u>	<u>Chemical Name</u>	<u>Professional Illness</u>
67-64-1	Acetone	not available
13463-67-7	Titanium Dioxide	not available
14808-60-7	Crystalline Silica, Quartz	not available
96-29-7	Methyl Ethyl Ketoxime	not available

Germany

VbF-Class: No Information

WGK-class: 3

Remarks: WGK 0 = In general not a water pollutant

WGK 1 = weak water pollutant

WGK 2 = water pollutant

WGK 3 = severe water pollutant

Processing restrictions:*

Incident Regulation:

No Information

Spain

Storage Conditions: No Information

Switzerland

VOC-Value: 27.18

United Kingdom

Storage Conditions: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 3/25/2020

Supersedes Date:

1/10/2020

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

NFPA Ratings:

Health:	2	Flammability:	3	Reactivity:	0	Hazards:	None
---------	---	---------------	---	-------------	---	----------	------

Volatile Organic Compounds, gr/ltr: 147

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.

H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS05



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed. Any use of the product not in conformance with this SDS or in combination with any other product or process is the responsibility of the user.

