

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 06/07/2018 Revision date: 09/20/2018 Version: 3.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Palmer Mirro-Mastic ®

Product code : Not available.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Mirror Adhesive

1.3. Details of the supplier of the safety data sheet

Palmer Products Corporation 146 St. Matthews Avenue Louisville, KY 40207 - USA T 502.893.3668

1 502.893.3008

palmer@mirro-mastic.com

1.4. Emergency telephone number

Medical Emergency Phone Number : (CHEMTREC): 1-800-424-9300 (24 Hours)
Transport Emergency Phone Number : (CHEMTREC): 1-800-424-9300 (24 Hours)

#### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

GHS-US classification Flammable Liquid 4

### 2.2. Label elements

**GHS-US** labelling

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

Combustible liquid

Precautionary statements (GHS-US)

Keep away from flames and hot surfaces. - No smoking. Wear protective gloves/eye protection/face protection. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with

local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Asphalt, oxidized	(CAS-No.) 64742-93-4	40 - 50
Naphtha, petroleum, hydrotreated heavy	(CAS-No.) 64742-48-9	20 - 30
Kaolin	(CAS-No.) 1332-58-7	10 - 20
Cellulose	(CAS-No.) 9004-34-6	5 - 10

<sup>\*</sup>Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn.

If irritation persists, get medical attention.

First-aid measures after ingestion

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

09/20/2018 EN (English) Page 1



## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of

carbon.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel.

#### 6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable

container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking, Avoid contact with skin and eyes, Avoid breathing

dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using

do not eat, drink or smoke.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container fightly closed and in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

Not available.

#### SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

Not applicable				
Cellulose (9004-34-6)				
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³		
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)		
NIOSH	NIOSH REL (TWA) (mg/m²)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)		

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

Not applicable

09/20/2018 EN (English) 2/5



## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Kaolin (1332-58-7)		
ACGIH	Local name	Kaolin
ACGIH	ACGIH TWA (mg/m²)	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
ACGIH	Remark (ACGIH)	Pneumoconiosis
ACGIH	Regulatory reference	ACGIH 2017
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m²)	10 mg/m³ (total dust) 5 mg/m² (respirable dust)

#### **Exposure controls**

Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection None necessary under normal conditions of use. Wear gloves if handling large quantities.

Eye protection Safety glasses or goggles are recommended when using product.

None necessary under normal conditions of use. Skin and body protection

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Environmental exposure controls Maintain levels below Community environmental protection thresholds.

Other information Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

3/5

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Physical state : Liquid Appearance Heavy Paste Colour Black Odour : Solvent

Odour threshold No data available pΗ No data available Melting point No data available Freezing point No data available Boiling point No data available

Flash point 160 °F

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) Flammable **Explosive limits** No data available Explosive properties : No data available Oxidising properties No data available Vapour pressure No data available

Relative density . 12

Relative vapour density at 20 °C No data available Solubility No data available Partition coefficient: n-octanol/water No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

#### 9.2. Other information

No additional information available



## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

#### Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

#### 10.5. Incompatible materials

Strong acids. Oxídizers.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

#### SECTION 11: Toxicological information

#### Information on toxicological effects

Acute toxicity	: Not classified.	
Asphalt, oxidized (64742-93-4)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
Cellulose (9004-34-6)		
LD50 oral rat	> 5 g/kg	
LC50 inhalation rat	> 5800 mg/m³ (Exposure time: 4 h)	
Naphtha, petroleum, hydrotreated heavy (64	742-48-9)	
LD50 oral rat	> 6000 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat	> 8500 mg/m³ (Exposure time: 4 h)	
Kaolin (1332-58-7)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 5000 mg/kg	
Skin corrosion/irritation	: Not classified.	
Serious eye damage/irritation	: Not classified.	
Respiratory or skin sensitisation	: Not classified.	
Germ cell mutagenicity	: Not classified.	
Carcinogenicity	: Not classified.	
Asphalt, oxidized (64742-93-4)		
IARC group	2A - Probably carcinogenic to humans	
In OSHA Hazard Communication Carcinogen list	Yes	
Reproductive toxicity	: Not classified.	
STOT-single exposure	: Not classified.	

reproductive toxicity	. NOI Classificu.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Symptoms/injuries after inhalation	May cause reeniratory tract irritation

May cause respiratory tract irritation.

Symptoms/injuries after skin contact : May cause skin imitation. Symptoms may include redness, drying, defatting and cracking of the skin, Symptoms/injuries after eye contact May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

## **SECTION 12: Ecological information**

tz.i. ioxicity		and the second of the second o
Ecology - general	: May cause long-term	adverse effects in the aquatic environr

09/20/2018 EN (English) 4/5



## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

LC50 fish 1 2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

### 12.2. Persistence and degradability

Palmer Mirro-Mastic ®
Persistence and degradability Not established.

#### 12.3. Bioaccumulative potential

Palmer Mirro-Mastic ®

Bioaccumulative potential Not established.

#### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

## **SECTION 14: Transport information**

#### Department of Transportation (DOT)

In accordance with DOT

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (Petroleum distillates)

Class (DOT) : 3
Packing group (DOT) : III

Additional Information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### 15.2. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## **SECTION 16: Other information**

 Date of issue
 : 06/07/2018

 Revision date
 : 09/20/2018

 Version
 : 3.1

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

