BENOX C-50



Distributed in Canada by: Distribué au Canada par:

Polynt Composites Canada Inc. 29, Regan Road Brampton Ontario L7A 1B2 Tel: (905)495-0606

Prairies: (204)668-4900 B.C. Tel: (604) 937-2663 Atl. Canada:(902)745-2855 Québec: (819) 477-4516 No d'urgence 24 heures: Emergency number 24 hours: CANUTEC: 1 888 226-8832

Version 2.0

Revision Date: 05/11/2018

SDS Number: 6000000000000

Print Date: 05/11/2018

SECTION 1. IDENTIFICATION

Product name

BENOX C-50

Manufacturer or supplier's details

Company name of supplier

: United Initiators, Inc.

Address

555 Garden Street Elvria OH 44035

Telephone

+1-440-323-3112

Telefax

+1-440-323-2659

Emergency telephone

CHEMTREC US (24h):

+1-800-424-9300

CHEMTREC WORLD (24h):

+1-703-527-3887

E-mail address of person

responsible for the SDS

cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use

Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Organic peroxides

Type D

Combustible dust

Category 1

Eye irritation

Category 2B

Skin sensitization

Category 1

Reproductive toxicity

Category 2

Acute aquatic toxicity

Category 1

Chronic aquatic toxicity

Category 1

GHS label elements

Hazard pictograms

> &

(!)



Signal Word

Danger

Hazard Statements

H242 Heating may cause a fire.

May form combustible dust concentrations in air.

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 60000000000000

Print Date: 05/11/2018

H317 May cause an allergic skin reaction.

H320 Causes eye irritation.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P234 Keep only in original packaging.

P240 Ground and bond container and receiving equipment. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

P410 Protect from sunlight.

P411 Store at temperatures not exceeding < 30 °C/ < 86 °F.

P420 Store separately.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

BENOX C-50



Version 2.0

Revision Date:

05/11/2018

SDS Number: 600000000300 Print Date: 05/11/2018

Substance / Mixture

Mixture

Chemical nature

Organic Peroxide Solid mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)	
Dicyclohexyl phthalate	84-61-7	>= 50 - < 55	
Dibenzoyl peroxide	94-36-0	>= 45 - < 50	

SECTION 4. FIRST AID MEASURES

General advice

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended. Call a physician immediately.

If inhaled

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician. If breathed in, move person into fresh air.

In case of skin contact

In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes. If symptoms persist, call a physician.

In case of eye contact

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed

Keep respiratory tract clear.

Call a physician immediately.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes eye irritation.

Suspected of damaging fertility.

Protection of first-aiders

First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician

Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 600000000300 Print Date: 05/11/2018

Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

The product burns violently. Flash back possible over considerable distance.

Vapors may form explosive mixtures with air.

The product will float on water and can be reignited on surface

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

Remove undamaged containers from fire area if it is safe to do

Use water spray to cool unopened containers.

Further information

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

Follow safe handling advice and personal protective

equipment recommendations.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

Contact with incompatible substances can cause

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 6000000000300

Print Date: 05/11/2018

containment and cleaning up

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures

See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on protection against fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from combustible material.

Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Protect from contamination.

Conditions for safe storage

Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

BENOX C-50



Version

2.0

Revision Date:

05/11/2018

SDS Number: 600000000300 Print Date: 05/11/2018

Materials to avoid

Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- : < 30 °C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of	Control parame- ters / Permissible concentration	Basis
Dib annual maravida	94-36-0	exposure) TWA	5 mg/m3	CA AB OEL
Dibenzoyl peroxide	94-30-0	TWA	5 mg/m3	CA BC OEL
		TWAEV	5 mg/m3	CA QC OEL
		TWA	5 mg/m3	ACGIH

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection

In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type

Filter type P

Hand protection

Material Break through time butyl-rubber >= 480 min

Glove thickness

0.5 mm

Remarks

Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous

substance and specific to place of work.

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove Wash hands before breaks and at the

end of workday.

Eye protection

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection

Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

potential.

Hygiene measures

Keep away from food and drink.

When using do not eat or drink.

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

 Print Date: 05/11/2018

When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

powder

Color

white

Odor

aromatic

рΗ

No data available

Melting point/range

Decomposition: Decomposes below the melting point.

Boiling point/boiling range

Not applicable

Flash point

Not applicable

Flammability (solid, gas)

Not applicable

Upper explosion limit

No data available

Lower explosion limit

No data available

Vapor pressure

No data available

Density

No data available

Solubility(ies)

Water solubility

insoluble

Solubility in other solvents

Solvent: Phthalates Description: soluble

Self-Accelerating decomposi-

tion temperature (SADT)

60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic

Not applicable

Viscosity, kinematic

No data available

Explosive properties

: Not explosive

Oxidizing properties

The substance or mixture is not classified as oxidizing.

Organic peroxide

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 60000000300 Print Date: 05/11/2018

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under recommended storage conditions.

tions

Possibility of hazardous reac- : Dust may form explosive mixture in air.

Conditions to avoid

Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks. Avoid confinement.

Incompatible materials

Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Ingredients:

Dicyclohexyl phthalate:

Acute oral toxicity

LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity

LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Dibenzoyl peroxide:

Acute oral toxicity

LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity

: LC50 (Rat): > 24.3 mg/l

Exposure time: 4 h Test atmosphere: vapor

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity

Remarks: No data available

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

 Print Date: 05/11/2018

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Ingredients:

Dicyclohexyl phthalate:

Result: No skin irritation

Dibenzoyl peroxide:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Product:

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Ingredients:

Dicyclohexyl phthalate:

Result: No eye irritation

Dibenzoyl peroxide:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks: Causes sensitization.

Ingredients:

Dicyclohexyl phthalate:

Routes of exposure: Skin contact

Species: Mouse

Result: May cause sensitization by skin contact.

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 6000000000300

Print Date: 05/11/2018

Dibenzoyl peroxide:

Routes of exposure: Skin contact

Species: Mouse

Method: Local lymph node assay (LLNA) Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Dicyclohexyl phthalate:

Genotoxicity in vitro

Result: negative

Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo

Remarks: No data available

Dibenzoyl peroxide:

Genotoxicity in vitro

Result: negative

Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo

: Result: negative

Remarks: In vivo tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

Ingredients:

Dicyclohexyl phthalate:

Remarks: This information is not available.

Dibenzoyl peroxide:

Remarks: Not classified due to data which are conclusive although insufficient for classification.

Reproductive toxicity

Suspected of damaging fertility.

Ingredients:

Dicyclohexyl phthalate:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Dibenzoyl peroxide:

Effects on fertility

Species: Rat, male

Application Route: Oral

General Toxicity Parent: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, female Application Route: Oral

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 600000000300 Print Date: 05/11/2018

General Toxicity Parent: NOAEL: 500 mg/kg body weight

Method: OECD Test Guideline 422

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility.

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Ingredients:

Dibenzoyl peroxide:

Routes of exposure: Ingestion

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Dibenzoyl peroxide:

Routes of exposure: Ingestion

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Ingredients:

Dicyclohexyl phthalate:

Species: Rat NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 90 d

Method: OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Ingredients:

DibenzovI peroxide:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 60000000000000

Print Date: 05/11/2018

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Dicyclohexyl phthalate:

Toxicity to fish LC50 (Oryzias latipes (Orange-red killifish)): > 2 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 2 mg/l

Exposure time: 48 h

Remarks: No toxicity at the limit of solubility.

Toxicity to algae ErC50 (Pseudokirchneriella subcapitata (green algae)): > 2

mg/l

Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.181 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms

NOEC: > 100 mg/l Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Dibenzoyl peroxide:

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.06

mg/

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

10

Toxicity to daphnia and other : aquatic invertebrates (Chron-

EC10 (Daphnia magna (Water flea)): 0.001 mg/l

Exposure time: 21 d

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 60000000000000

Print Date: 05/11/2018

ic toxicity)

Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

10

toxicity)

Toxicity to microorganisms

EC50 (Bacteria): 35 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity

Very toxic to aquatic life.

Chronic aquatic toxicity

Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Ingredients:

Dicyclohexyl phthalate:

Biodegradability

Result: Readily biodegradable.

Dibenzoyl peroxide:

Biodegradability

Result: Inherently biodegradable.

Bioaccumulative potential

Ingredients:

Dicyclohexyl phthalate:

Partition coefficient: n-

octanol/water

log Pow: 4.82 (25 °C)

Dibenzoyl peroxide:

Partition coefficient: n-

log Pow: 3.2 (20 °C)

octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

The product should not be allowed to enter drains, water

courses or the soil.

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 60000000300 Print Date: 05/11/2018

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging

Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum-

Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number

Proper shipping name

: UN 3106

ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class

5.2

Packing group

Not assigned by regulation

Labels

5.2

IATA-DGR

UN/ID No.

UN 3106

Proper shipping name

Organic peroxide type D, solid

(Dibenzoyl peroxide)

Class

5.2

Packing group

Not assigned by regulation

Labels

Organic Peroxides, Keep Away From Heat

Packing instruction (cargo

aircraft)

Packing instruction (passen-

570

ger aircraft)

IMDG-Code

UN number

UN 3106

Proper shipping name

ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class

5.2

Packing group

Not assigned by regulation

Labels

5.2

EmS Code Marine pollutant F-J. S-R yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number

UN 3106

Proper shipping name

ORGANIC PEROXIDE TYPE D, SOLID

(DIBENZOYL PEROXIDE)

Class

5.2

Packing group Labels

Ш 5.2

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

 Print Date: 05/11/2018

ERG Code
Marine pollutant

145 yes

SECTION 15. REGULATORY INFORMATION

NPRI Ingredients

: Dibenzoyl peroxide

The ingredients of this product are reported in the following inventories:

DSL (CA)

All components of this product are on the Canadian DSL

AICS (AU)

: On the inventory, or in compliance with the inventory

NZIoC (NZ)

: On the inventory, or in compliance with the inventory

ENCS (JP)

On the inventory, or in compliance with the inventory

ISHL (JP)

On the inventory, or in compliance with the inventory

KECI (KR)

: On the inventory, or in compliance with the inventory

PICCS (PH)

On the inventory, or in compliance with the inventory

IECSC (CN)

On the inventory, or in compliance with the inventory

TCSI (TW)

: On the inventory, or in compliance with the inventory

TSCA (US)

: On TSCA Inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;

BENOX C-50



Version 2.0

Revision Date: 05/11/2018

SDS Number: 6000000000000

Print Date: 05/11/2018

NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date

05/11/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / Z8