


# MATERIAL SAFETY DATA SHEET

## Klean-Strip KS Pro Paint Thinner

Page: 1

HEALTH		1
FLAMMABILITY	0	
PHYSICAL HAZ.	0	
PPE	C	



Printed: 12/31/2008  
Revision: 11/20/2008  
Supersedes Revision: 03/06/2008  
Date Created: 11/09/2005

### 1. Product and Company Identification

**Product Code:** 1691.3  
**Product Name:** Klean-Strip KS Pro Paint Thinner  
**Reference #:** 1691.3  
**Manufacturer Information**  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Web site address:** www.wmbarr.com  
**Preparer Name:** W.M. Barr and Company, Inc. (901)775-0100  
**Synonyms**  
GKKP94407, GKKPDP

### 2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA TWA	ACGIH TLV	Other Limits
1. Hydrotreated light distillate (petroleum)	64742-47-8	30.0 -40.0 %	200 ppm	200 mg/m3	No data.
Hazardous Components (Chemical Name)	CAS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Hydrotreated light distillate (petroleum)	64742-47-8	500 ppm/(10min)	300 ppm	No data.	No data.

### 3. Hazards Identification

#### Emergency Overview

Danger! Harmful or Fatal If Swallowed.

#### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

#### Potential Health Effects (Acute and Chronic)

The following health hazards are associated with the hazardous ingredients listed in Section 2.  
Composition/Information on Ingredients.

#### Inhalation Acute Exposure Effects:

Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause dizziness; headache; watering of eyes; eye irritation; weakness; nausea; muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions; unconsciousness; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

#### Skin Contact Acute Exposure Effects:

This material can cause mild, transient skin irritation with short-term exposure. Symptoms include redness, itching, and burning of the skin. Repeated or prolonged skin contact can produce moderate irritation.

#### Eye Contact Acute Exposure Effects:

This material can cause mild eye irritation. Symptoms include stinging, watering, redness, and swelling.

#### Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. If swallowed, this material may irritate the mucous membranes of the mouth,

# MATERIAL SAFETY DATA SHEET

## Klean-Strip KS Pro Paint Thinner

Page: 2

Printed: 12/31/2008

Revision: 11/20/2008

Supersedes Revision: 03/06/2008

throat, and esophagus. It can be readily absorbed by the stomach and intestinal tract. Symptoms include a burning sensation of the mouth and esophagus, nausea, vomiting, dizziness, staggering gait, drowsiness, loss of consciousness, and delirium, as well as additional central nervous system effects. There is a danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

### Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal. Prolonged or repeated contact may cause dermatitis. May cause jaundice; bone marrow damage; liver damage; anemia; and skin irritation.

### Signs and Symptoms Of Exposure

Inhalation, ingestion, and dermal are possible routes of exposure. See Health Hazards for signs and symptoms of exposure.

### Medical Conditions Generally Aggravated By Exposure

Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

## 4. First Aid Measures

### Emergency and First Aid Procedures

#### Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

#### Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

#### Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

#### Ingestion:

Do not induce vomiting. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Seek medical attention immediately. Call your local poison control center, hospital emergency room or physician immediately for further instructions.

### Note to Physician

A component of this product sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material.

Administration of sympathomimetic drugs should be avoided.

## 5. Fire Fighting Measures

**Flash Pt:** > 200.00 F Method Used: TAG Closed Cup

**Explosive Limits:** LEL: N.E. UEL: N.E.

### Fire Fighting Instructions

This material does not flash to boiling.

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

### Flammable Properties and Hazards

No flash to boiling.

### Extinguishing Media

Use carbon dioxide, dry powder, foam, or water spray.

**Unsuitable Extinguishing Media**

None known.

## 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled**

Clean up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering.

Small spills:

Take up with sand, earth or other noncombustible absorbent material and place in a metal or plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

Waste Disposal:

Dispose in accordance with applicable local, state and federal regulations.

## 7. Handling and Storage

**Precautions To Be Taken in Handling**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

**Precautions To Be Taken in Storing**

When stored for an extended period of time, the product may separate into two layers with the hazardous ingredient(s) on the top layer. Before use, mix the product by making sure the container is tightly closed and gently shaking the container to agitate the two layers back into solution.

Protect from freezing.

Keep container tightly closed when not in use.

Store in a cool, dry place.

Do not store near flames or at elevated temperatures.

## 8. Exposure Controls/Personal Protection

**Respiratory Equipment (Specify Type)**

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

**Eye Protection**

Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**Protective Gloves**

For OSHA controlled work place and other regular users, wear impermeable gloves to prevent skin contact. Gloves contaminated with product should be discarded.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip KS Pro Paint Thinner

Page: 4

Printed: 12/31/2008

Revision: 11/20/2008

Supersedes Revision: 03/06/2008

For occasional use, wear impermeable gloves to prevent extended or repeated contact with the skin.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

### Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open windows and doors if needed to provide fresh air. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

### Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing of the eyes and skin. Wash hands thoroughly after use. Do not eat, drink, or smoke in the work area. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas	[ X ] Liquid	[ ] Solid
<b>Melting Point:</b>	0.00 C		
<b>Boiling Point:</b>	> 100.00 C		
<b>Autoignition Pt:</b>	No data.		
<b>Flash Pt:</b>	> 200.00 F Method Used: TAG Closed Cup		
<b>Explosive Limits:</b>	LEL: N.E. UEL: N.E.		
<b>Specific Gravity (Water = 1):</b>	0.890 - 0.931		
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.		
<b>Vapor Density (vs. Air = 1):</b>	> 1		
<b>Evaporation Rate (vs Butyl Acetate=1):</b>	< 1		
<b>Solubility in Water:</b>	65 %		
<b>Percent Volatile:</b>	> 99.0 % by weight.		
<b>VOC / Volume:</b>	326.0000 G/L		
<b>Viscosity:</b>	50 at 77.0 F		
<b>Corrosion Rate:</b>	No data.		
<b>pH:</b>	Neutral		
<b>Appearance and Odor</b>			

Opaque, milky white, thin emulsion with a light petroleum distillate odor.

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

### Conditions To Avoid - Instability

No data available.

### Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents.

### Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Will occur [ ] Will not occur [ X ]

### Conditions To Avoid - Hazardous Polymerization

No data available.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip KS Pro Paint Thinner

Page: 5  
Printed: 12/31/2008  
Revision: 11/20/2008  
Supersedes Revision: 03/06/2008

### 11. Toxicological Information

No data available.

#### Carcinogenicity/Other Information

No data available.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Hydrotreated light distillate (petroleum)	64742-47-8	n.a.	n.a.	A4	n.a.
<b>Carcinogenicity:</b>	NTP? No	IARC Monographs? No	OSHA Regulated? No		

### 12. Ecological Information

No data available.

### 13. Disposal Considerations

#### Waste Disposal Method

Dispose in accordance with federal, state, and local regulations.

### 14. Transport Information

#### LAND TRANSPORT (US DOT)

##### DOT Proper Shipping Name

Paint Related Material, Not Regulated by D.O.T.

##### Additional Transport Information

For DOT information, contact W.M. Barr Technical Services.

### 15. Regulatory Information

#### US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	No	No

#### SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

<b>Sec.302:</b>	EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.
<b>Sec.304:</b>	EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.
<b>Sec.313:</b>	EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.
<b>Sec.110:</b>	EPA SARA 110 Superfund Site Priority Contaminant List

#### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

[X] Yes [ ] No Acute (immediate) Health Hazard  
[X] Yes [ ] No Chronic (delayed) Health Hazard  
[ ] Yes [X] No Fire Hazard  
[ ] Yes [X] No Sudden Release of Pressure Hazard  
[ ] Yes [X] No Reactive Hazard

### 16. Other Information

#### Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.