

Material Safety Data Sheet

Print Date 14-Feb-2012

Revision Date 14-Feb-2012

Revision Number 3

1. PRODUCT AND COMPANY IDENTIFICATION

Common name SERIES 90-97 PART A
Product code F090-0097A
Trade name TNEME-ZINC REDDISH GRAY
Product Class POLYMERIC DIISOCYANATE PAINT

Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

FLAMMABLE LIQUID AND VAPOR
HARMFUL IF INHALED
MAY CAUSE LUNG INJURY
MAY CAUSE ALLERGIC RESPIRATORY REACTION; EFFECTS MAY BE PERMANENT
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT
HARMFUL OR FATAL IF SWALLOWED
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes Moderately irritating to the eyes. Risk of serious damage to eyes.
Skin Irritating to skin. May cause sensitization by skin contact.
Inhalation Irritating to respiratory system. May cause allergic respiratory reaction. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Ingestion May be harmful if swallowed.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Liver disorders. Skin disorders. Respiratory disorders. Kidney disorders.

Interactive effects	Use of alcoholic beverages may enhance toxic effects.
Potential environmental effects	See Section 12 for additional Ecological Information.
Target Organ Effects	Central nervous system, Gastrointestinal tract, Eyes, Liver, Lungs, Respiratory system, Skin, Blood, Kidney

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	-	30 - 60
XYLENE	1330-20-7	30 - 60
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	5 - 10
ETHYL BENZENE	100-41-4	5 - 10
MICA (RESPIRABLE DUST)	12001-26-2	1 - 5
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	1 - 5
IRON OXIDE FUME	1309-37-1	1 - 5
AMORPHOUS SILICA	7631-86-9	1 - 5
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flammable properties	Flammable.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO2) - Foam - Dry chemical
Hazardous decomposition products	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Hydrogen cyanide. Isocyanates.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other information	Not applicable

7. HANDLING AND STORAGE

Handling

Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Close container after each use. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
XYLENE	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	TWA: 0.005 ppm	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	TWA: 0.005 ppm TWA: 0.051 mg/m ³	TWA: 0.005 ppm CEV: 0.02 ppm	TWA: 0.02 ppm TWA: 0.2 mg/m ³ TWA: 0.005 ppm TWA: 0.051 mg/m ³
ETHYL BENZENE	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
MICA (RESPIRABLE DUST)	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
IRON OXIDE FUME	TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³
AMORPHOUS SILICA		TWA: 6 mg/m ³			
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³

Engineering measures Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection Lightweight protective clothing, Apron, Impervious gloves
Eye/face protection Safety glasses with side-shields

Respiratory protection

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	26 °C / 78.0 °F
Boiling range	135 - 142.000 °C / 275.0 - 288.0 °F
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	1.07993 g/cm3
Density	8.98663 lbs/gal
Volatile organic compounds (VOC) content	3.827 lbs/gal
Volatile by weight	42.5790 %
Volatile by volume	52.7651 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to avoid	Heat, flames and sparks. Amines.
Incompatible products	Strong oxidizing agents. Water, alcohols, amines, strong bases, metal components, surface active materials. Acids.	Possibility of hazardous reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER			490 mg/m ³ , 4h (rat)
XYLENE	4300 mg/kg (Rat)	1700 mg/kg (Rabbit)	47635 mg/L (Rat) 4 h 5000 ppm (Rat) 4 h
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	9200 mg/kg (Rat)		
ETHYL BENZENE	3500 mg/kg (Rat)	15354 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		
IRON OXIDE FUME	10000 mg/kg (Rat)		
AMORPHOUS SILICA	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.2 mg/L (Rat) 1 h
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		

Irritation No information available
Corrosivity No information available.
Sensitization No information available.

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA	Mexico
ETHYL BENZENE	A3	Group 2B		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

Mutagenicity No information available.
Reproductive effects No information available.
Developmental effects No information available.
Teratogenicity No information available.
Target Organ Effects Central nervous system, Gastrointestinal tract, Eyes, Liver, Lungs, Respiratory system, Skin, Blood, Kidney.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
XYLENE		LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50= 13.4 mg/L Pimephales promelas 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h	EC50 = 0.0084 mg/L 24 h	LC50 = 0.6 mg/L 48 h EC50 = 3.82 mg/L 48 h
ETHYL BENZENE	EC50 = 4.6 mg/L 72 h EC50 > 438 mg/L 96 h EC50 2.6 - 11.3 mg/L 72 h EC50 1.7 - 7.6 mg/L 96 h	LC50 11.0 - 18.0 mg/L Oncorhynchus mykiss 96 h LC50 7.55 - 11 mg/L Pimephales promelas 96 h LC50 9.1 - 15.6 mg/L Pimephales promelas 96 h LC50= 32 mg/L Lepomis macrochirus 96 h LC50= 4.2 mg/L Oncorhynchus mykiss 96 h LC50= 9.6 mg/L Poecilia reticulata 96 h	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 1.8 - 2.4 mg/L 48 h
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Does not Comply
AICS	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
XYLENE	
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	
ETHYL BENZENE	

United States of America Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
XYLENE	1330-20-7	30 - 60	1.0
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	5 - 10	1.0
ETHYL BENZENE	100-41-4	5 - 10	0.1

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	yes
Acute Health Hazard	yes
Fire Hazard	yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

XYLENE 1330-20-7 (30 - 60)	100 lb			X
ETHYL BENZENE 100-41-4 (5 - 10)	1000 lb	X	X	X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
XYLENE	100 lb	
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	5000 lb	
ETHYL BENZENE	1000 lb	

United States of America State Regulations

California Prop. 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
ETHYL BENZENE	100-41-4	Carcinogen
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
XYLENE	X	X	X	X	
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	X	X	X	X	
ETHYL BENZENE	X	X	X	X	
MICA (RESPIRABLE DUST)	X	X	X		
CRYSTALLINE SILICA (QUARTZ)	X	X	X		
IRON OXIDE FUME	X	X	X		
AMORPHOUS SILICA	X	X	X		
CRYSTALLINE SILICA (QUARTZ)	X	X	X		

Other international regulations

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification

B2 Flammable liquid
 D2A Very toxic materials



Component	NPRI
XYLENE	Part 1, Group 1 Substance; Part 5 Substance
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	Part 1, Group 1 Substance
ETHYL BENZENE	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date 14-Feb-2012

Revision Note No information available


HMIS (Hazardous Material Information System) **Health** 3* **Flammability** 3 **Reactivity** 2

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Print Date 18-Apr-2011

Revision Date 18-Apr-2011

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Common name	SERIES 90-97 PART B
Product code	F090-0097B
Trade name	TNEME-ZINC ZINC PIGMENT
Product Class	ZINC METAL PIGMENT
Manufacturer	TNEMEC Company, Inc. 123 West 23rd Avenue North Kansas City, MO 64116-3064 816-474-3400
Emergency telephone	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

HARMFUL BY INHALATION.
MAY CAUSE HEADACHE AND DIZZINESS.
MAY CAUSE FLU-LIKE SYMPTOMS.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Inhalation

Acute effects

Eyes

May cause slight irritation

Skin

Substance may cause slight skin irritation

Inhalation

May cause irritation of respiratory tract. Inhalation of metallic zinc dust may result in symptoms known as metal fume fever. Symptoms include chills, fever, muscular pain, nausea and vomiting.

Ingestion

Gastrointestinal discomfort.

Chronic effects

Avoid repeated exposure.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions No information available

Interactive effects No information available

Potential environmental effects See Section 12 for additional Ecological Information

Target Organ Effects Respiratory system

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
ZINC	7440-66-6	60 - 100
ZINC OXIDE	1314-13-2	1 - 5

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties	No information available
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do NOT use water jet. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous decomposition products	Zinc oxide fume.
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	Shovel or sweep up.
Other information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Keep in a dry place. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
ZINC OXIDE	: 2 mg/m ³ TWA (respirable fraction) : 10 mg/m ³ STEL (respirable fraction)	: 5 mg/m ³ TWA (fume); 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) : 10 mg/m ³ STEL (fume) : 5 mg/m ³ TWA (fume); 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	TWA: 5 mg/m ³ TWAEV (fume); 10 mg/m ³ TWAEV (total dust, containing no asbestos and less than 1% crystalline silica) STEL: 10 mg/m ³ STEV (fume)	TWA: 2 mg/m ³ TWA (respirable) STEL: 10 mg/m ³ STEL (respirable)	: 5 mg/m ³ TWA (fume); 10 mg/m ³ TWA (dust) : 10 mg/m ³ STEL (fume)

Engineering measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face protection

Tightly fitting safety goggles

Respiratory protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	Not applicable
Boiling range	No information available
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	7.06595 g/cm ³
Density	58.79932 lbs/gal
Volatile organic compounds (VOC) content	.000 lbs/gal
Volatile by weight	.0000 %
Volatile by volume	.0000 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to avoid	Heat, flames and sparks.
Incompatible products	Strong oxidizing agents. Bases. Acids. Water. Product may release hydrogen.	Possibility of hazardous reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute toxicity

11. TOXICOLOGICAL INFORMATION

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ZINC OXIDE	5000 mg/kg (Rat)		

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenicity No information available
Reproductive effects No information available
Developmental effects No information available
Teratogenicity No information available
Target Organ Effects Respiratory system.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
ZINC	EC50 0.11 - 0.271 mg/L 96 h EC50 0.09 - 0.125 mg/L 72 h	LC50 0.211-0.269 mg/L Pimephales promelas 96 h LC50 2.16-3.05 mg/L Pimephales promelas 96 h LC50= 0.24 mg/L Oncorhynchus mykiss 96 h LC50= 0.41 mg/L Oncorhynchus mykiss 96 h LC50= 0.45 mg/L Cyprinus carpio 96 h LC50= 0.59 mg/L Oncorhynchus mykiss 96 h LC50= 2.66 mg/L Pimephales promelas 96 h LC50= 3.5 mg/L Lepomis macrochirus 96 h LC50= 30 mg/L Cyprinus carpio 96 h LC50= 7.8 mg/L Cyprinus carpio 96 h		EC50 0.139 - 0.908 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNAMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name ZINC PIGMENT

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Complies
AICS	Complies

United States of America Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC	7440-66-6	60 - 100	1.0 % de minimis concentration (Chemical Category N982) 1.0 % de minimis concentration (dust or fume only)
ZINC OXIDE	1314-13-2	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	no
Acute Health Hazard	yes
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC		X	X	
ZINC OXIDE		X		

CERCLA

United States of America State Regulations

California Prop. 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ZINC	X	X	X		X
ZINC OXIDE	X	X	X		X

Other international regulations

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification
 Non-controlled

Component	NPRI
ZINC	Part 1, Group 1 Substance

Legend
 NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date 18-Apr-2011

Revision Note No information available

HMIS (Hazardous Material Information System) Health 2 Flammability 1 Reactivity 1

Disclaimer
 For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS