MATERIAL SAFETY DATA SHEETS

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Uni Filter, Inc.

Emergency Phone No: 800-535-5053

Address: 1468 S. Manhattan Ave.

INFOTRAC

City, State, and Zip Code: Fullerton, CA 92831

Product Category (Acrosol):Lubricant

Product Name: Filter Oil

UFF-100

Date: 3-01-2001 Rev. Date: 6-26-2001

Lab No.: ALP1029-04&07

HMIS CODE: HEALTH ----- (2)

FLAMMABILITY----(4) REACTIVITY----(0)

PERSONAL PROTECTION----(G)

SECTION II – HAZARDOUS INGREDIENTS

INGREDIENT	%	OSHA PEL	TLV PPM	TLV MG/M3	LEL	CAS NUMBER
Aliphatic Petroleum Dist.	65-70	5.0 mg/m3		5.0		64742-54-7
Propane	15-20		1000			674-98-6
n-Butane	15-20		600			106-97-6
					1.	
		1	ĺ			
						The state of the s
Company of the control of the contro			T	1		

Carcinogenicity: THIS PRODUCT IS NOT CONSIDERED TO BE A CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER, THE OCCUPATIONAL SAFTY AND HEALTH ADMINISTRATION, OR NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY & HEALTH

SARA:

These ingredients are subject to SARA TITLE III Section 313 reporting for superfund

Amendments and Reauthorization Act of 1986 and CFR 40 part 372.

Manufacturer's Name: Uni Filter, Inc. Lab No.: ALP1029-04&07 (Page 2)

SARA: Acrosol products are subject to SARA TITLE III Section 312 reporting for Superfund

Amendments and Reauthorization Act of 1986 and CFR 40 part 372.

Pursuant to Proposition 65: CERTAIN RAW MATERIALS USED IN MAKING THIS PRODUCT MAY CONTAIN SMALL AMOUNTS OF MATERIALS AS IMPURITIES WHICH ARE REGULATED BY PROPOSITION 65. SEE SECTION IX.

SECTION III - PHYSICAL DATA

Boiling Range: Propellant Bellow 0.0° F Vapor Density:

Evaporation Rate Faster than ETHER Percent Volatile Weight Per

*Propellants By Weight: Gallon: 7.08

Maximum Incremental Reactivity:

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

Category: CONSUMMER COMMODITY Flash Point: PROPELLANT BELOW 20° F LEL: SEE SECTION II

ORM-D (T.O.C.) Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Fire and Explosion Hazards: DO NOT SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING.

Special Fire Fighting Procedures: WATER MAY BE INEFFECTIVE - WATER MAY BE USED TO KEEP FIRE CONTAINERS COOL.

SECTION V – HEALTH HAZARD DATA

Threshold Limit Value: (SEE SECTION II HAZARDOUS INGREDIENTS)

Effects of Overexposure: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. OVER-EXPOSURE MAY RESULT IN LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. HARMFUL OR FATAL IF SWALLOWED.

Chronic: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE, ALSO KIDNEY AND LIVER DAMAGE.

Medical Conditions Prone to Aggravation by Exposure: NONE ESTABLISHED.

Manufacturer's Name: Uni Filter, Inc.

Lab No.: ALP1029-04&07

(Page 3)

Routes of Entry:

Inhalation:

YES

Skin: YES

Ingestion:

YES

Emergency and First Aid Procedures:

Breathing:

REMOVE PATIENT TO FRESH AIR,

Eves:

FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

Skin:

WASH WITH SOAP AND WATER.

Swallowing:

CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

SECTION VI – REACTIVITY DATA

Stability:

STABLE

Conditions to avoid:

DO NOT STORE ABOVE 120° F

Incompatibility: (NONE)

Hazardous Decomposition products: Burning produces CARBON MONOXIDE AND CARBON DIOXIDE.

Hazardous Polymerization: WILL NOT OCCUR

SECTION VII – SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:

REMOVE ALL SOURCES OF IGNITION.

VENTILATE, AVOID BREATHING VAPORS AND REMOVE WITH INERT ABSORBENT

Waste disposal method:

DO NOT INCINERATE - DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND

LOCAL REGULATIONS REGARDING POLLUTION.

SECTION VIII – SPECIAL PROTECTION INFORMATION

Respiratory Protection:

AVOID BREATHING OF VAPOR OR SPRAY MIST.

IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE

LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR

PROTECTION AGAINST MATERIALS IN SECTION II.

WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR APPROVED BY NIOSH/MSHA FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT, OR THE ABRASIVE. THE APPLICABLE LIMITS FOR NUISANCE DUSTS ARE ACGIHTLV 10 mg/m3

(TOTAL DUST), OSHA PEL 15 mg/m3 (TOTAL DUST), 5 mg/m3 RESPIRABLE

FRACTION).

Manufacturer's Name: Uni Filter, Inc.

Lab No.: ALP1029-04&07

(Page 4)

Ventilation:

PROVIDE LOCAL EXHAUST VENTILATION IN VOLUME AND PATIERN TO KEEP

TLV OF ALL HAZARDOUS INGREDIENTS IN SECTION II BELOW ACCEPTABLE

LIMIT, AND LEL IN SECTION II BELOW STATED LIMIT.

Skin Protective:

Protective gloves and clothing are recommended when prolonged contact

with the concentrated material may occur.

Eye Protection:

FOR PROLONGED USE IN CLOSE QUARTERS RECOMMEND SAFETY GLASSES

WITH UNPERFORTATED SIDESHIELDS.

Other Protective Equipment:

SECTION IX-SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing:

DO NOT STORE ABOVE 120° F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING.

Other Precautions:

KEEP AWAY FROM CHILDREN.

DO NOT PUNCTURE OR INCINERATE.

DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

Pursuant to Proposition 65:

PROPOSITION 65 APPLIES TO A LIST OF CHEMICALS NAMED BY THE GOVERNOR OF CALIFORNIA AS CARCINOGENS OR REPRODUCTIVE TOXINS. WARNING REQUIREMENTS FOR SPECIFIC CHEMICALS TAKE EFFECT ONE YEAR AFTER THEY ARE ADDED TO THE GOVERNOR'S LIST. OTHER CHEMICALS ALREADY ADDED TO THE GOVERNOR'S LIST WILL BE REQULATED LATER UNDER PROPOSITION 65.

Notice to Reader

Reasonable care has been taken in the preparation of this information, but manufacturer makes no warranty of merchantability or any other warranty, express or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.