



- NOTES:**
1. Do not scale drawing
 2. Unless otherwise stated, all dimensions are in meters.
 3. Minimum height of entrances and exits

Class I/II	2.0m
Class IV	2.4m
Class VII	3.2m.
Class I/II	2.3m.
Class I/II	2.3m
Class IV	2.4m
Class VII	3.0m.
Class I/II	3.2m
Class IV	3.6m
Class VII	4.2m.
Class I/II	2.1m
Class IV	2.4m
Class VII	3.2m.
Class IV	3.8m
Class VII	4.8m.
 4. Minimum bay width of
 5. Minimum headroom over the bay
 6. Minimum headroom over the lift

measured from the platform surface when fully lowered.
The headroom must extend 0.5m of the non drive on end of the lift, 1.0m to the drive on end of the lift, and 0.5m on each side of the outside edge of the lift platform.
 7. Brake tester standing area to be substantially level ($\pm 12\text{mm}$).
 8. Headlight beam tester rails to be level to $\pm 2\text{mm}$.
 9. Headlight tester standing area to be level to $\pm 6\text{mm}$.
 10. Minimum clearance between lift post and wall of 0.6m.
 11. All dimensions shown are absolute minimums to be achieved.
 12. This layout is subject to VOSA approval, and therefore no civil work should be commenced until written approval has been obtained.
 13. The drawing must not be scaled for civil work. Recess drawings are available for the vehicle lift and brake tester. VOSA require all MOT vehicle lifts to be load tested.
 14. Provided a suitable vehicle with a current weigh bridge certificate is available during installation, GE-TECH will carry out the necessary thorough examination and issue certification FOC.

Rev	Revision note	Date	By
-	-	-	-

GE-TECH
GARAGE EQUIPMENT TECHNOLOGY
 PO Box 203
 Leeds
 West Yorkshire
 LS27 1BN

Telephone: 0844 8009785
 Fax: 0560 1139017
 Email: sales@getech.org.uk
 Web: getech.org.uk
 CO REG No: OCS29191

Ref	Class	By	Signed	Date	Scale	Sheet	Revision
HEADLIGHT BEAM TESTER ASSEMBLY	III	A.J.H.		16.03.2012			
GETECH						1/1	0

Customer: PO BOX 203, LEEDS, WEST YORKSHIRE, LS27 1BN

Site: GE5418L