

Name of chiller:	Plate-tube Direct Evaporative Cool Chiller		
Model:	WLSZ400CHG		
Performance:	Nominal Cooling Capacity	kW	400
	Ton of Refrigeration	Ton	114
	Nominal Input power (note 4)	kW	87
	System COP	W/W	4.60
	COP	W/W	5.08
Noise Level	Within 1 meter	dB	80
	Within 10 meters	dB	68
Power:	Max operating current	Α	200
	Power Supply	Ph/V/Hz	3/415/50
Chiller:	Refrigerant		R410A
	Refrigerant system		1
	Number of compressors		3
	Compressor brand		Danfoss
	Compressor type		Full-Hermetic Scroll
Evaporator:	Туре		Shell & Tube
	Water flow	m³/h	68.8
	Internal diameter of water pipe	mm	DN125
	Water pressure drop	kPa	≤70
Condenser:	Туре		Plate-tube direct evaporative
	Exhaust static pressure	Ра	10
	Water consumption	m³/h	0.56
	No. of fan		2
	Fan input power	kW	6
	No. of pump		1
	Input power of pump	kW	2.2

Notes:-

Weight:

Dimension:

- 1. Rated conditions for cooling operation:
 - (a) temperature of inlet/outlet chilled water: 12°C/7°C;
 - (b) Ambient dry/wet bulb temperature: 35°C/26°C

Length

Width

Height

Shipping

Operating

- 2. Temperature of supply cooling water is 30°C.
- 3. Supply cooling water pressure is 0.06~0.15 Mpa.
- 4. Nominal Input power includes power consumption of compressors, cooling water pump and condenser fan

mm

mm

kg

kg

3,480

2,300

3,150

5,700

6,500

- 5. Chiller electric supply base on maximum load.
- 6. If the chiller is installed indoor, the indoor air flow should be less than 2 m/s.
- 7. If the local water hardness is higher than 400mg/L, water softener is required.
- 8. Minimum refrigerated operating environment temperature is 15° C, or lower on request.
- 9. Chiller water flow range is 50% 130% of nominal chilled water flow in cooling mode.
- 10. Standard of chiller is GB/T 18430.1 & JB/T12323-2015
- 11. 28 °C wet bulb correction factor is 0.98
- 12. All above specifications are subject to change from to time without notice