

WISE-2410

LoRa/LoRaWAN Wireless Smart Vibration Sensor



Common Specification

Wireless Communication

 Frequency Band 	
------------------------------------	--

- Spreading Factor
- Transmit Power
- Topology
- Sensitivity
- Data Rate

General

- Power Input
- LED Indicator
- Configuration Interface Micro-B USB
- IP Class
- Mounting
- Dimension (H x D)
- Certification

Environment

- Operating Temperature -20~50°C
- Operating Humidity 10~95% RH
- Storage Temperature -25~70°C
- Storage Humidity

- 7~12 Up to 20dBm Star (LoRa/LoRaWAN) -148dB
 - 50 kbps at FSK mode EU868 21.9 kbps at SF7 mode US915

- **Features**
 - Built-in vibration and temperature sensor
 - Directly transmit vibration feature value (e.g. Velocity RMS, g peak & RMS)
 - . No power and communication wiring
 - LoRa/LoRaWAN wireless technology
 - Follow industrial standard installation
 - Compliant with ISO 10816
- IP66

Vibration Sensor

- Axis
- Frequency Range 10~1000Hz
 - ±16g
- Amplitude Range Detection type Velocity RMS, Acceleration (RMS & peak) Advanced: Kurtosis, Crest factor, Skewness, Standard deviation

X-Y-7

3200Hz

- Output Data Rate
 - Resolution
- 10 bit (all g range) Sensitivity (TYP.) 31.2mg/LSB
- Og offset(MAX.) ±150mg

Temperature Sensor

- Operating Range -20~50°C
- Resolution 12 bit
- ±2°C Accuracy

Ordering Information

Smart Vibration Sensor

WISE-2410-NA WISE-2410-EA

Wireless Smart Vibration Sensor - NA US 902-928 (MHz) Wireless Smart Vibration Sensor - EA EU 863-870 (MHz)

LoRaWAN Gateway

- WISE-6610-N100-A
- 915 MHz WISE-6610-E100-A LoRaWAN gateway supports up to 100 nodes with 868 MHz

Accessories

- 1760002647-01
- 96PD-MC534
- UNO-2000-LKAE
- Bat.Cylindrical 3.6V/2500mAh AA Li/SOCI2 Magnet base for WISE-2410 installation
- 10 sets connector lockable kit, for locking Mirco-B USB

LoRaWAN gateway supports up to 100 nodes with

All product specifications are subject to change without notice.

- EU 863-870 (MHz) US 902-928 (MHz)
- - IP66

 - CE (RED), FCC, NCC

5~95% RH

- 3.6V AA Battery *2pcs (Not included) Power, Tx
- Stud mount, Mounting pad and adhesives

- 84.7 x 48.3 mm