



1. IDENTIFICATION

Product identifier

Product Name Low VOC Low Sheen Wet Look Lacquer

Other means of identification

SDS # GST-008

Product Code GST 516

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Paint.

Details of the supplier of the safety data sheet

Manufacturer Address

GST International, Inc.
1205 Icehouse Ave.
Sparks, NV 89431
Ph: 775-829-2626
www.gstinternational.com

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America) Contract #93918

2. HAZARDS IDENTIFICATION

Appearance Liquid

Physical state Liquid

Odor Typical

Classification

This SDS was created using the criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and is compliant with the Globally Harmonized System of Labeling and Classification of Chemicals (GHS).

| | |
|--------------------------------------------------|------------|
| Serious eye damage/eye irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 2 |

Signal Word

Danger

Hazard statements

Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof equipment
 Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% |
|-------------------------------------|---------------|-----------------|
| 2-Propanone | 67-64-1 | 25-51 |
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | 8-18 |
| Butoxyethanol | 111-76-2 | 4-8 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Advice | Provide this SDS to medical personnel for treatment. |
| Eye Contact | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin Contact | Remove/take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before reuse. If skin irritation develops or persists, seek medical attention. |
| Inhalation | Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center if individual's condition declines or if symptoms persist. |
| Ingestion | Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth to an unconscious person. Immediate medical attention is required. |

Most important symptoms and effects, both acute and delayed

| | |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms | Causes serious eye irritation. Causes mild skin irritation. May cause drowsiness or dizziness. May be harmful if swallowed. Aspiration hazard: if swallowed can enter lungs and cause damage. |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|----------------------------------------------------------------|
| Notes to Physician | Provide general supportive measures and treat symptomatically. |
|---------------------------|----------------------------------------------------------------|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray or fog. Alcohol resistant foam. Dry chemical or CO₂.

Unsuitable Extinguishing Media Water jet.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Container may explode in heat or fire.

Hazardous combustion products Carbon oxides.

Explosion Data

Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Personal Precautions | Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition. |
| For Emergency Responders | Evacuate unprotected personnel from area. |

Environmental precautions

Environmental precautions Prevent runoff from entering drains, sewers or streams. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Absorb spill with inert material (e.g. dry sand or earth).

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash face, hands and any exposed skin thoroughly after handling. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use only with adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Store away from heat and incompatible materials.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| 2-Propanone 67-64-1 | STEL: 500 ppm TWA: 250 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| Butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ |

Appropriate engineering controls

Engineering Controls Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear approved safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Reference Wiley's "Quick Selection Guide to Chemical Protective Clothing". Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------------------------------|----------------------|--------------------------------|----------------|
| Physical state | Liquid | Odor | Typical |
| Appearance | Liquid | Odor Threshold | Not determined |
| Color | Not determined | | |
| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> | |
| pH | Not determined | | |
| Melting point / freezing point | Not determined | | |
| Boiling point / boiling range | Not determined | | |
| Flash point | 0 °F | | |
| Evaporation Rate | Not determined | | |
| Flammability (Solid, Gas) | Not determined | | |
| Flammability Limit in Air | | | |
| Upper flammability or explosive limits | Not determined | | |
| Lower flammability or explosive limits | Not determined | | |
| Vapor Pressure | Not determined | | |
| Vapor Density | >1 | (Air=1) | |
| Relative Density | 0.8718 | | |
| Water Solubility | Partially soluble | | |
| Solubility in other solvents | Not determined | | |
| Partition Coefficient | Not determined | | |
| Autoignition temperature | Not determined | | |
| Decomposition temperature | Not determined | | |
| Kinematic viscosity | Not determined | | |
| Dynamic Viscosity | Not determined | | |
| Explosive Properties | Not determined | | |
| Oxidizing Properties | Not determined | | |

Other information

VOC Content <100 g/l

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks. Avoid direct sunlight.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Thermal decomposition may produce oxides of carbon.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

| | |
|---------------------|----------------------------------------------------------------------------|
| Eye Contact | Causes serious eye irritation. |
| Skin Contact | Causes mild skin irritation. |
| Inhalation | May cause irritation if inhaled. |
| Ingestion | May be fatal if swallowed and enters airways. May be harmful if swallowed. |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|------------------------------------------------------|----------------------|--------------------------|------------------------------------------------|
| 2-Propanone 67-64-1 | = 5800 mg/kg (Rat) | > 15700 mg/kg (Rabbit) | = 50100 mg/m ³ (Rat) 8 h |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | > 5000 mg/kg (Rat) | > 2 mL/kg (Rabbit) | > 590 mg/m ³ (Rat) 4 h |
| Butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 435 mg/kg (Rabbit) | = 486 ppm (Rat) 4 h = 450 ppm (Rat) 4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---------------------------|-------|---------|-----|------|
| Butoxyethanol 111-76-2 | A3 | Group 3 | | |

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

STOT - single exposure May cause drowsiness or dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Oral LD50 3,400.11 mg/kg
Dermal LD50 5,118.80 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|---------------------------------------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| 2-Propanone 67-64-1 | | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 | 12600 - 12700: 48 h Daphnia magna mg/L EC50 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | 2.5: 72 h Skeletonema costatum mg/L EC50 | 41: 96 h Pimephales promelas mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.34: 96 h Oncorhynchus mykiss mg/L LC50 19: 96 h Pimephales promelas mg/L LC50 static | 0.95: 48 h Daphnia magna mg/L EC50 |
| Butoxyethanol 111-76-2 | | 2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static | 1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50 |

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

| Chemical name | Partition coefficient |
|---------------------------------------------------|-----------------------|
| 2-Propanone 67-64-1 | -0.24 |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | 6.1 |
| Butoxyethanol 111-76-2 | 0.81 |

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|------------------------|------|-----------------------------------|------------------------|------------------------|
| 2-Propanone 67-64-1 | | Included in waste stream: F039 | | U002 |

California Hazardous Waste Status

| Chemical name | California Hazardous Waste Status |
|------------------------|-----------------------------------|
| 2-Propanone 67-64-1 | Ignitable |

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for excepted quantity exception.

DOT

UN/ID No UN1263
 Proper Shipping Name Paint
 Hazard class 3
 Packing Group II

IATA

UN number UN1263
 Proper Shipping Name Paint
 Transport hazard class(es) 3
 Packing Group II

IMDG

UN number UN1263
 Proper Shipping Name Paint
 Transport hazard class(es) 3
 Packing Group II
 Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

| Chemical name | TSCA | TSCA Inventory Status | DSL/NDSL | EINECS/ELI NCS | ENCS | IECSC | KECL | PICCS | AICS |
|-------------------------------------|------|-----------------------|----------|----------------|------|-------|------|-------|------|
| 2-Propanone | X | ACTIVE | X | X | X | X | X | X | X |
| Naphtha (petroleum), heavy aromatic | X | ACTIVE | X | X | | X | X | X | X |
| Butoxyethanol | X | ACTIVE | X | X | X | X | X | X | X |

- Legend:**
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|------------------------|--------------------------|----------------|--------------------------------------------|
| 2-Propanone 67-64-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|--------------------------|----------|----------|-------------------------------|
| Butoxyethanol - 111-76-2 | 111-76-2 | 4-8 | 1.0 |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|---------------------------|------------|---------------|--------------|
| 2-Propanone 67-64-1 | X | X | X |
| Butoxyethanol 111-76-2 | X | X | X |

16. OTHER INFORMATION

NFPA

Health Hazards

Flammability

Instability

Special Hazards

Not determined

Not determined

Not determined

Not determined

HMIS

Health Hazards

Flammability

Physical hazards

Personal Protection

Not determined

Not determined

Not determined

Not determined

Issue Date: 12-May-2020
 Revision Date: 22-May-2020
 Revision Note: New product

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet