

UFO LED High Bay Light






Characteristics


- It's made of Cree SMD3030 and Sosen / LiFud LED driver for application which requires maximum performance and minimum maintenance.
- Heavy duty die-cast aluminum housing, fully sealed to be dirt and bug proof polyester power-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling.
- IP 65 waterproof protection.
- High quality polycarbonate lens with high lumen efficacy, 60 & 90 & 120 degree, 60 degree PC reflector with the solution of th
- New model design is easy for installation and maintenance.
- This high bay light fixture can get the same lumen intensity as triple HPS / HID / Metal halide for Warehouse, indoor stadium / badminton court / basketball court workshop and other lighting applications.
- Black and white shell are available.


Power	100W	150W	200W	240W	
Certification	ETL / cETL / DLC Premium				
Lumen	15000lm±5%	22500lm±5%	30000lm±5%	36000lm±5%	
Luminous Efficiency	150lm/w±5%				
Input Voltage	120-277V / 347-480V, 50-60Hz				
LED Brand	CREE				
Power Supply	LiFud / Sosen				
сст	3000-6500K				
CRI	>75Ra				
Sensor	Yes (optional)				
Beam Angle	60°/90°/20°				
Ingress protection	IP65				
Operation Temperature	(-20~45°C)				
Lamp Dimension	Ф250x182.5mm	Ф280x184.5mm	Ф320x189.5mm	Ф350x189.5mm	
Net Weight	2.2KG	3.4KG	4.4KG	5.4KG	

Installation


- 1. Hook Suspended Mounting
- 2. Surface Mounting
- 3. Conduit Suspended Mounting









Assembly Drawing




Light Distribution




60 degree



120 Degree



90 Degree



No.	Power	Carton Size (LxWxH)	G.W./Ctn	QTY/Ctn (PCS)
1	100W	12.2x12.2 x8.2 inches	6.40 lbs	1
2	150W	13.4x13.4 x 8.2 inches	8.80 lbs	1
3	200W	15.3x15.3 x 8.2 inches	10.80 lbs	1
4	240W	16.1x 16.1x 8.2 inches	12.80 lbs	1







