



Low-Bay Linear Luminaire Commercial & Industrial LED Lighting

High-efficiency low-bay linear LED luminaires designed to replace T12, T8, and T5 fluorescent fixtures. Engineered for maximum lumen output, energy savings, and fast installation.

| Model Series | Kelvin | Watts | Lumens / LPW | Dimming | DLC Product ID |
|--------------|------------|-------|--------------|---------|----------------|
| LMK418-DIM | 3500–5000K | 36W | 5780 / 161 | 0–10V | S-E6QNAT |
| LMK422-DIM | 4000–5000K | 43W | 6671 / 157 | 0–10V | S-9E6P0D |
| LMK422HO-DIM | 4000–5000K | 47W | 7461 / 160 | 0–10V | S-J03ESM |
| LMK436-DIM | 5000K | 37W | 5691 / 157 | 0–10V | S-XH0KRP |
| LMK448-DIM | 5000K | 48W | 7571 / 159 | 0–10V | S-XCGK7Q |
| LMK460-DIM | 5000K | 59W | 8507 / 146 | 0–10V | S-TNM2DT |

Key Specifications

- Input Voltage - 120–277VAC
- Dimming - 0–10VDC
- CRI - 80+
- Beam Angle - 120°
- Operating Temperature - -20 to 50°C (-4 to 122°F)
- Rated Life - >65,000 hours
- IP Rating - IP51 (Damp)
- Warranty - 7-Year Non-Prorated

Support: 1-463-259-6751