



SPARTA - MADRID Line Serisi



SPARTA 2728



SPARTA 27278



MADRID LINE 27873



QUALITY

Product Definition	ISO 2424	Tufted Loop Pile
Gauge		1/10"
No. of Tufts	ISO 1763	$\pm 173.360/m^2$
Pile Fibre	ISO 2424	100% PA SDN
Pile Weight	ISO 8543	510 gr/m ² $\pm 5\%$
Pile Height	ISO 1765	3.5 mm $\pm 5\%$
Primary Backing	ISO 2424	PA/PES non-woven-Colback
Tile Backing		Polyflex
Total Thickness	ISO 1765	5.2 mm $\pm 5\%$
Total Weight	ISO 8543	3800 gr/m ² $\pm 7,5\%$
Tile Size	EN 986	50 x 50 cm ($\pm 19,7'' \times 19,7''$)
Tiles per box		20
Use Classification	EN 1307	Heavy Contract Class 33
Abrasion		Pass
Vettermann Test	ISO 10361	Pass
Dimensional Stability	ISO 10361	Pass
Thermal Isolation		

ELEKTROSTATIC PROPERTIES

Static Loading	ISO 2424	Anti-static
Flame Properties		
Reaction to Fire	ISO 1763	
Hot Metal Nut Test	EN130501-1	Bfl-S1

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	>5.0
Rubbing, Dry	ISO 105 X12	5.0
Rubbing, Wet		5.0
Shampoo		5.0
Water	ISO 105 E01	4.0

GENERAL

Recommended Maintenance	
Pile Direction	
Laying Instructions	

Best results are obtained when cleaned with a dry shampoo method. Directional arrows are printed on the back of each tile. Best results are obtained when tiled in a staggered pattern. Tiles require no underlay, leveling, grouting or sealing and must be laid loose on a flat, dry, non-slippery floor. When tiles are laid on porous, vinyl or in other areas larger than 10 m² it is advisable to use double sided adhesive tapes on every 8th row or so.

