


HSK – Your partner for plastic welding – and bending technology

Hand welding extruder HSK28 RSX DATA /HSK28 RFX DATA



| | | |
|--|---|--|
| BASIC EXTRUDER | | |
| <ul style="list-style-type: none"> ▪ Extrusion welding from PEHD, PP, PVC* and PVDF ▪ temperature probe, location in the melt chamber ▪ rod feeding, no additional gearing ▪ Control units for actual / desired mass and air temperature and actual speed ▪ Digital recording of the welding temperature, ambient temperature, the speed and the welding times on SD Card ▪ Various welder programmed with its own SD card ▪ Pre-programmable welding and building materials on SD card ▪ Evaluated logs and charts on Excel ▪ Cold start protection ▪ Rod diameter 3,4 and 5 mm ▪ 1 pce nozzle blank included ▪ Speed control | | |
| | | *PVC with special screw |
| TECHNICAL DATA | | |
| Output | 2.8 kg/h (with PEHD rod 5 mm) | |
| Heating extruder | 700 W / air 2.200 W | |
| Drive | 1.150 W | |
| Air requirement | 300 l/min. | |
| Voltage | 230 V / 50Hz | |
| Weight | 8.5 kg | |
| Guarantee | screw and cylinder 24 months | |
| HSK28 RSX DATA (WITH HOT AIR BLOWER) | | |
| <ul style="list-style-type: none"> ▪ Works as basic extruder, without external air supply ▪ Hot air blower controlled (air quantity 300 l/min) ▪ Technical data see basic extruder ▪ Heating hot air blower 2.300 W | | |
| ADDITIONAL EQUIPMENT | | |
| <ul style="list-style-type: none"> ▪ Welding nozzles ▪ Transportation box ▪ Welding rod | <ul style="list-style-type: none"> Extruder nozzle preheating Prolongation Widen | <ul style="list-style-type: none"> Angle adaptor Air compactor |
| Technical execution subject to modifications | | |

Larry Rowold
 PLASTIC FABRICATION CONSULTANT
 1010 VERMONT AVE
 THE VILLAGES, FL 32159

[email: larowold@gmail.com](mailto:larowold@gmail.com)
 Cell phone: 630-319-3480